THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
CM	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	L	REVISED PER ECO-13-008064	13MAY13	DZ	YHM





VIEW A–A



RECOMMENDED MOUNTING HOLE PATTERN FOR .063 THK PRINTED CIRCUIT BOARD 2





1. MATERIAL: HEADER– POLYESTER UL94V–O (BLACK)
   POST– COPPER ALLOY.
2. SOLDER SIDE OF P.C. BOARD SHOWN.
3. PARTS COMPLY WITH AMP SOLDERABILITY SPEC 109–11–12.
4. THE RETENTION TABS PROVIDE A ONE–TIME INTERFERENCE FIT IN THE .078 DIAMETER BOARD HOLE FOR HEADER ASSEMBLY RETENTION DURING SOLDERING.
5. LATCH DETENT FEATURE OCCURS 2 PLACES ON EACH END (MAXIMUM OF FOUR PER PART). FOR 2 THRU 5 CIRCUIT HEADERS, LATCH FEATURE OCCURS BETWEEN EACH CIRCUIT.
6. COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
7. POST: 100% MATTE TIN PLATED.
8. UL RECOGNIZED (UR) LOGO AND CSA LOGO WILL APPEAR ON THE SIDE OF THE PART. THE AMP LOGO MAY APPEAR ON THE SIDE OR ON BOTTOM OF PART.
9. TWO SIDES OF TAPER, AS SHOWN, MUST BE PLATED. TYPICAL, BOTH ENDS.
10. TWO SIDES OF TAPER, AS SHOWN, AND TIP MAY BE UNPLATED. TYPICAL, BOTH ENDS.
11. POST: MATTE TIN–LEAD (93/7) PLATED.

LEADFREE	FINISH	L	IN	MM	NO OF POSITIONS	PART NUMBER
YES	7		1.484	37.69	14	3-644486-4
			1.384	35.15	13	3-644486-3
			1.284	32.61	12	3-644486-2
			1.184	30.07	11	3-644486-1
			1.084	27.53	10	3-644486-0
			.984	24.99	9	2-644486-9
			.884	22.45	8	2-644486-8
			.784	19.91	7	2-644486-7
			.684	17.37	6	2-644486-6
			.584	14.83	5	2-644486-5
			.484	12.29	4	2-644486-4
			.384	9.75	3	2-644486-3
			.284	7.21	2	2-644486-2
SUPERSEDED BY 3-644486-4			1.484	37.69	14	~~1-644486-4~~
SUPERSEDED BY 3-644486-3			1.384	35.15	13	~~1-644486-3~~
SUPERSEDED BY 3-644486-2			1.284	32.61	12	~~1-644486-2~~
SUPERSEDED BY 3-644486-1			1.184	30.07	11	~~1-644486-1~~
SUPERSEDED BY 3-644486-0			1.084	27.53	10	~~1-644486-0~~
SUPERSEDED BY 2-644486-9			.984	24.99	9	~~644486-9~~
SUPERSEDED BY 2-644486-8			.884	22.45	8	~~644486-8~~
SUPERSEDED BY 2-644486-7			.784	19.91	7	~~644486-7~~
SUPERSEDED BY 2-644486-6			.684	17.37	6	~~644486-6~~
SUPERSEDED BY 2-644486-5			.584	14.83	5	~~644486-5~~
SUPERSEDED BY 2-644486-4			.484	12.29	4	~~644486-4~~
SUPERSEDED BY 2-644486-3			.384	9.75	3	~~644486-3~~
SUPERSEDED BY 2-644486-2	NO	11	.284	7.21	2	~~644486-2~~

.040	1.02	.124	3.15	–	–
.030	0.76	.107	2.72	.440	11.18
.025	0.64	.100	2.54	.410	10.41
.010	0.25	.092	2.34	.313	7.95
.005	0.13	.078	1.98	.200	5.08
.003	0.08	.063	1.6	.176	4.47
.001	0.03	.062	1.57	.140	3.56
.000	0	.042	1.07	.125	3.18
IN	MM	IN	MM	IN	MM

CONVERSION TABLE

METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± .005
4 PLC ± –
ANGLES ± –

MATERIAL 1

FINISH SEE TABLE

DWN S. CARPENTER 27MAY2003
CHK D. BOSSI 28MAY2003
APVD D. BOSSI 28MAY2003
PRODUCT SPEC
APPLICATION SPEC
WEIGHT

TE Connectivity

NAME MTA–100 SHROUDED HEADER ASSEMBLY, FRICTION LOCK,STRAIGHT POST, TIN OR TIN LEAD PLATED

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-644486	–

CUSTOMER DRAWING | SCALE 10:1 | SHEET 1 OF 1 | REV L