



- DIMENSIONS ARE MAXIMUM UNLESS OTHERWISE SPECIFIED.
 - MATERIAL: HOUSING – PBT POLYESTER, COLOR: BLACK.
TERMINAL – PHOS-BRONZE PLATED WITH 1.27 μ m [.000050] MINIMUM THICK HARD GOLD IN LOCALIZED GOLD PLATE AREA AND 3.81 μ m [.000150] MINIMUM THICK MATTE TIN IN SOLDER AREA OVER 1.27 μ m [.000050] MINIMUM THICK NICKEL UNDERPLATE.
- $\triangle 3$ CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F.
 $\triangle 4$ BULK PACKAGED IN A TRAY.
 $\triangle 5$ PACKAGED 36 ASSEMBLIES PER TUBE WITH BOTH ENDS CRIMPED. SEE DETAIL A.

$\triangle 3$	8	2.80±0.25 [.110±.010]	5555167-4
$\triangle 4$	8	3.81±0.51 [.15±.02]	5555167-1
PACKAGED	TERMINALS	DIMENSION Z	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN 31AUG2007 G. ATTADIA/L.A. MAYER		TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:			
		0 PLC	± -	APVD 31AUG2007 S. FLICKINGER	
		1 PLC	± -	NAME MOD JACK ASSEMBLY, 8 POSITION LOW PROFILE, RIGHT ANGLE, KEYED, WITHOUT PANEL STOPS	
		2 PLC	± 0.13[.005]	PRODUCT SPEC 108-1163	
		3 PLC	± -	APPLICATION SPEC 114-2048	
MATERIAL SEE NOTE 2		FINISH SEE NOTE 2		WEIGHT -	RESTRICTED TO
CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1	REV B1