


LOC	DIST	REVISIONS			
		REV	DESCRIPTION	DATE	BY
DY	-	A4	REVISED PER ECO-11-005139	18APR11	RK HMR



- ① DIMENSION APPLIES WHEN ACTUATOR IS IN CLOSED POSITION.
- ② DIMENSION APPLIES WHEN ACTUATOR IS IN OPEN POSITION.
- ③ MAXIMUM ENGAGEMENT LENGTH TO CONTACT POINT.
- ④ CONTACTS: 0.002[.00008] MIN. TIN OVER 0.00127[.000050] MIN. NICKEL.
- ⑤ SOLDER TABS: 0.00127[.000050] MIN. TIN.
- ⑥ PACKAGE PER EIA 481 SPECIFICATION.
- ⑦ TOLERANCE NON-CUMULATIVE.
- ⑧ MATERIAL: CONTACT: PHOSPHOR BRONZE.
 SOLDER TABS: PHOSPHOR BRONZE.
 HOUSING: GLASS REINFORCED POLYESTER (LCP), UL 94V-0, COLOR-NATURAL.
 ACTUATOR: GLASS REINFORCED NYLON (PPA), UL 94V-0 OR GLASS REINFORCED PPS, UL 94V-0, COLOR-BLACK.

RECOMMENDED FPC LAYOUT SCALE 8:1

F	E	D	C	B	A	POS	PART NO
.50	31.00 [1.221]	37.92 [1.492]	31.18 [1.228]	29.0 [1.142]	30	3-	84952-0
-	30.00 [1.181]	36.92 [1.454]	30.18 [1.188]	28.0 [1.102]	29	2-	84952-9
.50	29.00 [1.142]	35.92 [1.414]	29.18 [1.149]	27.0 [1.063]	28	2-	84952-8
-	28.00 [1.102]	34.92 [1.375]	28.18 [1.109]	26.0 [1.024]	27	2-	84952-7
.50	27.00 [1.063]	33.92 [1.335]	27.18 [1.070]	25.0 [1.984]	26	2-	84952-6
-	26.00 [1.024]	32.92 [1.296]	26.18 [1.031]	24.0 [.945]	25	2-	84952-5
.50	25.00 [.984]	31.92 [1.257]	25.18 [.991]	23.0 [.906]	24	2-	84952-4
-	24.00 [.945]	30.92 [1.217]	24.18 [.952]	22.0 [.866]	23	2-	84952-3
.50	23.00 [.906]	29.92 [1.179]	23.18 [.913]	21.0 [.827]	22	2-	84952-2
-	22.00 [.866]	28.92 [1.139]	22.18 [.873]	20.0 [.787]	21	2-	84952-1
.50	21.00 [.827]	27.92 [1.099]	21.18 [.834]	19.0 [.748]	20	2-	84952-0
-	20.00 [.787]	26.92 [1.060]	20.18 [.794]	18.0 [.709]	19	1-	84952-9
.50	19.00 [.748]	25.92 [1.020]	19.18 [.755]	17.0 [.669]	18	1-	84952-8
-	18.00 [.709]	24.92 [.981]	18.18 [.716]	16.0 [.630]	17	1-	84952-7
.50	17.00 [.669]	23.92 [.942]	17.18 [.676]	15.0 [.591]	16	1-	84952-6
-	16.00 [.630]	22.92 [.902]	16.18 [.637]	14.0 [.551]	15	1-	84952-5
.50	15.00 [.591]	21.92 [.863]	15.18 [.598]	13.0 [.512]	14	1-	84952-4
-	14.00 [.551]	20.92 [.824]	14.18 [.558]	12.0 [.472]	13	1-	84952-3
.50	13.00 [.512]	19.92 [.784]	13.18 [.519]	11.0 [.433]	12	1-	84952-2
-	12.00 [.472]	18.92 [.745]	12.18 [.480]	10.0 [.394]	11	1-	84952-1
.50	11.00 [.433]	17.92 [.705]	11.18 [.440]	9.0 [.354]	10	1-	84952-0
-	10.00 [.394]	16.92 [.666]	10.18 [.401]	8.0 [.315]	9		84952-9
.50	9.00 [.354]	15.92 [.627]	9.18 [.361]	7.0 [.276]	8		84952-8
-	8.00 [.315]	14.92 [.587]	8.18 [.322]	6.0 [.236]	7		84952-7
.50	7.00 [.276]	13.92 [.548]	7.18 [.283]	5.0 [.197]	6		84952-6
-	6.00 [.236]	12.92 [.509]	6.18 [.243]	4.0 [.157]	5		84952-5
.50	5.00 [.197]	11.92 [.469]	5.18 [.204]	3.0 [.118]	4		84952-4

DIMENSIONS mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DRAWN: WYLEE 14MAY2003		TE Connectivity															
<table border="0"> <tr><td>0 PLC</td><td>±</td></tr> <tr><td>1 PLC</td><td>±0.2 [.008]</td></tr> <tr><td>2 PLC</td><td>±0.1 [.004]</td></tr> <tr><td>3 PLC</td><td>±</td></tr> <tr><td>4 PLC</td><td>±</td></tr> </table>		0 PLC	±	1 PLC	±0.2 [.008]			2 PLC	±0.1 [.004]	3 PLC	±	4 PLC	±	<table border="0"> <tr><td>ANGLES</td><td>±</td></tr> <tr><td>FINISH</td><td>④ ⑤</td></tr> </table>		ANGLES	±	FINISH	④ ⑤	CHK: LP TAN APVD: SF LEONG PRODUCT SPEC: 108-1393 APPLICATION SPEC: 114-1072 WEIGHT: -	
0 PLC	±																				
1 PLC	±0.2 [.008]																				
2 PLC	±0.1 [.004]																				
3 PLC	±																				
4 PLC	±																				
ANGLES	±																				
FINISH	④ ⑤																				
MATERIAL: ⑧				CUSTOMER DRAWING		SCALE: 4:1 SHEET 1 OF 1 REV A4															