



- 1 HOUSING: POLYESTER LIQUID CRYSTAL, BLACK  
CONTACTS: BRASS.
- 2 CONTACTS:  $0.76 \mu\text{m}$  [0.00030] MIN GOLD FOR A LENGTH OF  $3.50$  [0.138] MIN FROM MATING END,  $3.81 \mu\text{m}$  [0.00150] MIN TIN ON SOLDER TAILS, ALL OVER  $1.27 \mu\text{m}$  [0.00050] MIN NICKEL.
- 3 POSITION TOLERANCE APPLIES AT CONTACT TIP.
- 4 POSITION NUMBERS SHOWN FOR REFERENCE ONLY.
- 5 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 6. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM.
- 7. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD.

1, 13, 38, 50	ALL OTHER PINS	25, 26	5788667-1
5.00 [0.197]	4.25 [0.167]	3.50 [0.138]	PART NUMBER
"L" (PIN LENGTH) AND LOCATION			

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0 PLC ± -	1 PLC ± -	2 PLC ± 0.13[005]	3 PLC ± -	4 PLC ± -	ANGLES ± -
MATERIAL		FINISH		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
1		2		A1	00779	5788667	

Customer Drawing, SCALE 4:1, SHEET 1 OF 1, REV 0