




REV
NC
DRB12-60P*E-L018

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED
NC	NEW RELEASE PER E.O. P17208	4-5-01	RDR



6. WIRE ROUTER CAP IS INCLUDED WITH RECEPTACLE (-L018 MOD).
5. THIS RECEPTACLE MATES WITH DRB16-60S*(N)E-**** PLUG (* = A,B,C,D KEYS; **** = ALL MODIFICATIONS). CONSULT FACTORY FOR MODS.
4. FOR CONTACTS AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 0425-015-0000.
3. ITEMS SOLD SEPARATELY: SECONDARY LOCK: WB-60P*
INTERFACE FLANGE: DRBF-2*
2. DIMENSION TOLERANCE: ±.025 [.635].
1. DIMENSIONS ARE IN INCHES [mm].
- NOTES:

8. SEE SHEET 2 FOR OTHER KEY ARRANGEMENTS.
7. MATERIAL: RECEPTACLE: PLASTIC
SEAL/GROMMET: RUBBER
THREADED INSERT: STEEL

CONTACT SIZE	MIN. INSUL. O.D. [mm]	MAX. INSUL. O.D. [mm]	WIRE RANGE [mm ²] REF ONLY
16	.053 [1.346]	.120 [3.048]	14-20 AWG [2.0-0.5]
20	.040 [1.016]	.095 [2.413]	16-20 AWG [1.0-0.5]

SIGNATURE & DATE	
DR	S. PALLUTH 03/29/01
CHK	<i>[Signature]</i> 4/4/01
PE	<i>[Signature]</i> 4/2/01
APPD	<i>[Signature]</i> 4/4/01
SCALE	NONE

RECEPTACLE, 60 CONTACTS
KEYS A, B, C & D
"E" SEAL, -L018 MOD
COLOR: BLACK
DRB SERIES
ENVELOPE


CP EP059 MATL. CODE

The Deutsch Company
DEUTSCH I.P.D.
3850 INDUSTRIAL AVE.
HEMET, CALIF. 92545


DRB12-60P*E-L018

DWG SIZE CODE 11139 SHEET 1 OF 2


REV	DRB12-60P*E-L018	REVISIONS			
NC		SYM	DESCRIPTION	DATE	APPROVED
			SEE SHEET 1	4-5-01	RDR




DRB12-60PAE-L018
KEY ARRANGEMENT -A-



DRB12-60PBE-L018
KEY ARRANGEMENT -B-



DRB12-60PCE-L018
KEY ARRANGEMENT -C-



DRB12-60PDE-L018
KEY ARRANGEMENT -D-

NOTES:

SIGNATURE & DATE		RECEPTACLE, 60 CONTACTS KEYS A,B,C & D "E" SEAL, -L018 MOD COLOR: BLACK DRB SERIES ENVELOPE	CP	EP059	MATL. CODE
DR	S. PALLUTH 03/29/01		The Deutch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92545		
CHK	<i>R. May</i> 4-4-01		B DRB12-60P*E-L018 DWG SIZE 11139 SHEET 2 OF 2		
PE	<i>S. Palluth</i> 4/2/01				
APPD	<i>D. Meyer</i> 4/2/01				
SCALE	NONE				