



REV  
A DT06-3S-CE01

| REVISIONS |                             |         |          |
|-----------|-----------------------------|---------|----------|
| SYM       | DESCRIPTION                 | DATE    | APPROVED |
| NC        | NEW RELEASE PER E.O. P15117 | 8-22-96 | RDR      |
| A         | REVISED PER E.O. P16046     | 6-15-99 | RDR      |

DATE CODE: MONTH IS REPRESENTED BY SEQUENTIAL ALPHA CHARACTERS. EX: A=JANUARY  
YEAR IS REPRESENTED BY THE LAST NUMERICAL DIGIT. EX: 0=2000

5. THIS CONNECTOR CAN PASS THRU A ONE INCH [25.44] HOLE.
4. THIS PLUG MATES WITH THE DT04-3P-\*\*\*\* RECEPTACLE (\*\*\*\* = ALL MODIFICATIONS). CONSULT FACTORY FOR MODIFICATIONS.
3. FOR CONTACTS AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 0425-015-0000 AND 0425-017-0000.
2. DIMENSIONS ARE  $\pm .025$  [0.63] UNLESS OTHERWISE SPECIFIED.
1. ALL DIMENSIONS ARE IN INCHES [MILLIMETERS].

6. THIS CONNECTOR WILL ACCOMMODATE THE FOLLOWING WIRE INSULATION DIAMETERS:

| CONTACT SIZE | MIN. INSUL. O.D. | MAX. INSUL. O.D. | WIRE RANGE [mm <sup>2</sup> ] |
|--------------|------------------|------------------|-------------------------------|
| 16           | .053 [1.35]      | .120 [3.05]      | 14-20 AWG [2.0-0.5]           |

NOTES:

| SIGNATURE & DATE |                    |
|------------------|--------------------|
| DR               | D. SPENCER 04FEB99 |
| CHK              | S. Beard 6-14-99   |
| PE               | J. K. 6-9-99       |
| APPD             | R. Rad 6-15-99     |
| SCALE            | 3:1 WT             |

3 WAY PLUG  
REDUCED DIAS. OF SEAL  
CE01 MODIFICATION  
DT SERIES

CP NATL. CODE

**The Deutsch Company**  
DEUTSCH I.P.D.  
3850 INDUSTRIAL AVE.  
HEMET, CALIF. 92545

**B** DT06-3S-CE01

DWG SIZE CODE SHEET | OF |

ENVELOPE