

4

3

2

1

THIS DRAWING IS UNPUBLISHED

RELEASED FOR PUBLICATION

2015

© COPYRIGHT 2000 BY TE CONNECTIVITY

ALL RIGHTS RESERVED.

LOC DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
NC		NEW RELEASE PER E.O. P16572	07MAR2000	SB	RDR
A		REVISED PER E.O. P16875	29SEP2000	SB	RDR
B		REVISED PER E.O. P18119	15APR2003	AR	RDR
C		REVISED PER ECO-14-019072	23FEB2015	JA	DM

MAIN POLARIZING KEY

 $1.521 \pm .025$
 $[38.63 \pm 0.63]$

5

1

GROMMET

POLARIZING INDICATOR

 $\varnothing 1.950$
 $[49.53]$
 OVER KNURL

 $\varnothing 1.470$
 $[37.34]$

COUPLING RING

PLUG HOUSING

RETAINING RING

DATE CODE

POLARIZING INDICATOR

SCALE 1:1

5 NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

4 MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)
RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
GROMMET: SILICONE (ORANGE-RED)3 SEE 0425-021-0000 APPLICATION SPECIFICATION
A. RECOMMENDED WIRE INSULATION RANGE
B. CONTACT REMOVAL TOOLS2. THIS PLUG MATES WITH HDP24-24XXP/SX-XXXX RECEPTACLE
X = SEAL TYPE (N,T,E)
XX = INSERT ARRANGEMENT
XXXX = MODIFICATION

1 SEE CUSTOMER DRAWING 0425-014-2400 FOR AVAILABLE INSERT ARRANGEMENTS AND PART NUMBERS.

NOTES:

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 06MAR2000

STEVE BEARD

CHK 11APR2003

JAIME C. APOSTOL

APVD 11APR2003

STEVE BEARD

PRODUCT SPEC

0425-021-0000

APPLICATION SPEC

3

WEIGHT

Customer Drawing

DIMENSIONS:
INCHES [mm]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±.015 [0.38]
4 PLC	±
ANGLES	±0°30'0"

MATERIAL

4

FINISH

N/A

TE Connectivity

NAME

PLUG, COUPLING RING
SIZE 24
HDP SERIES

SIZE

A3

CAGE CODE

4AFU8

DRAWING NO

HDP26-24-XXP/SX

RESTRICTED TO

-

SCALE 2:1

SHEET 1 OF 1

REV C

1470-19 (3/11)