



REV B	DRC16-24S*-P013	REVISIONS		
SYM	DESCRIPTION	DATE	APPROVED	
NC	NEW RELEASE PER E.O. P15136	11-15-96	RDR	
A	REVISED PER E.O. P17547	12-10-01	RDR	
B	REVISED PER E.O. P17700	4-3-02	RDR	




8. MATING TORQUE REQUIREMENT: 25-28 IN-LB [2.82-3.13 Nm].
7. SEE SHEET 2 FOR OTHER KEY ARRANGEMENTS.
6. MATERIAL- PLUG: PLASTIC; SEAL/GROMMET: RUBBER; RETAINING BOLT: STEEL.
5. THIS PLUG MATES WITH DRC10-24P*-****; DRC12-24P*-****; DRC13-24P*-****; AND DRC14-24P*-**** RECEPTACLE. (*=A,B,C,D KEYS; ****=ALL MODIFICATIONS). CONSULT FACTORY FOR MODS.
4. FOR CONTACTS AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS, SEE ENVELOPE DRAWING 0425-015-0000.
3. PLUG SUPPLIED WITH DUST CAP. (NOT SHOWN).
2. DIMENSION TOLERANCE: ±.025 [.64].
1. DIMENSIONS ARE IN INCHES [mm].
- NOTES: UNLESS OTHERWISE SPECIFIED

MIN. INSUL. O.D.	MAX. INSUL. O.D.	WIRE RANGE [mm ²] REF ONLY
.100 [2.54]	.134 [3.40]	14-20 AWG [2.0-0.50]


9. PART MODIFICATION: INTERFACE SEALS ARE BONDED TO PLUG.

SIGNATURE & DATE		PLUG 24 SIZE 16 KEYS: A,B,C,D COLOR: BLACK DRC SERIES ENVELOPE	CP	MATL. CODE
DR	D. MEYER 11/29/01		The Deutsch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92545	
CHK	B. Reed 4/02/02		B DRC16-24S*-P013 DWG SIZE CODE 11139 SHEET 1 OF 2	
PE	D. Meyer 3/28/02			
APPD	R. Reed 4-3-02			
SCALE	NONE	WT		


REV B	DRC16-24S*P013		
REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED
	SEE SHEET 1	4-3-02	RDR




DRC16-24SA-P013
KEY: -A-







DRC16-24SB-P013
KEY: -B-



DRC16-24SC-P013
KEY: -C-



DRC16-24SD-P013
KEY: -D-



NOTES:

SIGNATURE & DATE		PLUG 24 SIZE 16 KEYS: A,B,C,D COLOR: BLACK DRC SERIES ENVELOPE	CP	MATL. CODE	
DR	D. MEYER 11/29/01		The Deutsch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92545		
CHK	B. Blum 4/02/02		B	DRC16-24S*P013	
PE	D. Meyer 3/28/02			DWG SIZE	CODE 11139
APPD	R. Ka 4-3-02				
SCALE	NONE	WT			