

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2014

© COPYRIGHT 2014

BY - TE CONNECTIVITY

ALL RIGHTS RESERVED.

LOC - -

DIST - -

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
NC		NEW RELEASE PER E.O. PI4915	04DEC1995	-	RDR
A		REVISED PER E.O. PI5908	05FEB1999	-	RDR
B		REVISED PER E.O. PI8134	23MAY2003	-	RDR
BI		REVISED AS PER ECO-15-001798	02SEP2014	VNB	DM

Top view of the receptacle connector. The main polarizing keyway is shown with a diameter of  $\varnothing 2.000$  [50.8]. The overall diameter of the shell is  $1.875$  [47.63].

Side view of the receptacle connector. Dimensions include: Shell length  $(1.647)$  [41.83], distance to contact  $1.030$  [26.16], contact length  $.505$  [12.83], and contact diameter  $\varnothing 1.470$  [37.34]. A callout 3 points to the contact tip. The receptacle housing is labeled with callout 6. The shell is identified as 1.6875-18 UNEF REF.

6. MATERIAL:  
RECEPTACLE HOUSING: AL 6000 SERIES

5. THIS PART MATES WITH HD36-24-XXXP/SX-XXXX

4. PART NUMBER INFO: XX= ARRANGEMENT: X= SEAL TYPE

3. TOTAL DIM. WITH EXTENDED WIRE SEAL (WITH CONTACTS #4 OR #8 ONLY) =  $1.870 \pm .050$  [47.50 ± 1.27].

2. FOR ARRANGEMENT OF CONTACT LOCATION  
SEE ENVELOPE DRAWING 0425-014-2400.

1. CONSULT THE FACTORY FOR ELECTRICAL AND MATERIAL SPECIFICATIONS.

NOTES:

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
INCHES [mm]

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±.010 [±.254]
4 PLC	±-
ANGLES	±0° 30' 0"
FINISH	-

MATERIAL SEE NOTE

DWN 30OCT2014

VIJETH BHARADWAJ

CHK 31OCT2014

I. GRANTCHAROVA

APVD 31OCT2014

D. MEYER

PRODUCT SPEC

0425-016-0000

APPLICATION SPEC

0425-015-0000

WEIGHT -

NAME

RECEPTACLE CONNECTOR  
SHELL SIZE 24 BAYONET COUPLING  
HD30 SERIES

SIZE

A3

CAGE CODE

-

DRAWING NO

©-HD34-24-XXP/SX

RESTRICTED TO

-

Customer Drawing

SCALE NONE

SHEET 1 OF 1

REV BI

**STE** TE Connectivity

1470-19 (3/11)