

4

3

2

1

THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION 2014

© COPYRIGHT 2014 BY TE CONNECTIVITY ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
-	-	NC	NEW RELEASE PER E.O. A14915	04DEC1995	-	RDR
		A	REVISED PER E.O. P18134	23MAY2003	-	RDR
		B	REVISED PER E.O. P18565	20SEP2004	-	RDR
		BI	REVISED PER ECO-15-001798	12AUG2014	PV	DM

MAIN POLARIZING KEY

(1.520)
[38.61]
POLARIZING INDICATOR

3

Ø 1.942^{+0.000}_{-0.100}
[49.32^{+0.00}_{-2.54}]
OVER KNURL

(Ø 1.353)
[34.37]

(Ø 1.470)
[37.33]

5
SHELL

.509
[12.93]

PLUG INSERTS INTO RECEPT.
WITHIN THIS DISTANCE.

5. MATERIAL:
PLUG HOUSING: AL 6000 SERIES
SHELL MATERIAL: METAL
INSULATOR : PLASTIC

4. THIS SHELL MATES WITH HD34-24-XXP/SX-XXXX

3. TOTAL DIM. WITH EXTENDED WIRE SEAL (WITH CONTACTS
#4 OR #8 ONLY) = 1.750±.050 [44.45±1.27].

2. SEE DRAWING 0425-014-2400 FOR ARRANGEMENT OF CONTACT LOCATION.

1. CONSULT THE FACTORY FOR ELECTRICAL AND MATERIAL SPECIFICATIONS.

NOTES:

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN VIJETH BHARADWAJ 30OCT2014	TE Connectivity	
DIMENSIONS: INCHES [mm]		CHK I. GRANTCHAROVA 31OCT2014		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. MEYER 31OCT2014	NAME PLUG CONNECTOR, SHELL SIZE 24 BAYONET COUPLING HD30 SERIES	
		PRODUCT SPEC 0425-015-0000	RESTRICTED TO	
MATERIAL SEE NOTE		FINISH -	APPLICATION SPEC 0425-016-0000	SIZE A3
		WEIGHT -	Customer Drawing	SCALE 2:1
			DRAWING NO C=HD36-24-XXP/SX	SHEET 1
				OF 1
				REV BI

1470-19 (3/11)