

Power Transformer Chassis Mount: Quick Pack

FD7-28

Description:

The FD7-28 Quick Pack small power transformer offers a significant reduction in size and weight over a standard transformer. This transformer can be used for a wide variety of applications. It is bobbin wound for reduced size and small operating space.

Electrical Specifications (@25C): Maximum Power: 56.0VA Input Voltage:

Series: 230VAC@50/60Hz Parallel: 115VAC@50/60Hz Output Voltage: 28.0VCT@2.0A

Construction:

Split bobbing non concentric winding eliminates costly electrostatic shielding. Termination is suitable for quick connects or soldering.

Safety:

UL Class B E53148




Dimensions:

| А | В | С | D | Е | F | G |
|-------|-------|-------|-------|-------|----------|-------|
| 2.250 | 3.125 | 3.687 | 1.812 | 2.687 | .187 Dia | 1.062 |

Notes: 1. Units: inches.

- 2. Terminal size: .187" X 0.021".
- 3. Weight: 1.70 lbs

Schematic:



Input (115V): Input 1 to 2 Connect 1 to 4, 2 to 5 Input (230V): Input 1 to 5 Connect 2 to 4 Output: 6 to 10

RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.



