



Heyco® OEM Wire Connectors



WIRE COMBINATIONS (AWG)	PART NO.	DESCRIPTION	COLOR	PART DIMENSIONS									
				A		B		C		D		E	
				in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.
300V #22 to #16 AWG Min. 2 #22 Max. 2 #16	2922	OEM WC 71	Tan	.158	4,0	.253	6,5	.328	8,4	.172	4,4	.578	14,7
300V #22 to #14 AWG Min. 2 #22 Max. 3 #16	2924	OEM WC 72	Tan	.172	4,4	.281	7,1	.391	9,9	.172	4,4	.703	17,9
600V* #22 to #16 AWG Min. 1 #18 w/ 1 #20 Max. 4 #16 w/ 1#20	2926	OEM WC 73*	Tan	.172	4,4	.343	8,8	.437	11,1	.312	7,9	.859	21,8
600V* #22 to #14 AWG Min. 2 #22 Max. 3 #14	2928	OEM WC 59*	Tan	.172	4,4	.375	9,5	.484	12,3	.515	13,1	1.063	27,0

*Rated for 600 volts or 1000 volts in fixtures and signs.
See drawing on page 6-9, same as High Temp Wire Connectors

- Ribbed shell provides sure grip.
- Welded one piece spring/shell for added reliability.
- Tough, UL94V-2 flame-retardant shell rated at 105°C (221°F). Rated for 300 volts, except as noted.
- Accepts #22 to #14 AWG wire.
- Deep, wide skirt helps protect against flash-over and turned back strands for maximum dielectric protection.
- Reuseable for easy circuit changes and additions.
- Classified in accordance with IEC Publications 998-2 and 998-2-4.
- Listed under the Component Program of Underwriters' Laboratories File #E-80121.
- Certified by Canadian Standards Association File #LR-211101.



Heyco® All-Plastic Wire Connectors

WIRE COMBINATIONS (AWG)	PART NO.	DESCRIPTION	COLOR	PART DIMENSIONS			
				A		B	
				in.	mm.	in.	mm.
JOINS: 2#16, 1#16 & 2# 18, 2-3#18	2913	HS-2	Yellow	.598	15,2	.256	6,5
JOINS: 1#14 & 1-2#16 1#14 & 1-2#18 2-3#16 2-4#18	2916	HS-4	Ivory	.673	17,1	.311	7,9
JOINS: 1#14 & 1-2#16 1#14 & 1-2#18 2-3#16 2-5#18	2919*	HS-6*	Ivory	.874	22,2	.366	9,3

*Rated for 600 volts or 1000 volts in fixtures and signs.

- Molded of urea plastic
- Clean, smooth integral threads gather and secure even delicate conductor strands.
- Three sizes for #14 AWG thru #18 AWG.
- Rated for 300 volts except as noted.
- Temperature rated at 105°C.
- Consult Heyco for Approvals.
- See page 5-13 for installation tools.

