


Dipped Radial Multilayer Ceramic K10 Capacitors




RoHS
COMPLIANT

DIMENSIONS




L2
Component outline for
Lead spacing 2.5 ± 0.8 mm
(straight leads)




H5
Component outline for
Lead spacing 5.0 ± 0.8 mm
(flat bent leads)

L2 and H5 are preferred styles



K2
Component outline for
Lead spacing 2.5 ± 0.8 mm
(outside kink)



K5
Component outline for
Lead spacing 5.0 ± 0.8 mm
(outside kink)

CAPACITOR DIMENSIONS AND WEIGHT								
SIZE	Wb _{MAX}	H _{MAX}	T _{MAX}	MAX. SEATING HEIGHT (SH)				WEIGHT (g)
				L2	H5	K2	K5	
10	3.6 (0.14)	3.6 (0.14)	2.3 (0.09)	1.58 (0.062)	2.54 (0.100)	3.50 (0.140)	3.50 (0.140)	≈ 0.10

Note

1. Bulk packed types have a standard lead length L = 25.4 mm (1.0 inch) minimum
2. Dimensions between parentheses are in inches
3. Thickness is defined as T



QUICK REFERENCE DATA				
DESCRIPTION	VALUE			
Capacitance range	10 to 1000 pF		100 pF to 0.1 μF	
Rated DC voltage	50 V	100 V	50 V	100 V
Tolerance on capacitance	± 5 % / ± 10 %		± 10 % / ± 20 %	
Dielectric Code	C0G (NP0)		X7R	
			Y5V	

ORDERING INFORMATION									
K	103	K	10	X7R	F	5	3	H	5
PRODUCT TYPE	CAPACITANCE CODE	CAPACITANCE TOLERANCE	SIZE CODE	TEMP. CHAR.	RATED VOLTAGE	LEAD DIAMETER	LEAD LENGTH/PACKAGING	LEAD STYLE	LEAD SPACING
K = Mono-Kap	Two significant digits followed by the number of zeros. example: 103 = 10000 pF	J = ± 5 % K = ± 10 % M = ± 20 % Z = + 80 / - 20 %	Ref. mechanical spec.	C0G X7R Y5V	F = 50 V _{DC} H = 100 V _{DC}	5 = 0.5 mm (0.020")	3 = bulk, with lead length of 30 ± 5.0 (1.25") T = Tape and Reel U = Ammo pack	L = Straight Lead H = High Seated assy	2 = 2.5 (0.100") 5 = 5.0 (0.200")



CAPACITANCE RANGE CHART COG (NPO) DIELECTRIC

SIZE		10	
RATED VOLTAGE		50	100
VALUE	CODE		
10 pF	100		
12 pF	120		
15 pF	150		
18 pF	180		
22 pF	220		
27 pF	270		
33 pF	330		
39 pF	390		
47 pF	470		
56 pF	560		
68 pF	680		
82 pF	820		
100 pF	101		
120 pF	121		
150 pF	151		
180 pF	181		
220 pF	221		
270 pF	271		
330 pF	331		
390 pF	391		
470 pF	471		
560 pF	561		
680 pF	681		
820 pF	821		
1000 pF	102		
1200 pF	122		
1500 pF	152		
1800 pF	182		
2200 pF	222		
2700 pF	272		
3300 pF	332		
3900 pF	392		
4700 pF	472		
5600 pF	562		
6800 pF	682		
8200 pF	822		
0.01 μ F	103		

Y5V DIELECTRIC

SIZE		10	
RATED VOLTAGE		50	
VALUE	CODE		
0.01 μ F	103		
0.015 μ F	153		
0.022 μ F	223		
0.033 μ F	333		
0.047 μ F	473		
0.068 μ F	683		
0.10 μ F	104		
0.15 μ F	154		
0.22 μ F	224		
0.33 μ F	334		
0.47 μ F	474		
0.68 μ F	684		
1.0 μ F	105		

X7R DIELECTRIC

SIZE		10	
RATED VOLTAGE		50	100
VALUE	CODE		
100 pF	101		
120 pF	121		
150 pF	151		
180 pF	181		
220 pF	221		
270 pF	271		
330 pF	331		
390 pF	391		
470 pF	471		
560 pF	561		
680 pF	681		
820 pF	821		
1000 pF	102		
1200 pF	122		
1500 pF	152		
1800 pF	182		
2200 pF	222		
2700 pF	272		
3300 pF	332		
3900 pF	392		
4700 pF	472		
5600 pF	562		
6800 pF	682		
8200 pF	822		
0.01 μ F	103		
0.012 μ F	123		
0.015 μ F	153		
0.018 μ F	183		
0.022 μ F	223		
0.027 μ F	273		
0.033 μ F	333		
0.039 μ F	393		
0.047 μ F	473		
0.056 μ F	563		
0.068 μ F	683		
0.082 μ F	823		
0.10 μ F	104		
0.15 μ F	154		
0.22 μ F	224		
0.33 μ F	334		
0.47 μ F	474		
0.68 μ F	684		
1.0 μ F	105		



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.