



Inductors, Commercial, Molded, Shielded, Miniature, Axial Leaded



ELECTRICAL SPECIFICATIONS

Inductance Tolerance: ± 10 % standard, ± 5 % available

Insulation Resistance: 1000 MΩ minimum per MIL-STD-202, method 302, test condition B

Dielectric Withstanding Voltage: 200 V_{AC} per MIL-STD-202, method 301 (at sea level)

Percent Coupling: 3 % maximum per MIL-PRF-15305

Operating Temperature: -55 °C to +105 °C

ENVIRONMENTAL PERFORMANCE		
TEST	CONDITIONS	SPECIFICATIONS
Barometric Pressure	C	MIL-STD-202, method 105
Thermal Shock	A-1	MIL-STD-202, method 107
Flammability	-	MIL-STD-202, method 111
Overload	-	MIL-PRF-15305
Low Temperature Storage	-	MIL-PRF-15305
Resistance to Soldering Heat	A	MIL-STD-202, method 210
Resistance to Solvents	-	MIL-STD-202, method 215

FEATURES

- Flame retardant coating
- Electromagnetic shield
- Small package for a shielded inductor
- Epoxy molded construction provides superior moisture protection
- Precision performance, excellent reliability, sturdy construction
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT

MECHANICAL SPECIFICATIONS

Terminal Strength: 3 lb pull per MIL-STD-202, method 211, test condition A, except 180° rotation for a total of 540°

Weight: IMS-2 = 0.30 g maximum

TEST EQUIPMENT (1)

- H/P 4342A Q-meter
- Measurements corporation megacycle meter, model 59
- Wheatstone bridge

Note

(1) Test procedure per MIL-PRF-15305

MATERIAL SPECIFICATIONS

Encapsulant: Epoxy

Standard Terminals: #24 AWG, tinned copper

DIMENSIONS in inches [millimeters]	

STANDARD ELECTRICAL SPECIFICATIONS							
MODEL	IND. (μH)	TOL. (%)	Q MIN.	TEST FREQUENCY L AND Q (MHz)	SRF MIN. (MHz) (1)	DCR MAX. (Ω)	RATED DC CURRENT (mA) (2)
IMS-2	0.10	± 10	54	25.0	490.0	0.10	670
IMS-2	0.12	± 10	52	25.0	430.0	0.11	635
IMS-2	0.15	± 10	50	25.0	415.0	0.12	610
IMS-2	0.18	± 10	49	25.0	375.0	0.13	585
IMS-2	0.22	± 10	47	25.0	330.0	0.15	545
IMS-2	0.27	± 10	46	25.0	300.0	0.16	530
IMS-2	0.33	± 10	44	25.0	260.0	0.18	495
IMS-2	0.39	± 10	42	25.0	230.0	0.19	485
IMS-2	0.47	± 10	41	25.0	220.0	0.21	460
IMS-2	0.56	± 10	41	25.0	210.0	0.23	440
IMS-2	0.68	± 10	39	25.0	180.0	0.24	430
IMS-2	0.82	± 10	38	25.0	165.0	0.27	405
IMS-2	1.0	± 10	37	25.0	150.0	0.30	385

Notes

(1) Measured with full length lead

(2) Rated DC current based on maximum temperature rise as shown in table



STANDARD ELECTRICAL SPECIFICATIONS							
MODEL	IND. (μH)	TOL. (%)	Q MIN.	TEST FREQUENCY L AND Q (MHz)	SRF MIN. (MHz) ⁽¹⁾	DCR MAX. (Ω)	RATED DC CURRENT (mA) ⁽²⁾
IMS-2	1.2	± 10	40	7.9	130.0	0.73	247
IMS-2	1.5	± 10	41	7.9	115.0	0.86	228
IMS-2	1.8	± 10	43	7.9	105.0	0.95	217
IMS-2	2.2	± 10	45	7.9	95.0	1.1	202
IMS-2	2.7	± 10	48	7.9	90.0	1.2	193
IMS-2	3.3	± 10	49	7.9	80.0	1.3	185
IMS-2	3.9	± 10	50	7.9	75.0	1.5	173
IMS-2	4.7	± 10	53	7.9	70.0	2.4	136
IMS-2	5.6	± 10	54	7.9	60.0	2.9	124
IMS-2	6.8	± 10	55	7.9	55.0	3.2	118
IMS-2	8.2	± 10	55	7.9	53.0	3.6	111
IMS-2	10.0	± 10	57	7.9	50.0	4.0	106
IMS-2	12.0	± 10	36	2.5	35.0	3.0	122
IMS-2	15.0	± 10	38	2.5	30.0	3.4	115
IMS-2	18.0	± 10	40	2.5	26.0	3.8	108
IMS-2	22.0	± 10	40	2.5	24.0	4.9	96
IMS-2	27.0	± 10	40	2.5	21.0	5.8	88
IMS-2	33.0	± 10	41	2.5	20.0	6.5	83
IMS-2	39.0	± 10	42	2.5	19.0	7.9	75
IMS-2	47.0	± 10	44	2.5	16.0	9.3	69
IMS-2	56.0	± 10	44	2.5	15.0	11.0	64
IMS-2	68.0	± 10	45	2.5	13.0	12.0	61
IMS-2	82.0	± 10	45	2.5	11.0	13.0	59
IMS-2	100.0	± 10	40	2.5	10.5	16.8	51

IRON CORE

Notes

- (1) Measured with full length lead
- (2) Rated DC current based on maximum temperature rise as shown in table

ORDERING INFORMATION				
IMS-2	10 μH	± 10 %	ER	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC® LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER			
I	M	S	0
2			
MODEL			
E	R		
PACKAGE CODE		1	0
		0	K
		INDUCTANCE VALUE	
		INDUCTANCE TOLERANCE	



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.