


## Heatsink Mount High Power Resistors

### WMHP Series

- TO-220 & TO-247 standard power packages
- Very low thermal resistance
- Non-inductive thick film technology
- 20 to 100 watt high power resistors
- Single screw mounting to heatsink
- Suitable for high frequency / fast pulse use



All parts are Pb-free and comply with EU Directive 2011/65/EU (RoHS2)

### Electrical Data

	WMHP20	WMHP35	WMHP50	WMHP100	Conditions	
Package style	TO-220			TO-247		
Power rating	watts	20	35	50	100	Heatsink with 25°C flange temperature
Power rating	watts	1.5	2.5	3	3.5	Without heatsink, in free air 25°C
Limiting element voltage	volts	350			700	dc or ac rms
Resistance range	ohms	R05 – 10K				
Dielectric strength	volts	1800				ac rms for 60s
Working temperature range	°C	-65 to 150		-65 to 175		
Insulation resistance	ohms	>10G				Between terminals and tab
Tolerances	%	≤1R0: ±5 >1R0: ±1, ±5				
TCR	ppm/°C	≤R20: ±1000 >R20-3R0: ±300 >3R0-10R: ±100 >10R: ±50			25 to 105°C	
Standard values		E24 preferred				

### Physical Data

	Dimensions (mm) & Weight (g)		
	TO-220	TO-247	
A	10.16 ±0.25	15.75 ±0.26	
B	15 ±0.3	20.7 ±0.26	
C	4.6 ±0.2	4.95 ±0.26	
D	3.85 ±0.15	3.63 ±0.1	
E	13.75 ±0.5	14.48 ±1.27	
F	4 max	2.79 ±0.76	
G	5.08 ±0.25	3.63 ±0.18	
H	0.78 ±0.08	1.52 ±0.1	
J	1.3 ±0.1	10.16 ±0.26	
K	6.4 ±0.25	5.33 ±0.26	
L	0.51 ±0.15	0.81 ±0.26	
M	2.27 ±0.25	2.41 ±0.26	
Wt	2.0 nom	3.7 nom	

### Performance Data

Test	Performance
Load at Rated Power: 2000hrs at rated power	±ΔR% 1
Short Term Overload: 2 x rated power with applied voltage not to exceed 1.5 x maximum continuous operating voltage for 5 seconds	±ΔR% 0.5
Damp Heat with Load: 40 ±2°C, 90 – 95% RH, maximum working voltage 1.5 hours on, 0.5 hours off, 1000 hours	±ΔR% 1
Thermal Shock: -65°C/150°C, 100cycles	±ΔR% 0.3
Terminal Strength: 2.4N pull test	±ΔR% 0.2


#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

## Heatsink Mount High Power Resistors

### WMHP Series

#### Temperature Derating




#### Mounting

The resistor should be mounted to a heatsink using a suitable thermal interface material. The maximum tightening torque for the M3 mounting screw is 0.9Nm.


#### Pulse Performance

Single Pulse ( $P_{mean} \ll P_r$ ) Condition



Pulse performance for durations  $\geq 1s$  is dependent on mounting conditions. The short term overload power limit is 2 x power rating for 5s.


#### Typical High Frequency Performance



Typical high frequency characteristics for WMHP35-220R. Self resonant frequency is 1GHz.

## Ordering Procedure

Example: WMHP35-10KJ (WMHP35 at 10 kilohms  $\pm 5\%$ , Pb-free)



1 Type	2 Rating	3 Value	4 Tolerance	Packing
WMHP	20	3 / 4 characters R = ohms	F = $\pm 1\%$	Plastic tubes TO-220: 50/tube TO-247: 30/tube
	35		J = $\pm 5\%$	
	50	K = kilohms		
	100			

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.