



300V 15A 2.5mm²

Poles: 2-24P

Pitch: 5.0mm(.197")/5.08mm(.200")

Materials

Housing: PA66 (UL 94V-0)

Contact: Phosphor Bronze, Nickel Plated.

Wire Cage: Brass(Nickel Plated)or Steel(zinc plated)

Screw: M2.5,Steel,A3 Zinc Plated.

Torque: 0.4N.m

设计 /Designed by	绘图 /Drawing by	审核 /Checked by	批准 /Approved by	未注公差 General Tolerance
				X ± 0.2 X ± 0.1 .XX ± 0.05 .XXX ± 0.01
				X' ± 2 X' ± 1 .XX' ± 0.5

图名 /Title

文件编号 /File No.

XY2500FA-5.0
XY2500FB-5.08

页序 /Sheet

备注 /Remark

单位 /Units: mm

序号 /RevNo.

更改记录 /Revision note

签名 /Signature

日期 /Date



新莱亚电子

XINLAYA ELECTRONIC CO.,LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [XON](#) manufacturer:

Other Similar products are found below :

[57.404.7553](#) [57.504.0053.7](#) [57.510.0053](#) [57.910.6153](#) [01.112.1453](#) [CTB932VE/6](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [734-304](#) [8-141-P](#) [FKCT 2.5/ 3-ST KMGY](#) [860505](#) [860508](#) [860516](#) [860810](#) [861908](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP02-5,00](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [H-10](#) [1546228-5](#) [ELFH09150](#) [ELFH16150](#) [ELFP03110](#) [ELFT06250](#) [ELFT07250](#) [ELVF09400](#) [ELVP03100](#) [ELXH03100](#) [ELXH071G0E](#) [ELXP041G0](#) [ELXT046G0](#) [1700101](#) [1700410](#) [1700425](#) [1703176](#) [1705229](#) [1710175](#) [1714537](#) [1717806](#) [1719600](#) [1729386](#) [1734692](#) [1734795](#)