



300V 15A 2.5mm<sup>2</sup> 28-12AWG

Poles: 2-24P

Pitch: 5.0mm (.197")/5.08mm (.200")

**Materials**

Housing: PA66 (UL 94V-0)

Clamp: Phosphor Bronze, Nickel Plated.

Wire Cage: Brass, Nickel Plated.

Screw: M3, Steel A3, Zinc Plated.

设计/Designed by 绘图/Drawing by 审核/checked by 批准/Approved by 未注公差  
General Tolerance

图名/Title 文件编号/File No.

XY2500FAVR-5-0

XY2500FBVR-5-08

页序/Sheet

X: ±0.2 X': ±2°  
.X ±0.1 .X' ±1°  
.XX ±0.05 .XX' ±0.5°  
.XXX ±0.01

序号/revno. 更改记录/Revision note 签名/Signature 日期/Date



XINLATA ELECTRONIC CO., LTD

备注/Remark

单位/Units: mm

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pluggable Terminal Blocks](#) category:*

*Click to view products by [XON](#) manufacturer:*

Other Similar products are found below :

[57.404.7553](#) [57.504.0053.7](#) [57.510.0053](#) [57.910.6153](#) [01.112.1453](#) [CTB932VE/6](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [734-304](#) [8-141-P](#) [FKCT 2.5/ 3-ST KMGY](#) [860505](#) [860508](#) [860516](#) [860810](#) [861908](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP02-5,00](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [H-10](#) [1546228-5](#) [ELFH09150](#) [ELFH16150](#) [ELFP03110](#) [ELFT06250](#) [ELFT07250](#) [ELVF09400](#) [ELVP03100](#) [ELXH03100](#) [ELXH071G0E](#) [ELXP041G0](#) [ELXT046G0](#) [1700101](#) [1700410](#) [1700425](#) [1703176](#) [1705229](#) [1710175](#) [1714537](#) [1717806](#) [1719600](#) [1729386](#) [1734692](#) [1734795](#)