


Bushings, Nipples, Locknuts and Plugs

Available in your choice of steel/malleable iron, aluminum or stainless steel.

Locknuts

- Steel from 1/4" to 2", malleable iron from 2 1/2" to 6"
- Aluminum 3003 from 1/2" to 6" or Type 304 stainless steel from 1/2" to 2"



CAT. NO.			DIMENSIONS (IN.)		
STL./M.I.	ALUM.	ST. STL.	SIZE (IN.)	A	B
139*	—	—	1/4	3/4	9/64
140*	—	—	3/8	1 1/16	9/64
141**	141AL	141-SST	1/2	1 1/64	5/32
142**	142AL	142-SST	3/4	1 3/8	3/16
143	143AL	143-SST	1	1 11/16	13/64
144	144AL	144-SST	1 1/4	2 1/32	13/64
145	145AL	145-SST	1 1/2	2 1/2	13/64
146	146AL	146-SST	2	3	7/32
147	147AL	—	2 1/2	3 3/16	13/32
148	148AL	—	3	4 1/16	13/32
149	149AL	—	3 1/2	4 13/16	15/32
150	150AL	—	4	5 5/16	15/32
151	151AL	—	4 1/2	5 15/16	17/32
152	152AL	—	5	6 1/2	17/32
153	153AL	—	6	7 1/4	19/32

*Hex shape

**Case hardened locknuts

Aluminum locknuts comply with federal standard of copper-free aluminum; less than .5% copper.

Available with DURA-PLATE® Finish.


UL File E-23018

CSA File No. 2884

Ensures positive bonding of conduit to box and prevents loosening due to vibration!

Bonding Locknuts

- Steel or malleable iron (steel through 2")
- Can be used anywhere an ordinary locknut is installed
- Also can be used for Service Entrance applications in conformance with code
- T&B rigid conduit and EMT (thinwall) fittings comply with Federal Specification A-A-50553



CAT. NO.	SIZE (IN.)	DIMENSIONS (IN.)	
		A	B
106†	1/2	1 3/8	.125
107†	3/4	1 3/8	.140
108	1	1 15/16	.170
109	1 1/4	2 5/32	.170
110	1 1/2	2 1/2	.170
111	2	3	.187
112†	2 1/2	3 33/32	.375
113†	3	4 13/16	.375
114†	3 1/2	4 29/32	.438
115†	4	5 5/32	.438

† Not CSA certified.

Available with DURA-PLATE® Finish.

UL File No. E-3060

CSA File No. 638

Provides positive seal against water and oil.

Sealing Locknuts

- For use with rigid and intermediate metal conduits or fittings
- Provides watertight or raintight seal at all enclosures



CAT. NO.	SIZE (IN.)	DIMENSIONS (IN.)		
		A	B	C
141SL	1/2	1.140	1/8	1/4
142SL	3/4	1.420	5/32	5/32
143SL	1	1.770	1/64	5/32
144SL	1 1/4	2.281	1/64	5/16
145SL	1 1/2	2.598	1/64	5/32
146SL	2	3.175	3/16	1/64

UL File No. E-23018
CSA File No. 2884

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification category](#):

Click to view products by [ABB manufacturer](#):

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)