

General Information

Extended Product Type:	CP-D 24/1.3
Product ID:	1SVR427043R0100
EAN:	4016779661171
Catalog Description:	CP-D 24/1.3 Power supply In: 100-240VAC Out: 24VDC/1.3A
Long Description:	The CP-D 24/1.3 is a power supply from the CP-D range. The primary switch mode power supply offers a wide range input of 90-264 V AC and 120-375 V DC, rated input voltage is 100-240 V AC. The rated output power is 30 W, rated output current is 1.3 A at an output voltage of 24 V DC. The output voltage is adjustable within a range of 24 to 28 V DC. The power supply provides a U/I output characteristic.

Categories

Products » Low Voltage Products and Systems » Control Products » Power Supplies

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85044090
EAN:	4016779661171

Dimensions

Product Net Height:	91 mm
Product Net Depth:	57.5 mm
Product Net Weight:	0.196 kg
Product Net Width:	53 mm

Container Information

Package Level 1 Length:	134 mm
Package Level 1 Height:	69 mm
Package Level 1 Gross Weight:	0.249 kg
Package Level 1 Units:	1 piece
Package Level 1 Width:	91 mm

Technical

Number of Phases:	1
Rated Input Voltage (U_{IN}):	100 ... 240 V AC
Input Voltage (U_{in}):	90 ... 264 V AC 120 ... 375 V DC
Rated Frequency (f):	50 Hz 60 Hz
Rated Frequency Limits:	47 ... 63 Hz
Characteristic of Output:	U/I characteristic curve
Rated Output Power:	30 W
Output Power:	30 W
Rated Output Voltage:	24 V DC
Output Voltage (U_{out}):	24 V DC
Rated Output Current:	1.3 A
Output Current:	1.3 A
Output Current Maximum (I_{out}):	1.3 A
Rated Impulse Withstand Voltage (U_{imp}):	Input Circuit / Output Circuit 3 kV
Degree of Protection:	Housing IP20 Terminals IP20
Pollution Degree:	2
Connecting Capacity Input Circuit:	Flexible with Ferrule 0.2 ... 2.5 mm ² Rigid 0.2 ... 2.5 mm ²
Connecting Capacity Output Circuit:	Flexible with Ferrule 0.2 ... 2.5 mm ² Rigid 0.2 ... 2.5 mm ²
Tightening Torque:	Input Circuit 0.7 N·m Output Circuit 0.7 N·m
Wire Stripping Length:	Input Circuit 7 mm Output Circuit 7 mm
Minimum Mounting Distance:	Electrical Conductive Board, Horizontal 25 mm Electrical Conductive Board, Vertical 25 mm Other Device Same Type, Horizontal 25 mm

Other Device Same Type, Vertical 25 mm

Mounting Position:	Position 1
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards:	IEC/EN 60950-1 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508 UL 60950 UL 1310 CAN/CSA C22.2 No.107.1 CAN/CSA C22.2 No.60950 CAN/CSA C22.2 No.223
Function:	Switch mode power supply

Environmental

Ambient Air Temperature:	Operation -40 ... +70 °C Storage -40 ... +85 °C
RoHS Status:	Following EU Directive 2011/65/EC

Technical UL/CSA

Connecting Capacity Input Circuit UL/CSA:	Rigid 24-12 AWG
Connecting Capacity Output Circuit UL/CSA:	Rigid 24-12 AWG
Tightening Torque UL/CSA:	Input Circuit 6 in-lb Output Circuit 6 in-lb

Electromagnetic Compatibility

Radiated Electromagnetic Field Immunity acc. to IEC 61000-4-3:	Level 3 10 V/m
Electrical Fast Transient (Burst Immunity) acc. to IEC 61000-4-4:	Level 4 Power Supply Port Signal 4 kV
Surge Immunity acc. to IEC 61000-4-5:	Level 3 Line-to-Line 2 kV
Conducted Disturbances Immunity acc. to IEC 61000-4-6:	Level 3 10 V
Electromagnetic Compatibility (EMC):	Emission - Class B Immunity - Class B
Electrostatic Discharge (ESD Immunity) acc. to IEC 61000-4-2:	Level 4 Air Discharge 15 kV Level 4 Contact Discharge 8 kV

Certificates and Declarations (Document Number)

Instructions and Manuals:	1SVC427041M0000
CB Certificate:	CB_JPTUV-058258
CCC Certificate:	CCC_2007020907000168
cUL Certificate:	cUL508_E174460
cUR Certificate:	cUR60950_E196145 cUR1310_E313203
Data Sheet, Technical Information:	2CDC114055D0201
Declaration of Conformity - CE:	1SVD982007-0000
EAC Certificate:	EAC_RU_C-DE.ME77.B.01651
GOST Certificate:	GOST_POCC_CN.AB76.B00924
RoHS Information:	1SVD981001-4400
UL Certificate:	UL508_E174460
UR Certificate:	UR60950_E196145 UR1310_E313203

Classifications

ETIM 4:	EC002540 - DC-power supply
ETIM 5:	EC002540 - DC-power supply
ETIM 6:	EC002540 - DC-power supply
eClass:	7.0 27049002
UNSPSC:	39121100
Object Classification Code:	T



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ABB manufacturer:](#)

Other Similar products are found below :

[F204AC-40/0.1](#) [F362-25/0.03](#) [AF09-30-10-11](#) [AF116-30-00-13](#) [AF460-30-11-68](#) [N22E-84](#) [1SAZ721201R1008](#) [1SBL277001R4100](#)
[1SDA057197R1](#) [1SFA611143R1101](#) [1SFA611143R1103](#) [1SFA611211R1001](#) [1SFA611212R1103](#) [1SFA611215R1001](#) [1SFA611285R1002](#)
[1SFA619100R3015](#) [OVR1N160277PS](#) [KT3LD](#) [RV-BC6/60](#) [S201-B16](#) [S202-B40](#) [2CCA703155R0001](#) [2CDS272001R0105](#) [AF753011RT-](#)
[72](#) [1SAM350000R1008](#) [1SFA611200R1104](#) [1SFA611213R1101](#) [1SFA611213R1103](#) [1SFA616160R1006](#) [1SLM004102A1108](#)
[1SPE007717F0721](#) [1SVR427026R0000](#) [1SVR730885R3300](#) [2CCA703250R0001](#) [2CSF202001R3630](#) [2CSF202001R4630](#) [TV10-8F](#) [3304M](#)
[L-10-50R-9-C](#) [DF3416FRAB0](#) [MS116-12](#) [S202-D10](#) [S203-K16](#) [5STP 16F2800](#) [CT-MBS.22S](#) [AF12Z-30-01-20](#) [AF38Z-22-00-23](#)
[AF40-30-00-11](#) [AF65-30-00-13](#) [AF96-30-00-41](#)