

PRODUCT-DETAILS

# CPS3B-100-CV0

## B. SLEEV. CONFORMED V0, 100M



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | CPS3B-100-CV0  |
| Product ID            | 7TCG054800R0072  |
| EAN                   | 5414363149729  |
| Catalog Description   | B. SLEEV. CONFORMED V0, 100M   |
| Long Description      | Flame Retardant Braided Sleeve, Black Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 3mm (0.118 Inches), Expandable Diameter Range 2mm (0.079 Inches) to 5mm (0.197 Inches), Mini-Reel Length 100m (328.08 Feet) |

### Ordering

|                         |               |
|-------------------------|---------------|
| EAN                     | 5414363149729 |
| UPC                     | 786210926902  |
| Country of Origin       | France (FR)   |
| Customs Tariff Number   | 3926909990    |
| Selling Unit of Measure | roll          |

### Dimensions

|                            |                    |
|----------------------------|--------------------|
| Product Net Depth / Length | 328.08 ft<br>100 m |
|----------------------------|--------------------|

### Container Information

|                                   |                    |
|-----------------------------------|--------------------|
| Package Level 1 Units             | 1 reel             |
| Package Level 2 Units             | 5 reel             |
| Package Level 2 Width             | 14.76 in<br>375 mm |
| Package Level 2 Height            | 13.78 in<br>350 mm |
| Package Level 2 Depth /<br>Length | 29.53 in<br>750 mm |

---

### Additional Information

|                   |                                |
|-------------------|--------------------------------|
| Brand / Label     | Catamount                      |
| Bundle Diameter   | 0.04 to 2.6 in<br>1 to 66 mm   |
| Color             | Black                          |
| Effective Date    | 20040129                       |
| Material          | Polyester                      |
| Product Name      | PLASTIC CONDUIT                |
| Product Type      | Braided Sleeve                 |
| Temperature Range | -58 to 302 °F<br>-50 to 150 °C |

---

### Certificates and Declarations (Document Number)

|                                      |               |
|--------------------------------------|---------------|
| Data Sheet, Technical<br>Information | CPS3B-100-CV0 |
| Instructions and<br>Manuals          | CPS3B-100-CV0 |

---

### Classifications

|                                       |   |
|---------------------------------------|---|
| ETIM 6                                | EC001937 - Cable protection for installation duct |
| ETIM 7                                | EC001937 - Cable protection for installation duct |
| ETIM 8                                | EC001937 - Cable protection for installation duct |
| UNSPSC                                | 39131602  |
| WEEE Category                         | Product Not in WEEE Scope                         |
| IDEA Granular Category<br>Code (IGCC) | 5392 >> Expandable braided sleeving               |

---

### Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [ABB manufacturer](#):*

Other Similar products are found below :

[00800](#) [00802](#) [00808](#) [00810](#) [00816](#) [00820](#) [00821](#) [00822](#) [00846](#) [00850](#) [00851](#) [00852](#) [035-72775-2](#) [035-72775-21](#) [035-72775-3](#) [035-72775-625](#) [05045](#) [05169](#) [053-71411-3](#) [053-71814-123](#) [0913M](#) [10-100](#) [103-W-1/2](#) [10-405](#) [10-411](#) [10-417](#) [104-W-3/4](#) [104-W-FB-3/4](#) [10NPW](#) [10RC-10F](#) [10RC-14](#) [10RC-14X](#) [10RC-250F](#) [10RC-251T](#) [10RC-2577](#) [10RC-38X](#) [10RC-6](#) [10RC-6FLX](#) [10RC-6X](#) [10RC-8](#) [10RC-8FL](#) [11-002](#) [11735](#) [11736](#) [11737](#) [11738](#) [11739](#) [11740](#) [1213-TB](#) [124](#)