

General Information

| | |
|-------------------------------|---|
| Extended Product Type: | AF09-30-01-13 |
| Product ID: | 1SBL137001R1301 |
| EAN: | 3471523110137 |
| Catalog Description: | AF09-30-01-13 100-250V50/60HZ-DC Contactor |
| Long Description: | AF09 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage U_c min. ... U_c max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available. |

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

Ordering

| | |
|--------------------------------|---------------|
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85369085 |
| EAN: | 3471523110137 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Depth: | 77 mm |
| Product Net Height: | 86 mm |
| Product Net Weight: | 0.270 kg |
| Product Net Width: | 45 mm |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Width: | 87 mm |
| Package Level 1 Length: | 79 mm |
| Package Level 1 Height: | 47 mm |
| Package Level 1 Gross Weight: | 0.27 kg |
| Package Level 1 EAN: | 3471523110137 |
| Package Level 2 Units: | 54 piece |
| Package Level 2 Width: | 250 mm |
| Package Level 2 Length: | 300 mm |
| Package Level 2 Height: | 315 mm |
| Package Level 3 Units: | 1296 piece |
| Package Level 1 Units: | 1 piece |

Technical

| | |
|---|--|
| Number of Main Contacts NC: | 0 |
| Number of Auxiliary Contacts NO: | 0 |
| Number of Auxiliary Contacts NC: | 1 |
| Standards: | IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N°14 |
| Rated Operational Voltage: | Auxiliary Circuit 690 V Main Circuit 690 V |
| Rated Frequency (f): | Auxiliary Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current (I_{th}): | acc. to IEC 60947-4-1, Open Contactors $q = 40$ °C 35 A acc. to IEC 60947-5-1, $q = 40$ °C 16 A |
| Rated Operational Current AC-1 (I_e): | (690 V) 40 °C 25 A (690 V) 60 °C 25 A (690 V) 70 °C 22 A |
| Rated Operational Current AC-3 (I_e): | (220 / 230 / 240 V) 60 °C 9 A (380 / 400 V) 60 °C 9 A (415 V) 60 °C 9 A (440 V) 60 °C 9 A (500 V) 60 °C 9.5 A (690 V) 60 °C 7 A |

| | |
|---|---|
| Rated Operational Power AC-3 (P_e): | (220 / 230 / 240 V) 2.2 kW (380 / 400 V) 4 kW (400 V) 4 kW (415 V) 4 kW (440 V) 4 kW (500 V) 5.5 kW (690 V) 5.5 kW |
| Rated Operational Current AC-15 (I_e): | (220 / 240 V) 4 A (24 / 127 V) 6 A (400 / 440 V) 3 A (500 V) 2 A (690 V) 2 A |
| Rated Short-time Withstand Current (I_{cw}): | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A |
| Maximum Breaking Capacity: | cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 106 A |
| Maximum Electrical Switching Frequency: | AC-1 600 cycles per hour AC-15 1200 cycles per hour AC-2 / AC-4 300 cycles per hour AC-3 1200 cycles per hour DC-13 900 cycles per hour |
| Rated Operational Current DC-13 (I_e): | (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (24 V) 6 A / 144 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (48 V) 2.8 A / 134 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W (72 V) 1 A / 72 W |
| Rated Insulation Voltage (U_i): | acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V |
| Rated Impulse Withstand Voltage (U_{imp}): | 6 kV |
| Maximum Mechanical Switching Frequency: | 3600 cycles per hour |
| Rated Control Circuit Voltage (U_c): | 50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V |
| Operate Time: | Between Coil De-energization and NC Contact Closing 13...98 ms Between Coil De-energization and NO Contact Opening 11...95 ms Between Coil Energization and NC Contact Opening 38...90 ms Between Coil Energization and NO Contact Closing 40...95 ms |
| Connecting Capacity Main Circuit: | Flexible with Insulated Ferrule 1x 0.75...4 mm ² Flexible with Insulated Ferrule 2x 0.75...2.5 mm ² Flexible with Ferrule 1/2x 0.75...6 mm ² Rigid 1/2x 1...6 mm ² |
| Connecting Capacity Auxiliary Circuit: | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1...2.5 mm ² |
| Connecting Capacity Control Circuit: | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ² |
| Wire Stripping Length: | Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm |
| Degree of Protection: | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Terminal Type: | Screw Terminals |
| Number of Main Contacts NO: | 3 |

Environmental

| | |
|--|--|
| Climatic Withstand: | Category B according to IEC 60947-1 Annex Q |
| Maximum Operating Altitude Permissible: | 3000 m |
| Resistance to Vibrations acc. to IEC | 5 ... 300 Hz 4 g closed position / 2 g open position |

60068-2-6:**Resistance to Shock acc. to IEC 60068-2-27:**

Closed, Shock Direction: B1 25 g
 Open, Shock Direction: B1 5 g
 Shock Direction: A 30 g
 Shock Direction: B2 15 g
 Shock Direction: C1 25 g
 Shock Direction: C2 25 g

RoHS Status:

Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2008 Q1

Ambient Air Temperature:

Close to Contactor for Storage -60...+80 °C
 Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C
 Close to Contactor without Thermal O/L Relay -40 ... +70 °C

Technical UL/CSA**General Use Rating UL/CSA:**

(600 V AC) 25 A

Horsepower Rating UL/CSA:

(120 V AC) Single Phase 3/4 Hp
 (240 V AC) Single Phase 1-1/2 Hp
 (200 ... 208 V AC) Three Phase 2 Hp
 (220 ... 240 V AC) Three Phase 2 Hp
 (440 ... 480 V AC) Three Phase 5 Hp
 (550 ... 600 V AC) Three Phase 7-1/2 Hp

Tightening Torque UL/CSA:

Auxiliary Circuit 11 in-lb
 Control Circuit 11 in-lb
 Main Circuit 13 in-lb

Certificates and Declarations (Document Number)**Instructions and Manuals:**

1SBC101027M6801

ABS Certificate:

ABS_15-GE1349500-PDA_90682247

CB Certificate:

CB_SE_70855M1

CCC Certificate:

CCC_2010010304445624

Data Sheet, Technical Information:

1SBC101402D0201

Declaration of Conformity - CE:

1SBD250000U1000

DNV Certificate:

DNV-GL_E13871

EAC Certificate:

EAC_RU C-FR ME77 B01010

GL Certificate:

DNV-GL_E13871

GOST Certificate:

GOST_POCCFR.ME77.B07175.pdf

LR Certificate:

LRS_1300087E1

RINA Certificate:

RINA_ELE084013XG

RMRS Certificate:

RMRS_1400682124

RoHS Information:

1SBD251013E1000

UL Certificate:

UL_20140305-E312527_7_1

UL Listing Card:

E312527

Classifications**E-number:**

3210010

ETIM 4:

EC000066 - Magnet contactor, AC-switching

ETIM 5:

EC000066 - Magnet contactor, AC-switching

ETIM 6:

EC000066 - Power contactor, AC switching

UNSPSC:

39121529

Object Classification Code:

Q



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Contactors - Electromechanical category](#):

Click to view products by [ABB manufacturer](#):

Other Similar products are found below :

[686-117111](#) [686-120111](#) [686-924](#) [686-948](#) [70-901](#) [70-914](#) [MB-3D-6](#) [MC-22A/4-AC120V](#) [8-1616943-9](#) [8-1672124-5](#) [120-905](#) [A701U](#) [120-904](#) [154-905](#) [154-912](#) [154-913](#) [154-915](#) [154-902](#) [154-910](#) [AVR743D](#) [B6-40-00-84](#) [B7-40-00-84](#) [1616017-5](#) [MVDILM](#) [HP-11D-24](#) [P30C47A12D1-120](#) [P40C47A12D1-120](#) [CA7-72-00-24Z](#) [90-162](#) [9-1393132-2](#) [2NC4F0222](#) [A275KXXV2-120VAC](#) [ACC338UMM20](#) [AF80-30-11-13](#) [SZ-B1](#) [3GC2H0M22](#) [3NC1Q0A22](#) [3NC2H0A22](#) [42AF35AG](#) [42CF35AE](#) [42CF35AG](#) [42EF35AFR](#) [45CG10AFA](#) [45CG10AJA](#) [45CG10EJA](#) [45CG20AF](#) [45CG20AL](#) [45CG20EF](#) [45CG20EG](#) [45CG20EL](#)