

## General Information

<b>Extended Product Type:</b>	AF26Z-22-00-22
<b>Product ID:</b>	1SBL236501R2200
<b>EAN:</b>	3471523116825
<b>Catalog Description:</b>	AF26Z-22-00-22 48-130V50/60HZ-DC Contactor
<b>Long Description:</b>	AF26Z 4-pole contactors are used for controlling power circuits up to 690 V AC and 440 V DC. They are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...). AF..Z contactors include an electronic coil interface accepting a wide control voltage $U_c$ min. ... $U_c$ max. Only four coils cover control voltages between 24...250 V 50/60 Hz or 12...250 V DC. AF..Z contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF..Z contactors allow direct control by PLC-output $\geq 24$ V DC 500 mA and obtain a reduced holding coil consumption. AF..Z contactors withstand short voltage dips and voltage sags (SEMI F47-0706 compliance) between 24...250 V 50/60 Hz AF..Z contactors have built-in surge protection and do not require additional surge suppressors The AF... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 2 N.O. + 2 N.C. main poles, front and side-mounted add-on auxiliary contact blocks. (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369085
<b>EAN:</b>	3471523116825

## Dimensions

<b>Product Net Depth:</b>	101 mm
<b>Product Net Height:</b>	86 mm
<b>Product Net Weight:</b>	0.400 kg
<b>Product Net Width:</b>	45 mm

## Container Information

<b>Package Level 1 Width:</b>	87 mm
<b>Package Level 1 Length:</b>	103 mm
<b>Package Level 1 Height:</b>	47 mm
<b>Package Level 1 Gross Weight:</b>	0.4 kg
<b>Package Level 1 EAN:</b>	3471523116825
<b>Package Level 2 Units:</b>	36 piece
<b>Package Level 2 Width:</b>	250 mm
<b>Package Level 2 Length:</b>	300 mm
<b>Package Level 2 Height:</b>	315 mm
<b>Package Level 3 Units:</b>	864 piece
<b>Package Level 1 Units:</b>	1 piece

## Technical

<b>Number of Main Contacts NC:</b>	2
<b>Number of Auxiliary Contacts NO:</b>	0
<b>Number of Auxiliary Contacts NC:</b>	0
<b>Standards:</b>	IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N°14
<b>Rated Operational Voltage:</b>	Main Circuit 690 V
<b>Rated Frequency (f):</b>	Main Circuit 50 / 60 Hz
<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	acc. to IEC 60947-4-1, Open Contactors $q = 40$ °C 55 A
<b>Rated Operational Current AC-1 (<math>I_e</math>):</b>	(690 V) 40 °C 45 A (690 V) 60 °C 40 A (690 V) 70 °C 32 A
<b>Rated Operational Current AC-3 (<math>I_e</math>):</b>	(220 / 230 / 240 V) 60 °C 23.2 A (380 / 400 V) 60 °C 22 A (415 V) 60 °C 21.2 A (440 V) 60 °C 20 A (500 V) 60 °C 17.6 A (690 V) 60 °C 10.5 A

<b>Rated Operational Power AC-3 (P<sub>e</sub>):</b>	(220 / 230 / 240 V) 5.5 kW (400 V) 11 kW (415 V) 11 kW (440 V) 11 kW (500 V) 11 kW (690 V) 9 kW
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 55 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 450 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A
<b>Maximum Electrical Switching Frequency:</b>	AC-1 600 cycles per hour
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	6 kV
<b>Maximum Mechanical Switching Frequency:</b>	3600 cycles per hour
<b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>	50 Hz 48 ... 130 V 60 Hz 48 ... 130 V DC Operation 48 ... 130 V
<b>Operate Time:</b>	Between Coil De-energization and NC Contact Closing 13...98 ms Between Coil De-energization and NO Contact Opening 11...95 ms Between Coil Energization and NC Contact Opening 38...90 ms Between Coil Energization and NO Contact Closing 40...95 ms
<b>Connecting Capacity Main Circuit:</b>	Flexible with Insulated Ferrule 1x 1.5...16 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 1.5...16 mm <sup>2</sup> Flexible with Ferrule 1/2x 1.5...16 mm <sup>2</sup> Rigid 1/2x 1.5...16 mm <sup>2</sup>
<b>Connecting Capacity Control Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>
<b>Wire Stripping Length:</b>	Control Circuit 10 mm Main Circuit 12 mm
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
<b>Terminal Type:</b>	Screw Terminals
<b>Number of Main Contacts NO:</b>	2

## Environmental

<b>Climatic Withstand:</b>	Category B according to IEC 60947-1 Annex Q
<b>Maximum Operating Altitude Permissible:</b>	3000 m
<b>Resistance to Vibrations acc. to IEC 60068-2-6:</b>	5 ... 300 Hz 4 g closed position / 2 g open position
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	Closed, Shock Direction: A 30 g Closed, Shock Direction: B1 25 g Closed, Shock Direction: B2 15 g Closed, Shock Direction: C1 25 g Closed, Shock Direction: C2 25 g Open, Shock Direction: A 25 g Open, Shock Direction: B1 5 g Open, Shock Direction: B2 10 g Open, Shock Direction: C1 20 g Open, Shock Direction: C2 20 g
<b>RoHS Status:</b>	Following EU Directive 2011/65/EC
<b>Ambient Air Temperature:</b>	Close to Contactor for Storage -60...+80 °C Near Contactor for Operation in Free Air -40 ... +70 °C

## Technical UL/CSA

<b>General Use Rating UL/CSA:</b>	(600 V AC) 45 A
<b>Tightening Torque UL/CSA:</b>	Control Circuit 11 in·lb Main Circuit 22 in·lb

## Certificates and Declarations (Document Number)

<b>Instructions and Manuals:</b>	1SBC101027M6801
<b>ABS Certificate:</b>	ABS_15-GE1349500-PDA_90682247
<b>CB Certificate:</b>	CB_SE_70858M1
<b>CCC Certificate:</b>	CCC_2010010304445623
<b>Data Sheet, Technical Information:</b>	1SBC101425D0201

<b>Declaration of Conformity - CE:</b>	1SBD250001U1000
<b>DNV Certificate:</b>	DNV-GL_E13871
<b>EAC Certificate:</b>	EAC_RU C-FR ME77 B01010
<b>GL Certificate:</b>	DNV-GL_E13871
<b>GOST Certificate:</b>	GOST_POCCFR.ME77.B07175.pdf
<b>LR Certificate:</b>	LRS_1300087E1
<b>RINA Certificate:</b>	RINA_ELE084013XG
<b>RMRS Certificate:</b>	RMRS_1400682124
<b>RoHS Information:</b>	1SBD251015E1001
<b>UL Certificate:</b>	UL_20120918-E319322-3-1
<b>UL Listing Card:</b>	UL_E319322

### Classifications

<b>ETIM 4:</b>	EC000066 - Magnet contactor, AC-switching
<b>ETIM 5:</b>	EC000066 - Magnet contactor, AC-switching
<b>ETIM 6:</b>	EC000066 - Power contactor, AC switching
<b>UNSPSC:</b>	39121529
<b>Object Classification Code:</b>	Q



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Solid State Relays - Industrial Mount](#) category:*

*Click to view products by [ABB](#) manufacturer:*

Other Similar products are found below :

[6225XXASRS-DC3](#) [D2440-C](#) [H10CA4890](#) [D4875C](#) [D53TP50DH-10](#) [1395831-1](#) [BR312BY](#) [A-1326](#) [AQY210SXE01](#) [AQY221N2SYD01](#)  
[AQY414SXE01](#) [26532764](#) [H10CA4850](#) [H12CA4890VL](#) [RA2410-D06](#) [D1202F](#) [D53TP50-10](#) [W230E-1-12](#) [W230T-3-12](#) [W6125ASX-1](#)  
[W6225DSX-2](#) [W6240DSX-4](#) [W6240DTX-2](#) [1-1617030-3](#) [1-1617033-9](#) [1-1617033-7](#) [MS2-D2420](#) [MS2-D2430](#) [A-1440](#) [4-1617080-0](#)  
[RJ1P60V50E](#) [RN1F48I50](#) [70.362.1028.0](#) [7-1393030-8](#) [Z5.509.0828.0](#) [W230E-2-5](#) [G3RV-SR700-D AC110](#) [G3RV-SR500-AL AC100](#)  
[G3RV-SR500-D ACDC24](#) [G3RV-SR500-AL ACDC24](#) [G3RV-SR700-D ACDC24](#) [G3RV-SR700-AL ACDC24](#) [G3RV-SR500-D DC12](#)  
[G3RV-SR700-A ACDC24](#) [G3RV-SR500-A ACDC24](#) [2912138](#) [2912141](#) [SSRDAC10](#) [1613353](#) [1613349](#)