

General Information

Extended Product Type:	CAL4-11
Product ID:	1ISBN010120R1011
EAN:	3471523130043
Catalog Description:	CAL4-11 Auxiliary Contact Block
Long Description:	CAL4-11 Auxiliary Contact Block

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors Accessories

Ordering

EAN:	3471523130043
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Weight:	0.040 kg
---------------------	----------

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	125 mm
Package Level 1 Height:	20 mm
Package Level 1 Length:	125 mm
Package Level 1 Gross Weight:	0.04 kg
Package Level 1 EAN:	3471523130043
Package Level 2 Units:	300 piece
Package Level 3 Units:	5400 piece
Product Packing Type:	Bag

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2008 Q1
--------------	---

Technical UL/CSA

Tightening Torque UL/CSA:	Auxiliary Circuit 11 in·lb
---------------------------	----------------------------

Additional Information

Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1...2.5 mm ²
Conventional Free-air Thermal Current (I _{th}):	acc. to IEC 60947-5-1, q = 40 °C 16 A
IIT Publishing Status:	Level 0 - Information enabled
Maximum Electrical Switching Frequency:	AC-15 1200 cycles per hour DC-13 900 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Mounted Auxiliary Contacts:	1 NO, 1 NC
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Product Main Type:	Accessories for Block Contactors
Product Name:	Auxiliary Contact Block
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp}):	6 kV
Rated Insulation Voltage (U _i):	acc. to UL/CSA 600 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Operational Current AC-15 (I _e):	(220 / 240 V) 4 A (24 / 127 V) 6 A (400 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Rated Operational Current DC-13	(110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W

(I_e): (220 V) 0.27 A / 60 W
(24 V) 6 A / 144 W
(250 V) 0.27 A / 68 W
(400 V) 0.15 A / 60 W
(48 V) 2.8 A / 134 W
(500 V) 0.13 A / 65 W
(600 V) 0.1 A / 60 W
(72 V) 1 A / 72 W

Rated Operational Voltage: Auxiliary Circuit 24 ... 690 V

Rated Short-time Withstand Current (I_{cw}): for 0.1 s 140 A
for 1 s 100 A

RoHS Date: 20090609

Suitable For: AF09
AF12
AF16
AF26
AF30
AF38
AF40
AF52
AF65
AF80
AF96
NF

Terminal Type: Screw Terminals

Tightening Torque: Auxiliary Circuit 1.2 N·m

Wire Stripping Length: Auxiliary Circuit 10 mm

Certificates and Declarations (Document Number)

ABS Certificate: ABS_15-GE1349500-PDA_90682247

CB Certificate: CB_SE_70921

CCC Certificate: CCC_2011010304496319

Data Sheet, Technical Information: 1SBC100173C0201

Declaration of Conformity - CE: 1SBD250007U1000

EAC Certificate: EAC_RU C-FR ME77 B01048

GOST Certificate: GOST_POCCFR.ME77.B07175.pdf

LR Certificate: LRS_1300087E1

RINA Certificate: RINA_ELE084013XG

RMRS Certificate: RMRS_1300133124

RoHS Information: 1SBD251010E1000

UL Certificate: UL_20091128-E252354-3-1

Classifications

E-number: 3211435

ETIM 4: EC002498 - Accessories for low-voltage switch technology

ETIM 5: EC002498 - Accessories for low-voltage switch technology

ETIM 6: EC002498 - Accessories for low-voltage switch technology

Object Classification Code: K

UNSPSC: 39121500



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ABB manufacturer:](#)

Other Similar products are found below :

[F204AC-40/0.1](#) [F362-25/0.03](#) [AF09-30-10-11](#) [AF116-30-00-13](#) [AF460-30-11-68](#) [N22E-84](#) [1SAZ721201R1008](#) [1SBL277001R4100](#)
[1SDA057197R1](#) [1SFA611143R1101](#) [1SFA611143R1103](#) [1SFA611211R1001](#) [1SFA611212R1103](#) [1SFA611215R1001](#) [1SFA611285R1002](#)
[1SFA619100R3015](#) [OVR1N160277PS](#) [KT3LD](#) [RV-BC6/60](#) [S201-B16](#) [S202-B40](#) [2CCA703155R0001](#) [2CDS272001R0105](#) [AF753011RT-](#)
[72](#) [1SAM350000R1008](#) [1SFA611200R1104](#) [1SFA611213R1101](#) [1SFA611213R1103](#) [1SFA616160R1006](#) [1SLM004102A1108](#)
[1SPE007717F0721](#) [1SVR427026R0000](#) [1SVR730885R3300](#) [2CCA703250R0001](#) [2CSF202001R3630](#) [2CSF202001R4630](#) [TV10-8F](#) [3304M](#)
[L-10-50R-9-C](#) [DF3416FRAB0](#) [MS116-12](#) [S202-D10](#) [S203-K16](#) [5STP 16F2800](#) [CT-MBS.22S](#) [AF12Z-30-01-20](#) [AF38Z-22-00-23](#)
[AF40-30-00-11](#) [AF65-30-00-13](#) [AF96-30-00-41](#)