
# Thomas&Betts





### **Ring Terminal T&B Catalog Number:**

RZ22-4

**UPC Number:** 78621080453

Status: Active

**Description:** 

Nylon Insulated Ring Terminal, Length .65 Inches, Width .21 Inches, Maximum Insulation .083, Bolt Hole #4, Wire Range #26-#22 AWG, Color Yellow, Copper, Tin Plated

| -   |              |                   |
|-----|--------------|-------------------|
| 1 A | $^{\prime}$  | <br>$\sim$        |
| w   | / <b>-</b> K | <br><b>&gt;</b> - |
|     |              |                   |

US Cutsheet PDF Catalog Link http://www-public.tnb.com/contractor/docs/

stakon.pdf

#### **Features**

Self-insulated with high dieletric-strength nylon sleeves. An inner bronze insulation grip sleeve lengthens the flexing radius of the conductor and eliminates conductor creep.

|                 | eliminates conductor creep. |
|-----------------|-----------------------------|
| General         |                             |
|                 |                             |
| Insulation Type | Insulated Nylon             |
| Terminal Series | RZ                          |
| Material        | Copper                      |
|                 |                             |

| Dimension Information |                     |
|-----------------------|---------------------|
| Stud Size             | #4                  |
| Wire Range            | 26-22               |
| Color                 | Yellow              |
| Finish                | Electro -Tin Plated |
| Material              | Copper              |
| Terminal Series       | RZ                  |
| insulation Type       | insulated Nylon     |

| Maximum Insulation (inches) | .083 |  |
|-----------------------------|------|--|
| Stock Thickness             | .02  |  |
| A (inches)                  | .65  |  |
| B (inches)                  | .21  |  |
| C (inches)                  | .20  |  |
| M (inches)                  | .54  |  |
| Chasifications              |      |  |

| Specifications     |       |  |
|--------------------|-------|--|
| Temperature Rating | 105°C |  |
| Voltage Rating     | 600V  |  |
|                    |       |  |

| 8 8                 |                      |
|---------------------|----------------------|
| Flammability Rating | UL 94 V-2            |
| Tooling             |                      |
|                     |                      |
| Tool Charts         | Available on Website |
| Application Tools   | WT1452               |
| Recommended Tool    | ERG4006              |
| Packaging           |                      |
|                     |                      |
| T&B Order Multiple  | 100                  |
| T&B Inner Pack      | 100                  |
| Package in Units    | 500                  |
| Package Type        | Standard             |
| T&B Sold in UOM     | Each                 |
| T&B Weight Per UOM  | 1.25 lbs. per 1000   |
| Application Support |                      |
|                     |                      |

#### **T&B Sales Drawings** wsd-000204 Available on Website Overview



| Wire Guide Tables | Available on Website |
|-------------------|----------------------|
| Certifications    |                      |
| RoHS Compliance   | Yes                  |

#### For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

### Click to view similar products for abb manufacturer:

Other Similar products are found below:

TV10-516R 017667013 RF727 2CMA100178R1000 2CMA100163R1000 5SDD 92Z0401 ESV14-BS EZS-21-250 F204AC-40/0.03 F36225/0.03 GJL1211201R8000 GJL1211501R8000 GJL1213001R0017 GJL1213001R0101 GJL1311001R0011 GJL1311001R0101
GJL1311001R8010 GJL1311201R0001 GJL1313001R0011 GJL1313001R0101 GJL1317201R0001 A40-30-10-84 AF09-30-01-11
AF460-30-11-68 1455 B14-250 EF45-30 ERG297 HSC2-20 ISAM201904R1001 ISAM350000R1003 ISAZ721201R1009
ISAZ721201R1014 ISAZ721201R1025 ISBL157001R1310 ISBL277001R1300 ISBL277001R4100 ISBL367001R1300
ISBL387001R4100 ISBN010110R1001 ISBN010110R1010 ISBN010140R1022 ISBN010140R1122 ISDA057197R1 ISFA611101R1002
ISFA611130R1103 ISFA611131R1101 ISFA611143R1101 ISFA611202R1108 ISFA611203R1108