

AEACBD050018-SG3



50.0 x 50.0 x 18.0 mm RoHS/RoHS II Compliant MSL = 1

Features

- High positioning accuracy
- GPS/GLONASS/BeiDou/Galileo band support
- IP67 Rated
- Gain of 5.0 dBic
- Active GNSS with integrated LNA
- High LNA gain of 34 dB
- Low VSWR of 1.5
- RHCP polarization
- Magnetic mounting
- Improved GNSS reliability

Applications

- GPS/GLONASS/BeiDou/Galileo applications
- IoT
- M2M
- Surveillance
- Fleet management and asset tracking
- Autonomous driving
- Telematics
- Agriculture
- Instrumentation
- Survey

Electrical Specifications

| Parameters | Min. | Тур. | Max. | Units | Note |
|-----------------|------|-----------------|------|-------------------------------------|-------------|
| Frequency Range | | 1561.098 ~ 1602 | | MHz | |
| VSWR | | | 1.5 | | |
| Polarization | RHCP | | | Right Hand Circular Polarization | |
| Impedance | | 50 | | Ω | |
| Gain | | 5 | | dBic | @PCB Zenith |
| Axial Ratio | | | 3 | dB | |

| LNA Parameters | Min. | Тур. | Max. | Units | Note |
|---------------------|------|------|------|-------|------|
| Gain | 32 | 34 | 36 | dB | |
| VSWR | | | 2.0 | | |
| Noise Figure | | | 1.5 | dB | |
| Supply Voltage | | 3~5 | | V | DC |
| Current Consumption | | | 20 | mA | |

Mechanical Characteristics

| Parameters | Description |
|----------------|-------------|
| Connector | SMA |
| Cable Type | RG174/3M |
| Mounting | Magnet |
| Radom Material | ABS |





AEACBD050018-SG3




50.0 x 50.0 x 18.0 mm RoHS/RoHS II Compliant MSL = 1

Environmental Characteristics

| Parameters | Description |
|-----------------------|-------------------------------------------|
| Ingress Protection | IP67 rated |
| Operating temperature | -40°C to +85°C |
| Relative Humidity | Up to 95 % |
| Vibration | 10 to 55 Hz with 1.5 mm amplitude 2 hours |

Dimensions



Product Image








AEACBD050018-SG3



50.0 x 50.0 x 18.0 mm RoHS/RoHS II Compliant MSL = 1


VSWR



Radiation Patterns:

2D-Pattern

Frequency: --- 1561 --- 1575 --- 1602 XY - Plane



ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.






AEACBD050018-SG3



50.0 x 50.0 x 18.0 mm RoHS/RoHS II Compliant MSL = 1


Radiation Patterns:




YZ - Plane

3D- Pattern

Frequency: 1561 MHz



Frequency: 1575.42 MHz



Frequency: 1602 MHz

Packaging

The carton weighs of 15 Kgs and has 100 pieces in a dimension of 70.0 x 32.0 x 16.0 cm.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Abracon manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF EXB144SM C37 MAF94051 GD35-17P-NF P1744 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393