

# Mini Drum Core Inductor

AIUR-02H Series



RoHS/RoHS II compliant



12.0 x  $\phi$ 8.5 mm

## FEATURES:

- Ferrite core with heat shrink tube
- High Reliability

## APPLICATIONS:

- Switching Power Supplies
- Noise Filtering
- DC to DC Converters
- Electronic Household Appliances
- Buzzers and Alarm Systems
- Television and Audio Equipment

## STANDARD SPECIFICATIONS:

PARAMETERS	
ABRACON P/N:	AIUR-02H Series
Operating temperature:	-40°C to + 125°C (including self-heating)
Storage temperature:	-40°C to + 125°C

Part Number	Inductance	Tolerance	DCR (Max)	Saturation Current (Max)	Temperature Rise Current (Max)	Inductance Code
Units	$\mu$ H	%	$\Omega$	A		
Symbol	L	K, M, N	DCR	Isat	I <sub>DC</sub>	
AIUR-02H-1R0	1.0	N	0.021	8.60	3.5	1R0N
AIUR-02H-2R2	2.2	M	0.026	6.30	3.2	2R2M
AIUR-02H-3R3	3.3	M	0.030	5.40	2.7	3R3M
AIUR-02H-4R7	4.7	M	0.034	4.60	2.5	4R7M
AIUR-02H-6R8	6.8	M	0.037	4.10	2.3	6R8M
AIUR-02H-100	10	K	0.044	3.40	2.0	100K
AIUR-02H-120	12	K	0.049	3.10	1.9	120K
AIUR-02H-150	15	K	0.054	2.90	1.8	150K
AIUR-02H-180	18	K	0.058	2.66	1.6	180K
AIUR-02H-220	22	K	0.065	2.40	1.4	220K
AIUR-02H-270	27	K	0.072	2.20	1.3	270K
AIUR-02H-330	33	K	0.080	2.05	1.1	330K
AIUR-02H-390	39	K	0.101	1.85	1.1	390K
AIUR-02H-470	47	K	0.121	1.77	0.99	470K
AIUR-02H-560	56	K	0.145	1.48	0.90	560K
AIUR-02H-680	68	K	0.161	1.36	0.81	680K
AIUR-02H-820	82	K	0.174	1.30	0.76	820K
AIUR-02H-101	100	K	0.21	1.40	0.72	101K
AIUR-02H-121	120	K	0.24	1.25	0.67	121K
AIUR-02H-151	150	K	0.27	1.15	0.61	151K
AIUR-02H-181	180	K	0.30	1.08	0.54	181K
AIUR-02H-221	220	K	0.34	1.00	0.50	221K
AIUR-02H-271	270	K	0.39	0.90	0.41	271K
AIUR-02H-331	330	K	0.62	0.78	0.39	331K
AIUR-02H-391	390	K	0.69	0.74	0.37	391K
AIUR-02H-471	470	K	0.77	0.68	0.32	471K
AIUR-02H-561	560	K	0.83	0.64	0.30	561K
AIUR-02H-681	680	K	0.94	0.59	0.27	681K
AIUR-02H-821	820	K	1.03	0.56	0.24	821K
AIUR-02H-102	1000	K	1.30	0.51	0.22	102K
AIUR-02H-222	2200	K	3.00	0.20	0.10	222K

## Test Conditions and equipments

Test frequency: 1KHz, 0.25V

Isat: 30% inductance drops from initial value.

I<sub>DC</sub>: The DC current at which the temperature rise is 40°C max

# Mini Drum Core Inductor

AIUR-02H Series



RoHS/RoHS II compliant



12.0 x  $\phi$ 8.5 mm

## ➤ OPTIONS & PART IDENTIFICATION:


AIUR-02H  -

Lead Length
Blank: 5mm

Inductance Code
Please refer to the Electrical Spec Table

Tolerance
K: $\pm$ 10%
M: $\pm$ 20%
N: $\pm$ 30%

## ➤ MECHANICAL DIMENSIONS:



A	B	C	D	E
9.0 (max)	12.0 (max)	5.0 $\pm$ 1	5Ref	0.6

Dimension: inch/mm

# Mini Drum Core Inductor

AIUR-02H Series




RoHS/RoHS II compliant



12.0 x  $\phi$ 8.5 mm

## WAVE SOLDERING PROFILE:



**ATTENTION:** Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fixed Inductors](#) category:*

*Click to view products by [Abracon](#) manufacturer:*

Other Similar products are found below :

[CR43NP-680KC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [CTX32CT-100](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHL1JCTTD12NJ](#)  
[PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-62892NL](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#)  
[9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2-2R2TR](#) [HC2LP-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#)  
[RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#) [RCR110DNP-331L](#)  
[DH2280-4R7M](#) [DS1608C-106](#) [ASPI-4020HI-R10M-T](#) [B10TJ](#) [B82477P4333M](#) [B82498B3101J000](#) [B82498B3680J000](#) [ELJ-RE27NJF2](#)  
[1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#) [1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#)