1-PORT 10GBASE-T SMD RJ45 WITH INTEGRATED **MAGNETICS**



16.10 x 13.87 x 25.68mm **RoHS/RoHS II Compliant**

ARJE-1034

FEATURES

- High speed 10GBase-T
- 10/100/1000Base-T compatibility
- Surface mount device
- Wide -40C to 85C operating temperature range
- Integrated magnetics
- Integrated shielding and metal fingers for excellent EMI performance


APPLICATIONS

- Networking equipment
- Industrial IoT/IoT
- Video IP cameras
- Machine-to-machine (M2M)
- Industrial process control
- Servers and cloud computing
- High performance computing (HPC)
- Network interface cards (NIC)
- Media converters

STANDARD SPECIFICATIONS

Parameters	Minimum	Typical	Maximum	Units	Notes
Turn Ratio (±3%)		1CT:1CT			
Inductance	100			uН	100kHz, 0.1Vrms
Insertion Loss			-3.0	dB	100KHz
			-2.0		1-400MHz
Return Loss	-18.0			dB	1-40MHz
	19-10Log(F/40)*				40-500MHz
Crosstalk	-30.0			dB	1-100MHz
	-20.0				100-500MHz
CM-DMRR	-30.0			dB	1-250MHz
	-20.0				250-500MHz
Hipot		1500 Vrms min		Pri to Sec	
Operating Temperature	-40		85	С	See options

PART NUMBER IDENTIFICATION



ABRACON LLC

5101 Hidden Creek Lane Spicewood TX 78669 Phone: 512-371-6159 | Fax: 512-351-8858 For terms and conditions of sale please visit: www.abracon.com

REVISED: 09/26/2016

> ABRACON IS ISO9001-2008 CERTIFIED


1-PORT 10GBASE-T SMD RJ45 WITH INTEGRATED MAGNETICS




ARJE-1034

16.10 x 13.87 x 25.68mm RoHS/RoHS II Compliant

MECHANICAL DIMENSIONS: mm (unless otherwise specific, all tolerances are $\pm 0.01/0.25$)








5101 Hidden Creek Lane Spicewood TX 78669 Phone: 512-371-6159 | Fax: 512-351-8858 For terms and conditions of sale please visit: www.abracon.com **REVISED:** 09/26/2016

ABRACON IS ISO9001-2008 CERTIFIED


1-PORT 10GBASE-T SMD RJ45 WITH INTEGRATED MAGNETICS




ARJE-1034

16.10 x 13.87 x 25.68mm RoHS/RoHS II Compliant

SCHEMATIC





Zone	Description	Temperature	Time
1	Preheat	$\begin{array}{c} T_{\rm SMIN} \sim T_{\rm SMAX} \\ 150 ^{\rm o}{\rm C} \sim 200 ^{\rm o}{\rm C} \end{array}$	60 ~ 180 sec.
2	Reflow	T _L 217°C	$60 \sim 150 \text{ sec.}$
3	Peak heat	Т _Р 245°С	20 ~ 40 sec.



REVISED: 09/26/2016
ane Spicewood TX 78669
ABRACON IS

1-PORT 10GBASE-T SMD RJ45 WITH INTEGRATED MAGNETICS





ARJE-1034

16.10 x 13.87 x 25.68mm RoHS/RoHS II Compliant

PACKAGING

T: 110 pcs/reel





NOTES

- 1. The parts are manufactured in accordance with this specification. If other conditions and specifications which are required for this specification, please contact ABRACON for more information.
- 2. ABRACON will supply the parts in accordance with this specification unless we receive a written request to modify prior to an order placement.
- 3. In no case shall ABRACON be liable for any product failure from in appropriate handling or operation of the item beyond the scope of this specification.
- 4. When changing your production process, please notify ABRACON immediately.
- 5. ABRACON LLC's products are COTS Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. ABRACON's products are not specifically designed for Military, Aviation, Aerospace, Life- dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from ABRACON LLC is required. Please contact ABRACON LLC for more information.
- 6. All specifications and Marking will be subject to change without notice.

REVISED: 09/26/2016

ABRACON IS ISO9001-2008 CERTIFIED



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Abracon manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L 155302-001