

## REGULATORY COMPLIANCE

|  |  |  |  |   |
|--|--|--|--|---|
|  <p><b>Lead Free</b><br/>COMPLIANT</p> |  <p><b>EU RoHS</b><br/>2011/65 +<br/>2015/863<br/>COMPLIANT</p> |  <p><b>China RoHS</b><br/>COMPLIANT</p> |  <p><b>REACH</b><br/>SVHC<br/>COMPLIANT</p> |  <p><b>DRC</b><br/>CONFLICT<br/>FREE</p> |
|--|--|--|--|---|


## ITEM DESCRIPTION

Quartz Crystal Clock Oscillators XO (SPXO) LVCMOS (CMOS) 3.3Vdc 4 Pad 5.0mm x 7.0mm Ceramic Surface Mount (SMD)


## ELECTRICAL SPECIFICATIONS

|  |  |
|--|--|
| <b>Nominal Frequency</b>   | 1MHz to 155.52MHz  |
| <b>Frequency Tolerance/Stability</b>                               | Inclusive of all conditions: Calibration Tolerance at 25°C, Frequency Stability over the Operating Temperature Range, Supply Voltage Change, Output Load Change, First Year Aging at 25°C, Shock, and Vibration<br>±100ppm Maximum<br>±20ppm Maximum<br>±25ppm Maximum<br>±50ppm Maximum |
| <b>Aging at 25°C</b>   | ±5ppm/year Maximum   |
| <b>Operating Temperature Range</b>                                 | 0°C to +70°C<br>-40°C to +85°C   |
| <b>Supply Voltage</b>  | 3.3Vdc ±10%  |
| <b>Input Current</b>   | No Load<br>35mA Maximum  |
| <b>Output Voltage Logic High (V<sub>OH</sub>)</b>                  | I <sub>OH</sub> = -8mA<br>2.7Vdc Minimum   |
| <b>Output Voltage Logic Low (V<sub>OL</sub>)</b>                   | I <sub>OL</sub> = +8mA<br>0.5Vdc Maximum   |
| <b>Rise/Fall Time</b>  | Measured at 20% to 80% of waveform<br>6nSec Maximum over Nominal Frequency of 1MHz to 70MHz<br>4nSec Maximum over Nominal Frequency of 70.000001MHz to 155.52MHz   |
| <b>Duty Cycle</b>  | Measured at 50% of waveform<br>50 ±10(%)<br>50 ±5(%)   |
| <b>Load Drive Capability</b>                                       | 30pF Maximum over Nominal Frequency of 1MHz to 70MHz<br>15pF Maximum over Nominal Frequency of 70.000001MHz to 155.52MHz   |
| <b>Output Logic Type</b>   | CMOS   |
| <b>Pin 1 Connection</b>  | Tri-State (High Impedance)   |
| <b>Tri-State Input Voltage (V<sub>IH</sub> and V<sub>IL</sub>)</b> | 70% of V <sub>DD</sub> Minimum to enable output, 20% of V <sub>DD</sub> Maximum to disable output, No Connect to enable output.  |
| <b>Absolute Clock Jitter</b>                                       | ±250pSec Maximum, ±100pSec Typical   |
| <b>One Sigma Clock Period Jitter</b>                               | ±50pSec Maximum, ±40pSec Typical   |
| <b>Start Up Time</b>   | 10mSec Maximum   |
| <b>Storage Temperature Range</b>                                   | -55°C to +125°C  |


## PART NUMBERING GUIDE



**MECHANICAL DIMENSIONS**



**SUGGESTED SOLDER PAD LAYOUT**




| PIN | CONNECTION     |
|-----|----------------|
| 1   | Tri-State      |
| 2   | Ground         |
| 3   | Output         |
| 4   | Supply Voltage |


All Tolerances are  $\pm 0.1$

**All Dimensions in Millimeters**

OUTPUT WAVEFORM & TIMING DIAGRAM



## TEST CIRCUIT FOR CMOS OUTPUT



**Note 1:** An external  $0.1\mu\text{F}$  low frequency tantalum bypass capacitor in parallel with a  $0.01\mu\text{F}$  high frequency ceramic bypass Capacitor close to the package ground and  $V_{DD}$  pin is required.

**Note 2:** A low capacitance ( $<12\text{pF}$ ), 10X attenuation factor, high impedance ( $>10\text{Mohms}$ ), and high bandwidth ( $>300\text{MHz}$ ) passive Probe is recommended.



**Note 3:** Capacitance value  $C_L$  includes sum of all probe and fixture capacitance.

**TAPE & REEL DIMENSIONS**


Quantity per Reel: 1,000 Units

All Dimensions in Millimeters

Compliant to EIA-481



**RECOMMENDED SOLDER REFLOW METHOD**




**HIGH TEMPERATURE INFRARED/CONVECTION**

|   |   |
|---|---|
| <b>TS MAX to TL (Ramp-up Rate)</b>                    | 3°C/Second Maximum                                |
| <b>Preheat</b>  |   |
| - Temperature Minimum (T <sub>S</sub> MIN)            | 150°C   |
| - Temperature Typical (T <sub>S</sub> TYP)            | 175°C   |
| - Temperature Maximum(T <sub>S</sub> MAX)             | 200°C   |
| - Time (t <sub>S</sub> MIN)                           | 60 - 180 Seconds                                  |
| <b>Ramp-up Rate (TL to TP)</b>                        | 3°C/Second Maximum                                |
| <b>Time Maintained Above:</b>                         |   |
| - Temperature (T <sub>L</sub> )                       | 217°C   |
| - Time (t <sub>L</sub> )                              | 60 - 150 Seconds                                  |
| <b>Peak Temperature (TP)</b>                          | 260°C Maximum for 10 Seconds Maximum              |
| <b>Target Peak Temperature(TP Target)</b>             | 250°C +0/-5°C                                     |
| <b>Time within 5°C of actual peak (t<sub>p</sub>)</b> | 20 - 40 Seconds                                   |
| <b>Ramp-down Rate</b>                                 | 6°C/Second Maximum                                |
| <b>Time 25°C to Peak Temperature (t)</b>              | 8 Minutes Maximum                                 |
| <b>Moisture Sensitivity Level</b>                     | Level 1   |
| <b>Additional Notes</b>                               | Temperatures shown are applied to body of device. |

**High Temperature Manual Soldering**

260°C Maximum for 5 Seconds Maximum, 2 times Maximum. (Temperatures shown are applied to body of device.)

**RECOMMENDED SOLDER REFLOW METHOD**



**LOW TEMPERATURE INFRARED/CONVECTION 240°C**

|  |  |
|--|--|
| TS MAX to TL (Ramp-up Rate)                | 5°C/Second Maximum                                     |
| <b>Preheat</b>                             |  |
| - Temperature Minimum (T <sub>s</sub> MIN) | N/A  |
| - Temperature Typical (T <sub>s</sub> TYP) | 150°C  |
| - Temperature Maximum(T <sub>s</sub> MAX)  | N/A  |
| - Time (t <sub>s</sub> MIN)                | 60 - 120 Seconds                                       |
| Ramp-up Rate (TL to TP)                    | 5°C/Second Maximum                                     |
| <b>Time Maintained Above:</b>              |  |
| - Temperature (T <sub>L</sub> )            | 150°C  |
| - Time (t <sub>L</sub> )                   | 200Seconds Maximum                                     |
| Peak Temperature (TP)                      | 240°C  |
| Target Peak Temperature(TP Target)         | 240°C Maximum 2 Times/230°C Maximum 1Time              |
| Time within 5°C of actual peak (tp)        | 10 Seconds Maximum 2 Times / 80 Seconds Maximum 1 Time |
| Ramp-down Rate                             | 5°C/Second Maximum                                     |
| Time 25°C to Peak Temperature (t)          | N/A  |
| Moisture Sensitivity Level                 | Level 1  |
| Additional Notes                           | Temperatures shown are applied to body of device.      |

**Low Temperature Manual Soldering**

185°C Maximum for 10 Seconds Maximum, 2 times Maximum. (Temperatures shown are applied to body of device.)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard Clock Oscillators](#) category:*

*Click to view products by [Abracon](#) manufacturer:*

Other Similar products are found below :

[601252](#) [F335-25](#) [F535L-33.333](#) [F535L-50](#) [ASV-20.000MHZ-LR-T](#) [MXO45HS-2C-66.6666MHZ](#) [NBXDBB017LN1TAG](#) [SiT1602BI-22-33E-50.000000E](#) [SiT8209AI-32-33E-125.000000](#) [SIT8918AA-11-33S-50.000000G](#) [SM4420TEV-40.0M-T1K](#) [SMA4306-TL-H](#) [F335-24](#) [F335-40](#) [F535L-10](#) [F535L-12](#) [F535L-16](#) [F535L-24](#) [F535L-27](#) [PE7744DW-100.0M](#) [ASF1-3.686MHZ-N-K-S](#) [ASV-4.000MHZ-LCS-T](#) [XLH735025.000JU4I8](#) [XLP725125.000JU6I8](#) [XO57CTECNA3M6864](#) [601251](#) [EP16E7E2H26.000MTR](#) [SiT8503AI-18-33E-0.200000X](#) [SIT8918AA-11-33S-16.000000G](#) [SIT9122AI2C233E300.000000X](#) [XO37CTECNA20M](#) [XO3003](#) [9120AC-2D2-33E212.500000](#) [9102AI-243N25E100.000000](#) [8208AC-82-18E-25.000000](#) [8008AI-72-XXE-24.545454E](#) [8004AC-13-33E-133.33000X](#) [AS-4.9152-16-SMD-TR](#) [ASFL1-48.000MHZ-LC-T](#) [632L3I004M00000](#) [SIT8920AM-31-33E-25.0000](#) [DSC1028DI2-019.2000](#) [9121AC-2C3-25E100.000000](#) [9102AI-233N33E100.00000X](#) [9102AI-233N25E200.000000](#) [9102AI-232H25S125.000000](#) [9102AI-133N25E200.000000](#) [9102AC-283N25E200.000000](#) [9001AC-33-33E1-30.000](#) [3921AI-2CF-33NZ125.000000](#)