




Rev	AWO #	Description	Date	Appr
-		RELEASED	4/12/05	

APPROVED: _____

DATE: _____ TITLE: _____



Positions: 2 thru 20
 A = .156 [3.96] x No. of Positions + .016 [0.40]
 B = .156 [3.96] x No. of Spaces

SPECIFICATIONS:
 Material:
 Insulator: Nylon 66, rated UL 94V-2
 Insulator color: White
 Electrical:
 Operating voltage: 250 VAC max
 Current rating: 5 Amps max
 Insulation resistance: 1,000 Mohms min
 Dielectric withstanding voltage: 1,500 VAC for 1 minute
 Temperature Rating:
 Operating temperature: -25°C to +85°C
 Environmental:
 Lead free, RoHS compliant

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED
 INCHES HOLES
 .X ± .10 ØXX ± .10
 .XX ± .020 ØXXX ± .015
 .XXX ± .015 ØXXXX ± .010

DRAWN		SS	4/12/05	TITLE		.156 [3.96] WIRE HOUSING	
CHECKED				SIZE	PART NO.	ADAM TECH	
APPROVED				X	MTB-XX	909 Rahway Avenue, Union, NJ 07083	
				REF:	SCALE: NTS	Phone: 908-687-5000 Fax: 908-687-5710	
						REV.	



6 5 4 3 2 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Adam](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#) [CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)