


3U CompactPCI Peripheral Cards

PMC Modules

cPCI-8217/cPCI-8217R

3U CompactPCI®/PXI VGA/LCD Interface Card


- PICMG® 2.0 32-bit/33 MHz CompactPCI® specification
- SMI-721 graphic controller with 8 M built-in VRAM
- Max. 1280 x 1024, 24-bit true color
- On-board 44-pin LCD interface, LCD brightness adjustable
- cPCI-8217 is PXI compatible
- cPCI-8217R is a 50 mm RTM with J2 and rear I/O



cPCI-7841

Dual-port Isolated CAN Interface Card

- PICMG® 2.0 Rev 2.1
- Dual-independent CAN network operation
- Up to 1 Mbps programmable transfer rate
- 16 MHz CAN controller frequency
- 2500 V_{RMS} optical isolation
- Direct memory mapping to the CAN controllers
- Powerful master interface for CAN bus protocols
- Rear I/O available on cPCI-7841R



cPCI-3544

4-Port RS-422/485 Isolated Serial Communications Card

- 32-bit CompactPCI®, PICMG® 2.0 Rev 2.1
- Plug-and-play, IRQ & I/O address automatically assigned by PCI BIOS
- Four asynchronized communications ports with intelligent buffer
- Four RS-422/485 ports
- 2500 V_{RMS} isolation voltage
- Supports multiple OS
- Surge protectors
- Rugged DB37 connector
- Only supports CompactPCI interface 5 V (I/O)



cPCI-8273

3U CompactPCI® 3-port IEEE-1394 Card

- PICMG® 2.0 32-bit/33 MHz CompactPCI® specification
- VIA VT6306 IEEE-1394a controller
- Provides three ports, up to 400 Mbps
- Supports OHCI compliant programming interface
- Rear I/O version available upon request



PMC-8246

Dual-Gigabit Ethernet Ports PCI-X - PMC Module with Failover Function

- Dual-Gigabit Ethernet ports
- Supports PCI-X bus up to 133 MHz
- Failover capability during system power off or software halt
- Software programmable failover control
- DIP Switch selectable failover control
- Programmable watchdog timer, WDT status read-back
- Intel® - PMC Module Boot Agent BIOS



PMC-8681

2-Port RS-232, 2-Port RS-232/485/422 UART PMC Module

- PMC IEEE P1386.1 Spec. 32-bit/33 MHz PCI - PMC Module
- 4-port Serial UART OXFORD OX16 controller
- Ports 1, 2 support RS-232 (two DB-9 front panel connectors)
- Ports 3, 4 support RS-232/422/485 jumper selectable
- Four on-board headers for all four ports



PMC-8676

Quad-USB v2.0 Ports PMC Module

- PMC IEEE P1386.1 Spec. 32-bit/33 MHz PCI
- Four USB 2.0 ports
- Philips ISP1561 Hi-Speed USB PCI host controller
- Module host controller
- Supports all Hi-Speed USB transfer speed modes
- High-speed (480 Mb/s), full-speed (12 Mb/s) and low-speed (1.5 Mb/s)



PMC-8219

PMC VGA Module

- PMC IEEE P1386.1 Spec. 32-bit/33 MHz PCI
- ATI Rage XL graphic controller with 16 MB VRAM
- Supports up to 1280 x 1024 VGA display in 24-bit true color
- High performance, 2D, 3D, and video acceleration
- ACPI, VESA DPMS, and VESA DDC 2-bit compliant



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) category:

Click to view products by [ADLINK Technology](#) manufacturer:

Other Similar products are found below :

[IFD8520](#) [cPCI-3544](#) [422CON](#) [ATX6022/14GP7](#) [ATX6022/8](#) [AX93221-24/48](#) [FC6A-EXM2](#) [OPT8AP-AE](#) [96RMKVM-19V1C-A](#) [60016-011](#) [60016-014](#) [60006-008](#) [60011-075](#) [HPCI-14S12U](#) [cBP-3208](#) [cBP-3062A](#) [FAB205-6P5](#) [ATX6022/6](#) [60016-012](#) [96RMKVM-17V1C-A](#) [PCE-DP10-00A1E](#) [MOS-1120Y-0201E](#) [96RMLCD-17V1-A](#) [96RMKVM-17V8C-A](#) [60004-005](#) [60016-017](#) [60006-009](#) [60016-035](#) [60016-034](#) [60016-031](#) [60016-030](#) [60016-026](#) [60016-024](#) [60016-018](#) [60016-007](#) [60016-005](#) [60007-002](#) [60006-010](#) [AXX10GBTWLHW3](#) [382-BBEH](#) [555-BDCL](#) [K6CMISZBI52](#) [426451401-3](#) [60011-093](#) [MIC-3620/3-BE](#) [MPCIE-UART-KIT02-R20](#) [RSM232](#) [PCIE-1680-AE](#) [BB-FOSTCDRI](#) [73-544-002](#)