

Terminal Boards for Motion Control

For Mitsubishi Servos

DIN-814M0



Terminal Board for Mitsubishi MR-J2S-A Servo Amplifiers

- On-board Connector Type: 100-pin SCSI-II
- Dimensions:
123 x 107 x 44 mm (W x L x H)
(4.84" x 4.21" x 1.73")
- Mating Cable:
-ACL-102100-1: 100-pin SCSI-II cable, 1 M

DIN-68M-J2A0



Terminal Board for Mitsubishi MR-J2S-A Servo Amplifiers

- On-board Connector Type: 68-pin SCSI-II
- Dimensions:
103 x 83 x 43 mm (W x L x H)
(4.06" x 3.27" x 1.69")
- Mating Cable:
-ACL-10568-1: 68-pin SCSI-VHDCI cable, 1 M
-ACL-10569-1: 68-pin SCSI-II cable, 1 M

DIN-814M-J3A0



Terminal Board for Mitsubishi MR-J3A/J4A Servo Amplifiers

- On-board Connector Type: 100-pin SCSI-II
- Dimensions:
123 x 107 x 44 mm (W x L x H)
(4.84" x 4.21" x 1.73")
- Mating Cable:
-ACL-102100-1: 100-pin SCSI-II cable, 1 M

DIN-68M-J3A0



Terminal Board for Mitsubishi MR-J3A/J4A Servo Amplifiers

- On-board Connector Type: 68-pin SCSI-II
- Dimensions:
103 x 83 x 43 mm (W x L x H)
(4.06" x 3.27" x 1.69")
- Mating Cables:
-ACL-10568-1: 68-pin SCSI-VHDCI cable, 1 M
-ACL-10569-1: 68-pin SCSI-II cable, 1 M

For Mitsubishi Servos


DIN-839-J3B0



Terminal Board for Mitsubishi MR-J3B/J4B Servo Amplifiers

- Dimensions:
103 x 83 x 43 mm (W x L x H)
(4.06" x 3.27" x 1.69")
- Mating Cable:
-MR-J2HBUS M: controller to amplifier bus cable

DIN-825-J3A0



Terminal Board for Mitsubishi MR-J3A/J4A Servo Amplifiers

- On-board Connector Type: 68-pin SCSI-II
- Dimensions:
103 x 83 x 43 mm (W x L x H)
(4.06" x 3.27" x 1.69")
- Mating Cable:
-ACL-10568-1: 68-pin SCSI-VHDCI cable, 1 M
-ACL-10569-1: 68-pin SCSI-II cable, 1 M

DIN-814Y0



Terminal Board for Yaskawa Sigma V Servo Amplifiers

- On-board Connector Type: 100-pin SCSI-II
- Dimensions:
123 x 107 x 44 mm (W x L x H)
(4.84" x 4.21" x 1.73")
- Mating Cable:
-ACL-102100-1: 100-pin SCSI-II cable, 1 M

DIN-68Y-SGII0




Terminal Board for Yaskawa Sigma V Servo Amplifiers

- On-board Connector Type: 68-pin SCSI-II
- Dimensions:
103 x 83 x 43 mm (W x L x H)
(4.06" x 3.27" x 1.69")
- Mating Cables:
-ACL-10568-1: 68-pin SCSI-VHDCI cable, 1 M
-ACL-10569-1: 68-pin SCSI-II cable, 1 M

For Panasonic Servos


DIN-814P-A40



Terminal Board with 100-pin SCSI-II Connector for Panasonic MINAS A4/A5 Servo Amplifiers

- On-board Connector Type: 100-pin SCSI-II
- Dimensions:
123 x 107 x 44 mm (W x L x H) (4.84" x 4.21" x 1.73")
- Mating Cable:
-ACL-102100-1: 100-pin SCSI-II cable, 1 M

DIN-68P-A40



Terminal Board with 68-pin SCSI-II Connector for Panasonic MINAS A4/A5 Servo Amplifiers

- On-board Connector Type: 68-pin SCSI-II
- Supports 500 k & 2 Mpps pulse frequency input options
- Mating Cables:
-ACL-10568-1: 68-pin SCSI-VHDCI cable, 1 M
-ACL-10569-1: 68-pin SCSI-II cable, 1 M

Terminal Boards for Motion Control

For General Purpose

DIN-37D-01



Terminal Board with One 37-pin D-sub Connector and DIN-rail Mounting

- On-board Connector Type: 37-pin D-sub female
- Dimensions: 113 x 85 x 52 mm (W x L x H) (4.45" x 3.35" x 2.05")
- Mating Cable:
 - ACL-10137-1MM: 37-pin D-sub male/male cable, 1 M

DIN-100S-01



Terminal Board with One 100-pin SCSI-II Connector and DIN-rail Mounting

- On-board Connector Type: 100-pin SCSI-II female
- Dimensions: 158 x 120 x 52 mm (W x L x H) (6.22" x 4.72" x 2.05")
- Mating Cable:
 - ACL-102100-1: 100-pin SCSI-II cable, 1 M


DIN-68S-01



Terminal Board with One 68-pin SCSI-II Connector and DIN-rail Mounting

- On-board Connector Type: 68-pin SCSI-II female
- Dimensions: 103 x 85 x 46.2 mm (W x L x H) (4.06" x 3.35" x 1.82")
- Mating Cables:
 - ACL-10568-1: 68-pin SCSI-VHDCI cable, 1 M
 - ACL-10569-1: 68-pin SCSI-II cable, 1 M

DIN-825-4M0



Terminal Board with 100-pin SCSI-II Connector for General Purpose Servo & Stepper (for PCI-8254/8258)

- Supports Voltage Command and Pulse Command
- Supports Specific Servos & Steppers by Cable Selecting
- Dimensions: 200 x 107 x 44 mm (W x L x H) (7.87" x 4.21" x 1.73")
- Mating Cable:
 - ACL-102100-1: 100-pin SCSI-II cable, 1M


DIN-50S-01



Terminal Board with One 50-pin SCSI-II Connector and DIN-rail Mounting

- On-board Connector Type: 50-pin SCSI-II female
- Plastic cover for protection of wiring
- Dimensions: 125 x 85 x 50 mm (W x L x H) (4.92" x 3.35" x 1.97")
- Mating Cable:
 - ACL-10250-1: 50-pin SCSI-II cable, 1 M

DIN-814-GP



Terminal Board with 100-pin SCSI-II Connector for General Purpose

- Supports Specific Servos & Steppers by Cable Selecting
- On-board Connector Type: 100-pin SCSI-II
- Dimensions: 146 x 85 x 44 mm (W x L x H) (5.75" x 3.35" x 1.73")
- Mating Cable:
 - ACL-102100-1: 100-pin SCSI-II cable, 1 M


DIN-825-GP4



Terminal Board with 100-pin SCSI-II Connector for General Purpose Servo & Stepper (for AMP-204C/208C & PCI-8254/8258)

- Supports Specific Servos & Steppers by Cable Selecting
- On-board Connector Type: 100-pin SCSI II
- Dimensions: 300 x 107 x 44 mm (W x L x H) (11.81" x 4.21" x 1.73")
- Mating Cable:
 - ACL-102100-1: 100-pin SCSI-VHDCI cable, 1 M
 - ACL-10137-1: 37-pin D-sub male/male cable, 1 M

DIN-825-4P0



Terminal Board with 100-pin SCSI-II Connector for General Purpose Servo & Stepper (for AMP-204C/208C)

- Supports Pulse Command and General Purpose DI/O
- Supports Specific Servos & Steppers by Cable Selecting
- Dimensions: 200 x 107 x 44 mm (W x L x H) (7.87" x 4.21" x 1.73")
- Mating Cable:
 - ACL-102100-1: 100-pin SCSI-II cable, 1M
 - ACL-10137-1: 37-pin D-sub male/male cable, 1M

Cable Accessories

HSL-4XMO-DM Cable

- For Mitsubishi MR-J2S-A servo amplifiers
- Available for 1 M, 2 M, 3 M



4XMO-DA Cable M

- For Delta A2 servo series
- Available for 3 M



HSL-4XMO-DP Cable

- For Panasonic MINAS A4/A5 servo amplifier with brake control
- Available for 1 M, 1.5 M, 2 M



4XMO-DM-J3

- For Mitsubishi MR-J3 servo amplifiers
- Available for 2 M



HSL-4XMO-DY Cable

- For Yaskawa Sigma V servo amplifier
- Available for 1 M, 2 M, 3 M



4XMO-OPEN Cable M

- For Stepper or general purpose
- Available for 1 M, 2 M



MR-JCCBL M

- Encoder cable (for KFS series)
- Available for 2 M, 5 M

**MR-JHSCBL M**

- Encoder cable (for SFS series)
- Available for 2 M, 5 M

**MR-J2HBUS M**

- Controller to amplifier bus cable
- Compliant with PCI-8392(H)
- Available for 2 M, 5 M

**ACL-50P M**

- Controller to amplifier bus cable, 50-pin to 50-pin
- Available for 1 M, 2 M, 3 M
- Suitable for Panasonic A4/A5 servo and Yaskawa Sigma V servo

**MR-J2HBUS M(CAN)**

- Controller to amplifier bus cable
- Compliant with PCI-8392(H)
- Available for 2 M, 5 M

**ACL-50P M-OPEN**

- Controller to amplifier bus cable, 50-pin to open wire
- Available for 2 M, 3 M
- Suitable for Panasonic A4/A5 servo and Yaskawa Sigma V servo

**MA-J3BUS M**

- SSCNET III fiber cable
- Available for 0.15 M, 0.3 M, 0.5 M, 1 M, 3 M, 5 M

**SCSI-VHDCI 100P Cable**

- SCSI-VHDCI 100-pin cable
- Compliant with PCI-8158
- Available for 2 M, 3 M

**ACL-10568-I**

- 68-pin SCSI-VHDCI cable
(mating with AMP-787082-7), 1 M

**ACL-102100-I**

- 100-pin SCSI-II cable
(mating with AMP-787082-9), 1 M

**ACL-10250-I**

- 50-pin SCSI-II cable
(mating with AMP-787082-5), 1 M

**ACL-10569-I**

- 68-pin SCSI-II cable
(mating with AMP-787082-7), 1 M

**ACL-RRS- M**

- CAT5e, SFTP,
- Two sides RJ45 type,
- Available for 1M, 3M and 5M

**ACL-HHS- M**

- CAT5e, SFTP,
- Two sides Hirose 3p type
- Available for 1M, 3M and 5M

**ACL-RHS- M**

- CAT5e, SFTP,
- One side RJ45 type, another Hirose 3p type
- Available for 1M, 3M and 5M

**ACL-10137-IMM**

- 37-pin D-sub male/male cable, 1 M



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminal Block Interface Modules](#) category:

Click to view products by [ADLINK Technology](#) manufacturer:

Other Similar products are found below :

[73-551-6002I](#) [GCN1MX25B](#) [DIN-50P-01](#) [DIN-68H-01](#) [DIN-96DI-01](#) [2291901](#) [2295185](#) [2907794](#) [2M10FCL](#) [FLKM-2I/O](#) [FLKM-4I/O](#)
[2281759](#) [2906251](#) [2907808](#) [5601749](#) [5541962](#) [1776613-1](#) [GCN1-004A](#) [ADAM-3920R-AE](#) [060-6827-06](#) [2311030](#) [2287708](#) [XW2C-20G6-](#)
[IO16](#) [GCN1-T](#) [MACX](#) [MCR-VAC](#) [5775235](#) [ADAM-3956-BE](#) [XW6T-COM2.5X20YL](#) [XW6T-COM1.5X8BL](#) [XW6T-COM1.5X16BL](#)
[XW6T-COM1.5X20YL](#) [XW6T-COM1.5X16YL](#) [XW6T-COM1.5X20RD](#) [XW6T-COM1.5X20BL](#) [XW6T-COM2.5X8BL](#) [1976610000](#) [UM](#)
[45-D50SUB/B/ZFKDS](#) [5541234](#) [410-261](#) [2906243](#) [2907706](#) [ADAM-3909-AE](#) [ADAM-3920-AE](#) [ADAM-3925-AE](#) [ADAM-3937-BE](#)
[ADAM-3950-AE](#) [ADAM-3951-BE](#) [ADAM-3968-AE](#) [ADAM-3968/50-AE](#) [2905026](#)