

# IMX-3000

## Industrial Mobile Handheld Computer



### Features

- Android 4.0 operating system
- 3.8" WVGA (480 x 800) TFT-LCD; sunlight readable; five point capacitive touch screen
- Wireless radio
  - WLAN: IEEE 802.11 b/g/n
  - WPAN: V4.0
  - WWAN: WCDMA 850/1900/2100; GSM 850 /900/1800/1900; HSDPA: 7.2Mb/s; HSUPA: 5.76 Mb/s
- GPS - enabled & AGPS supported
- Data capture: CCD/1D laser engine/ 2D imager/NFC PN544 (13.56 MHz)
- 5M pixel camera with AF flash LED (standard)/ 2M pixel CMOS without AF (optional)
- Rechargeable 2600mAh Li-ion battery/3.7V, Rechargeable 3900mAh Li-ion battery/3.7V (optional)
- 1.5m drop (with protective cover) and IP 54 rating

### Specifications

#### Physical Characteristics

Dimensions (L x W x H)	140.9 x 72.9 x 27.3(mm) / 5.5 x 2.9 x 1.1(inch)
Weight	177g ± 5g (excluding battery)
Expansion slot	microSD x 1, support microSDHC
SIM slot	SIM slot x1
SAM slot	SAM slot x1 (for NFC)
Notification	Vibrator, triple LED (R, G, B)
Keypad/Button	5 keys, 2 side keys
Audio speaker	90dB 1KHz @ 10cm
Headset/Receiver/ Microphone	3.5 mm headset x 1 / Receiver x 1/ Microphone x 1
Light sensor	With Light sensor
G sensor	With G sensor
E-Compass	With E-Compass
Proximity sensor	With proximity sensor

#### Performance Characteristics

CPU	1.2GHz dual CPU
Memory	768MB DDR SDRAM / 4GB eMMC Flash
Interface	USB 2.0 OTG

#### Data Capture

CCD	CCD imager
1D	1D laser engine
2D	2D imager
NFC	NFC PN544 (13.56MHz)

#### Wireless

WLAN	IEEE 802.11 b/g/n
WPAN	Bluetooth V4.0
WWAN	WCDMA 850/1900/2100; GSM 850/900/1800/1900; HSDPA: 7.2Mb/s; HSUPA: 5.76 Mb/s

#### Working Environment

Operating Temperature	CCD: -10°C ~ 40°C (14°F ~ 104°F) 1D/2D: -10°C ~ 50°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C / -4°F ~ 140°F
Charging Temperature	0°C ~ 40°C / 32°F ~ 104°F
Humidity	10% to 90% @ 25°C, non-condensing
Drop Spec	1.5m drop (with protective cover)
Sealing Spec	IP54
Electrostatic	+/- 12KV (air discharge), +/- 8KV (direct discharge)

## Product Illustration



## Ordering Information

### Modules

Model Number	Description/Configuration
IMX-3020	Rugged Handheld unit, CCD, Qualcomm, Android 4.0, NFC, 2M camera, BT/WiFi, GPS, 3.5G high speed, 2600mAh - EU
IMX-3150	Rugged Handheld unit, Laser, Qualcomm, Android 4.0, NFC, 5M camera, BT/WiFi, GPS, 3.5G high speed, 2600mAh - EU
IMX-3250	Rugged Handheld unit, 2D, Qualcomm, Android 4.0, NFC, 5M camera, BT/WiFi, GPS, 3.5G high speed, 2600mAh - EU

### Accessories

Model Number	Description/Configuration
IMX-1100	Charging cradle with extra battery slot

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Embedded Box Computers](#) category:*

*Click to view products by [ADLINK Technology](#) manufacturer:*

Other Similar products are found below :

[tBOX312-870-FL-i7-DC](#) [tBOX313-835-FL-RJ-DC](#) [UPOS-3150-R0W0E](#) [ARK-20-S8A1E](#) [R2224WTTYSR](#) [BXNUC9i5QNX](#)  
[BXNUC9i5QNX1](#) [BKNUC9V7QNX](#) [BKNUC9V7QNX1](#) [2-A0DF-2001](#) [BKCMB1ABB](#) [BKCMB1ABA](#) [EM3000-3845-8-128-WL-U-1](#)  
[TANK-870AI-i5/8G/2A-R10](#) [PRFE21000038](#) [EM5000-I3-8-128-WL-W7-1](#) [EM3000-3845-8-128-WL-W7-1](#) [PRFE21000039](#) [AMOS-825-](#)  
[1Q10A1](#) [UPS-EDAI-X70864-U01-DC01](#) [UPX-EDGEI7-A10-1664-F01](#) [MXE-211/M8G](#) [PXIe-3985/M16G](#) [PXIe-3987/M16G/SSD](#)  
[ROScube-I, IntelR Core? i7, RQI-57](#) [AIMB-T1215DA-00Y0E](#) [AIMB-T1217DW-00Y0E](#) [AIMB-T12315A-00Y0E](#) [AMAX-5580-54000A](#)  
[APAX-5580-474AE](#) [ARK-6322-Q0A2E](#) [DS-100GF-S8A1E](#) [DS-100GL-S8A1E](#) [EPC-R4680CQ-XAA1E](#) [ESRP-CSS-UNO2484](#) [ITA-1611-](#)  
[10A1E](#) [ITA-1711-10A1E](#) [MIC-720AI-00A1](#) [UNO-247-J1N1AE](#) [UTX-3115FS-S6A2E](#) [AMI220AF-4L-7500](#) [ELIT-1200](#) [AIE100-903-FL](#)  
[EBOX671-517-FL-DC](#) [MVS900-511-FL](#) [AMS200](#) [SE-92-I7](#) [SI-606](#) [SI-60E](#) [ITG-100-AL-E1/2GB/S-R10](#)