

# MVP-6100 Series

Value Family 9th Generation Intel® Xeon®/Core™ i7/i5/i3 & 8th Gen Celeron® Processor-Based Expandable Computer

## Features

- 9th Gen Intel® Xeon®/Core™ i7/i5/i3 & 8th Gen Celeron® LGA processor
- Dual SODIMMs for up to 32GB DDR4 non-ECC/ ECC memory
- Rich I/O: 2x DP++/ DVI/ VGA/ 3x GbE/ 4x COM/ 8-ch DI/ 8-ch DO/TPM2.0
- 2x USB 3.1 Gen2 + 1x USB 3.1 Gen1 + 3x USB 2.0
- Rich storage: up to 4x 2.5" SATA, CFast, M.2 2280
- Embedded Expansion: Mini PCIe/ M.2 3042/ 2x USIM
- Front accessible I/O and adaptive Function Module v.2 option
- Flexible modular expansion with 2 or 4 slots



## Software Support

- Win10 IoT Enterprise CBB 64bit
- Linux Ubuntu 18.04

## Optional Accessories

- **MVP-6100 Fan Kit (P/N: 91-95267-0010)**
- **Factory Installed 2.5" SATA SSD/HDD/M.2/CFast**
- **Wireless Module**  
Wi-Fi/ BT/ 3G/ 4G LTE/ LoRa wireless kit (w/ antenna)
- **Optional 2x 2.5" SATA Kit (w/ Bracket and Cable)**
- **AC/DC Adapter**  
220W (P/N: 31-62149-0000)  
280W (P/N: 31-62162-1010-A0)
- **Internal power cable for add-on card**  
30-21656-0000-A0: for MVP-6120  
30-21655-0000-A0: for MVP-6140

## Ordering Information

Model	CPU	PCH	Slot #
MVP-612X-1E/M4G	Intel® Xeon® E-2278GE	C246	2
MVP-612A-1E/M4G	Intel® Core™ i7-9700E	H310	2
MVP-6121-1E/M4G	Intel® Core™ i7-9700TE	H310	2
MVP-6122-1E/M4G	Intel® Core™ i5-9500TE	H310	2
MVP-6123-1E/M4G	Intel® Core™ i3-9100TE	H310	2
MVP-6124-1E/M4G	Intel® Celeron® G4900T	H310	2
MVP-614X-3E/M4G	Intel® Xeon® E-2278GE	C246	4
MVP-614A-3E/M4G	Intel® Core™ i7-9700E	C246	4
MVP-6141-3E/M4G	Intel® Core™ i7-9700TE	C246	4
MVP-6142-3E/M4G	Intel® Core™ i5-9500TE	C246	4
MVP-6143-3E/M4G	Intel® Core™ i3-9100TE	C246	4
MVP-6144-3E/M4G	Intel® Celeron® G4900T	C246	4

## Specifications

Model Name	MVP-610X	MVP-610A	MVP-6101	MVP-6102	MVP-6103	MVP-6104
<b>System Core</b>						
Processor	Intel® Xeon® E-2278GE	Intel® Core™ i7-9700E	Intel® Core™ i7-9700TE	Intel® Core™ i5-9500TE	Intel® Core™ i3-9100TE	Intel® Celeron® G4900T
TDP	80W	65W	35W	35W	35W	35W
# of Cores	8	8	8	6	4	2
Base Freq.	3.3 GHz	2.6 GHz	1.8 GHz	2.2 GHz	2.2 GHz	2.9 GHz
Max Turbo Freq.	4.7 GHz	4.4 GHz	3.8 GHz	3.6 GHz	3.2 GHz	-
Chipset	C246	MVP-6120 series: H310 MVP-6140 series: C246				
Memory	4GB DDR4 non-ECC 2400 MHz, dual SODIMMs, up to 32GB (Optional: 4/8/16/32GB ECC, only for Intel® Xeon®/Core™ i3/Celeron w/ C246)					
<b>I/O Interface</b>						
Display	2x DP++ 1.2, DVI-D, VGA (dual independent displays w/ H310, 3 independent displays w/ C246)					
Ethernet	3x Intel GbE: 2x i211AT + i219 (Support Intel® AMT/vPro™ w/ C246)					
Serial Ports	COM1/2: RS-232/422/485, COM3/4: RS-232 (Optional COM5/6: RS-232, shared w/ DI/O)					
USB	3x USB 3.1 Gen 1 + 3x USB 2.0, 1x internal USB 2.0 dongle (2x USB 3.1 up to Gen 2 w/ C246)					
Audio	Line-out, Mic-in (Optional: speaker-out)					
Mini PCIe	1x Full size (USB 2.0 + PCIe)					
M.2	1x socket 2, key B+M or B, 2280/3042 (USB3.1 + SATA III + PCIe x1. Up to PCIe x2 w/ C246)					
USIM	2					
DI/O	8-CH DI and 8-CH DO					
I <sup>2</sup> C	2 (3.3V/5V)					
TPM	TPM2.0					
Expansion Slots	MVP-6120 series: PCIe x16 + PCI (total up to 150W) MVP-6140 series: PCIe x16 + 2 PCIe x4 + PCI (total up to 150W with 12V in; total up to 250W with 24V in)					
<b>Storage Device</b>						
2.5" SATA	2x internal (RAID 0/1/5/10 support w/ C246) (Optional: additional 2x internal, w/ C246)					
CFast	1 Type II					
<b>Mechanical</b>						
Dimensions	MVP-6120 series: 165 (W) x 240 (D) x 210 (H) mm (6.5" x 9.45" x 8.27") MVP-6140 series: 206 (W) x 240 (D) x 210 (H) mm (8.11" x 9.45" x 8.27")					
Weight	MVP-6120 series: 4.8 kg (10.6 lbs) MVP-6140 series: 5.1 kg (11.2 lbs)					
Mounting	Wall mount					
Fan	Optional					
<b>Power Supply</b>						
DC Input	12-24V (± 10% tolerance)					
AC Input	Optional: 220W/280W AC/DC adapter					
<b>Environmental</b>						
Operating Temperature	Standard: (w/ air flow 0.6 m/s)					
	0°C to 40°C	0°C to 50°C				
	Extended: (w/ air flow 0.6 m/s & ind. storage)					
Storage Temperature	-20°C to 40°C	-20°C to 50°C	-20°C to 60°C			
	-40°C to 85°C (-40°F to 185°F) (excl. storage)					
Humidity	~95% @ 40°C (non-condensing)					
Vibration	Operating: 5 Grms, random, 5-500 Hz, 3 axes (w/2.5" SSD/CFast, 3 Grms w/ fan)					
	Operating: 0.5 Grms, random, 5-500 Hz, 3 axes (w/ HDD)					
Shock	Operating: 50 G, half sine 11ms duration (w/ 2.5" SSD/CFast)					
ESD	Contact +/-4KV, Air +/-8KV					
EMC	EN61000-6-4/-2, CE & FCC Class A					
Safety	UL/cUL, CB, CCC					

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Embedded Box Computers](#) category:*

*Click to view products by [ADLINK Technology](#) manufacturer:*

Other Similar products are found below :

[BXNUC9i5QNX](#) [BXNUC9i5QNX1](#) [BXNUC10I3FNHN1](#) [BXNUC10I5FNKN1](#) [RNUC11BTMI90001](#) [BXNUC10I3FNHN](#) [EPC-R4710NO-XAA1E](#) [HMIG3U](#) [UBC-DS31CD-PAA1E](#) [UBC-200CQ-MEA1E](#) [UBC-200CD-MDA1E](#) [UTX-3115SA4P-S6A2E](#) [TREK-303R-HA0E](#) [ITA-1710-01A1E](#) [AVS-540-00A1E](#) [AIIS-1240-00A1E](#) [TANK-870AI-i5/8G/2A-R10](#) [PRFE21000038](#) [UPN-EDGE-EHLCN2-A10-0232](#) [UPS-EDAI-X70864-U01-DC01](#) [UPX-EDGEI7-A10-1664-F01](#) [UPX-EDGE-TGLI5-A10-0000-0001](#) [UPX-EDGE-TGLI3-A10-0000-0001](#) [EOS-JNX-G](#) [ROScube-I, IntelR Core? i7, RQI-57](#) [RQX-590](#) [AIR-030-S30A1](#) [DS-100GL-S8A1E](#) [EPC-R4680CQ-XAA1E](#) [ITA-1611-10A1E](#) [UNO-247-J1N1AE](#) [USM-110C-BD113](#) [AIE100-903-FL](#) [eBOX626-311-FL](#) [EBOX671-517-FL-DC](#) [ASM30002](#) [AMI230AFM](#) [DRPC-240-TGL-U-i5CS-R10](#) [PAC-1000GBPX-R30/300W](#) [BKCM8v5CB8N](#) [BKCM8v7CB8N](#) [BKCM8i3CB4N](#) [BKNUC9V7QNX](#) [BKNUC9VXQNB](#) [BKNUC9VXQNX](#) [BKNUC9VXQNX1](#) [BNUC11TNBV50000](#) [BNUC11TNBI70000](#) [BNUC11TNHV70001](#) [BNUC11TNKV50000](#)