

Converter Modules

ND-6510

RS-422/RS-485 Repeater



- **Input**
 - RS-422 (4-wire, full-duplex)
 - RS-485 (2-wire, half-duplex) protocol
- **Output**
 - RS-422 (4-wire, full-duplex)
 - RS-485 (2-wire, half-duplex) protocol
- **Speeds:** 115.2 k, 57.6 k, 38.4 k, 19.2 k, 9600, 4800, 2400, 1200
- Auto baud rate and data format adjustment
- Isolation Voltage: 2500 VRMS
- Surge protector on communications signals
- Connector: Plug-in screw terminal block
- Replacer Request: Over 128 modules or distance over 4000 feet
- Power Consumption: 1.104 W typical

ND-6520

RS-232 to RS-422/RS-485 Converter



- **Protocol**
 - RS-422 (4-wire, full-duplex)
 - RS-485 (2-wire, half-duplex) protocol
- **Speeds:** 115.2 k, 38.4 k, 19.2 k, 9600, 4800, 2400, 1200
- Auto baud rate and data format adjustment
- Isolation Side: RS-232 signal (TXD, RXD, GND)
- Isolation Voltage: 2500 VRMS
- Surge protector on RS-422/RS-485 communications signals
- Connector: Female DB-9 and plug-in screw terminal block
- Power Consumption: 0.912 W typical

ND-6530

USB to RS-422/RS-485 Converter



- **Protocol** (DIP switch selectable)
 - RS-232 (5-wire: RXD, TXD, RTS, CTS, GND)
 - RS-422 (4-wire: TX+, TX-, RX+, RX-)
 - RS-485 (2-wire: Data+, Data-)
- **Speeds:** 1200 to 115.2 kbps
- Isolation Voltage: 2500 VRMS
- USB 1.1 compliant
- Power Consumption: 0.795 W typical

ND-6531

Configurable Communications Controller



- **Protocol**
 - RS-232 (5-wire: RXD, TXD, RTS, CTS, GND)
 - RS-422 (4-wire: TX+, TX-, RX+, RX-)
 - RS-485 (2-wire: Data+, Data-)
- **Speed:** 1200 to 115200 bps (RS-232 and RS-422/RS-485 can be set to different baud rate)
- Convert RS-422/RS-485 to RS-232 with configurable address
- Isolation Voltage: 1000 Vdc
- Surge protector on communications signals
- Connector: Female DB-9 and plug-in screw terminal block
- Power Consumption: 1.008 W typical

NDP-243, NDP-243U2

Panel Mounting Power Supply



NDP-243U2



NDP-243

- **Input Voltage**
 - NDP243: 85 to 132 VAC or 170-264 VAC, switchable
 - NDP-243U: 90-264 VAC
- **Input Frequency:** 47 to 63 Hz
- **Input Current:** 1.4 A (max.)
- **Short Protection**
- **Output Voltage**
 - NDP-243: +24 Vdc \pm 10 %
 - NDP-243U: +24 Vdc 1 A, +12 Vdc 1 A, +5 Vdc 3 A
- **Output Current: 3 A (max.)**
 - Overload protection
 - Dimensions: 5" (L) \times 3.8" (W) \times 1.6" (H)
- **Operating Temperature:** 0°C to +50°C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) category:

Click to view products by [ADLINK Technology](#) manufacturer:

Other Similar products are found below :

[8500-003](#) [IFD8520](#) [cPCI-3544](#) [422CON](#) [ATX6022/14GP7](#) [ATX6022/8](#) [AX93221-24/48](#) [FC6A-EXM2](#) [OPT8AP-AE](#) [96RMKVM-19V1C-A](#)
[60016-011](#) [60016-014](#) [60006-008](#) [60011-075](#) [HPCI-14S12U](#) [cBP-3208](#) [cBP-3062A](#) [FAB205-6P5](#) [ATX6022/6](#) [60016-012](#) [96RMKVM-](#)
[17V1C-A](#) [PCE-DP10-00A1E](#) [MOS-1120Y-0201E](#) [96RMLCD-17V1-A](#) [96RMKVM-17V8C-A](#) [60004-005](#) [60016-017](#) [60006-009](#) [60016-035](#)
[60016-034](#) [60016-031](#) [60016-030](#) [60016-026](#) [60016-024](#) [60016-018](#) [60016-007](#) [60016-005](#) [60007-002](#) [60006-010](#) [AXX10GBTWLHW3](#)
[382-BBEH](#) [555-BDCL](#) [K6CMISZBI52](#) [426451401-3](#) [60011-093](#) [MIC-3620/3-BE](#) [MPCIE-UART-KIT02-R20](#) [RSM232](#) [PCIE-1680-AE](#) [BB-](#)
[FOSTCDRI](#)