

PCI-7396

96-CH High-Driving DIO Card



Features

- Supports a 32-Bit 5 V PCI bus
 - 96-CH digital TTL inputs/outputs (PCI-7396)
 - High driving up to 48 mA (sink) and 15 mA (source)
 - Emulates 4/2 industry standard 8255 PPI (mode 0)
 - Ports are independently configurable as input or output
 - External latch signal available for digital inputs
 - Output status read back
 - Known power-up states
 - Onboard 8254 timer/counter chip
 - I-CH 16-Bit event counter for external signal
 - I-CH 32-Bit timer for timed interrupt generation
 - Change-of-state (COS) interrupt
 - Multiple programmable interrupt sources
 - Compact, half-size PCB
- **Supported Operating System**
 - Windows 7/8 x64/x86, Linux
 - **Driver and SDK**
 - LabVIEW, MATLAB, C/C++, Visual Basic, Visual Studio.NET
 - **Software Utility**
 - AD-Logger

Specifications

Digital I/O

- Number of channels
 - 96 input/output
- Compatibility: 5 V/TTL
- Power-on state: input
- Digital logic levels
 - Input high voltage: 2-5.25 V
 - Input low voltage: 0-0.8 V
 - Output high voltage: 2.4 V minimum
 - Output low voltage: 0.5 V maximum
- Output driving capacity
 - Source current: 15 mA
 - Sink current: 48 mA
- Data transfers: programmed I/O

Interrupt

- Interrupt #0 sources
 - PIC0
 - PIC3
 - 16-Bit event counter
 - Change-of-state detection on any bit of PPI 1 & PPI 2
- Interrupt #1 sources
 - P2C0
 - P2C3
 - 32-Bit timer (based on 2 MHz internal clock),
 - Change-of-state detection on any bit of PPI 3 & PPI 4

General Specifications

- I/O connector : One 100-pin SCSI-II female
- Operating temperature: 0°C to 60°C (32°F to 140°F)
- Storage temperature: -20°C to 80°C (-4°F to 176°F)
- Relative humidity: 5% to 95%, non-condensing
- Power requirements

Device	+5 V
PCI-7396	450 mA typical

- Dimensions (not including connectors)
158 mm x 107 mm (6.16" x 4.17")

Terminal Boards & Cables

- **DIN-100S-01**
Terminal Board with One 100-pin SCSI-II Connector and DIN-Rail Mounting (Cables are not included.)
 - **DIN-96DI-01**
96-CH Isolated DI Terminal Board with DIN-Rail Mounting (Cables are not included.)
 - **ACL-102100-1**
100-pin SCSI-II cable (mating with AMP-787082-9), 1 M
- * For more information on mating cables, please refer to P3-48/49.

Ordering Information

- **PCI-7396**
96-CH High-Driving DIO Card

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Data Logging & Acquisition](#) category:

Click to view products by [ADLINK Technology](#) manufacturer:

Other Similar products are found below :

[PCI-6208A](#) [DAQe-2502](#) [PXI-2208](#) [ACL-8112DG](#) [SpotBotBLE](#) [LPCI-7230](#) [USB-4761-BE](#) [SE028](#) [PCI-1761-BE](#) [AR207/8/S1/PPPP/IP65](#)
[PCI-1711UL-CE](#) [USB-4702-AE](#) [USB-4704-AE](#) [USB-4716-AE](#) [USB-4750-BE](#) [USB-4751-AE](#) [PCIE-1810-AE](#) [PCI-1710U-DE](#) [PCI-](#)
[1710HGU-DE](#) [AR207/8/S1/PPPP/IP30](#) [U2781A](#) [4610](#) [EL-USB-5](#) [AR407/S1/P/P/P/P](#) [AR207/8/S2/PPPP/IP30](#) [ACL-8112PG](#) [cPCI-7248](#)
[cPCI-7433](#) [DAQ-2213](#) [ND-6053](#) [ND-6060](#) [PCI-7230](#) [PCI-7432](#) [PCI-9111DG](#) [PCI-9112](#) [PCI-9112A](#) [PCI-9113A](#) [PCI-9221](#) [PCM-7248+](#)
[USB-1903](#) [USB-2401](#) [PCIE-1813-AE](#) [PCIE-1816-AE](#) [PCIE-1816H-AE](#) [PCIE-1884-AE](#) [USB-5856-AE](#) [USB-5862-AE](#)
[AR654/S2/P/P/P/P/IP30](#) [DAS30](#) [DAS60](#)