

PCI-9524

24-Bit Precision Load Cell Input Card



Introduction

The PCI-9524 is a robust, multi-purpose module designed for turnkey material test systems (MTS). Equipped with four strain gauge-based full-bridge transducer input channels, four general purpose analog input channels, and a 3-axis motion controller, the PCI-9524 delivers a complete hardware solution for MTS manufacturers. The PCI-9524 easily integrates physical quantity measurement and implements strategy of software-based close-loop control in a single module package. For transducer measurement, the PCI-9524 supports sensitivity from 1.0 mV/V to 4.0 mV/V and provides a 1/200000 accuracy of measurement of full scale. These features make the PCI-9524 suitable for precise measurement in large-scale transducers.

The PCI-9524 is also equipped with four, 24-bit general purpose analog input channels that allow accurate measurements of the LVDT (Linear Variable Differential Transducer) and Linear wire potentiometer signals to achieve high-resolution of displacement.

With motion control capability and 16-bit DA channels, the PCI-9524 comes with three stepper/servo motor axes and two channels of hydraulic system control function. The built-in incremental encoder feedback channels enable the PCI-9524 to implement the stratagem of MTS' software-based closed-loop control.

The impressive PCI-9524 features permit easy implementation of required control or measurement functionalities with just a single module, saving precious development and integration time for MTS manufacturers, CNC machines, and civil testing equipment.

Features

- Transducer Inputs for precise measurement
 - 4-CH full-bridge load cell transducer inputs
 - Accuracy up to 1/200,000 counts at full-scale
 - Sensitivity from 1.0 mV/V to 4.0 mV/V
 - 2.5/10 Vdc excitation voltage, software selectable
 - Internal 24-bit A/D resolution
- Motion control interface for stepper and hydraulic system control
 - 3-axis PWM output with OUT/DIR and CW/CCW mode
 - 2-CH 16-bit analog outputs
 - A-B phase encoder input with 24-bit counter
- General-Purpose Analog Inputs for accurate measurements of LVDT¹ and linear wire potentiometer signals
 - 4-CH analog input with 24-bit resolution
 - Programmable gains of ± 1.25 V, ± 2.5 V, ± 5 V, ± 10 V
 - Up to 30 kS/s sampling rate (single channel)

Note 1: LVDT: Linear Variable Differential Transducer

■ Supported Operating System

- Windows 7/8 x64/x86, Linux

■ Driver and SDK

- LabVIEW, MATLAB, C/C++ , Visual Basic, Visual Studio.NET

Specifications

4-channel Load Cell Transducer Input

- Excitation voltage: 2.5 V/10 Vdc
- Internal A/D resolution: 24-bit
- Update speed when Auto-zero Disabled
 - Up to 30 KSPS (single channel)
 - Up to 1,638 SPS (multi-channel)
- Update speed when Auto-zero Enabled
 - Up to 819 SPS (single channel or multi-channel)
- Transducer sensitivity: 1.0 mV/V to 4.0 mV/V
- Number of channels: 4
- Accuracy: 1/200000 of full scale (with remote sense & auto zero enabled)
- Onboard 256 samples A/D FIFO

PWM Output & Encoder Input

- Number of axis: 3
- Pulse output options: OUT/DIR and CW/CCW (26LS31, differential line driver, driving current: up to 20 mA)
- Maximum output frequency: 500 kHz
- Encoder Input: 24-bit up/down counter for incremental encoder feedback

General Purpose Analog Input

- Resolution: 24-bit
- Programmable range: ± 1.25 V, ± 2.5 V, ± 5 V, ± 10 V
- Number of channels: 4
- Sampling rate: 30 kS/s (non-multiplexing)
- Onboard 256 samples A/D FIFO

Isolated Digital Input

- Number of channels: 8
- Maximum input range (non-polarity): 0 V to 24 V
- Input resistance: 2.7 K Ω

Isolated Digital Output

- Number of channels: 8
- Output type: Power MOSFET
- Sink current: Up to 300 mA/channel

Analog Output

- Resolution: 16-bit
- Output range: ± 10 V
- Number of channels: 2
- Update rate: Up to 5 kS/s
- Onboard 1 K samples D/A FIFO
- Driving capability: 5 mA

Hardware Timer Interrupt

- Base clock: 10 MHz
- Resolution: 32-bit
- Interrupt Frequency: 10 MHz/N ; N = 1 ~ (2³²-1)

General Specifications

- 5V power output current:
 - ISO5VDD: max. 160 mA
 - ISOPWR: max. 16 mA
- I/O connector: Two 68-pin SCSI-VHDCI female
- Operation Temperature: 0 to 45° C
- Power requirements: 5 V @ 2 A
- Dimensions (not including connectors): 156 mm x 116 mm (6.14" x 4.57")

Ordering Information

- **PCI-9524**
24-Bit Precision Load Cell Input Card

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Data Logging & Acquisition](#) category:

Click to view products by [ADLINK Technology](#) manufacturer:

Other Similar products are found below :

[PCI-6208A](#) [DAQe-2502](#) [PXI-2208](#) [ACL-8112DG](#) [SpotBotBLE](#) [LPCI-7230](#) [USB-4761-BE](#) [SE028](#) [PCI-1761-BE](#) [AR207/8/S1/PPPP/IP65](#)
[PCI-1711UL-CE](#) [USB-4702-AE](#) [USB-4704-AE](#) [USB-4716-AE](#) [USB-4750-BE](#) [USB-4751-AE](#) [PCIE-1810-AE](#) [PCI-1710U-DE](#) [PCI-](#)
[1710HGU-DE](#) [AR207/8/S1/PPPP/IP30](#) [U2781A](#) [4610](#) [EL-USB-5](#) [AR407/S1/P/P/P/P](#) [AR207/8/S2/PPPP/IP30](#) [ACL-8112PG](#) [cPCI-7248](#)
[cPCI-7433](#) [DAQ-2213](#) [ND-6053](#) [ND-6060](#) [PCI-7230](#) [PCI-7432](#) [PCI-7442](#) [PCI-9112](#) [PCI-9112A](#) [PCI-9113A](#) [PCI-9221](#) [PCM-7248+](#) [USB-](#)
[1903](#) [USB-2401](#) [PCIE-1813-AE](#) [PCIE-1816-AE](#) [PCIE-1816H-AE](#) [PCIE-1884-AE](#) [USB-5856-AE](#) [USB-5860-AE](#) [USB-5862-AE](#)
[AR654/S1/P/P/P/P/IP30](#) [AR654/S2/P/P/P/P/IP30](#)