

PCIe-8560/PXI-8565

PCI Express Control of PXI/CompactPCI



Introduction

The PCI Express-to-PXI/CompactPCI expansion kit provides control of PXI/CompactPCI modules installed in a PXI/CompactPCI expansion system using high-bandwidth PCI Express technology. With comprehensive hardware and software transparency, the expansion kit enables fast and convenient detection of any installed PXI/CompactPCI cards in the expansion system, without requiring additional drivers or software installation.



Controlling PXI™/CompactPCI® with PCI Express®

The PCIe-8560 and PXI-8565 PCI Express-to-PXI/CompactPCI expansion kit provides additional PXI slots to the host computer by implementing a PCI Express-based control of PXI/CompactPCI modules. The technology consists of a PCIe-8560 card installed in the host computer, a shielded cable, and the expansion system with the 3U (Eurocard) PXI-8565 expansion module. The PCIe-8560 comes in a PCI Express x1 footprint and converts PCI Express signals to a PCI bridge that supports seven 32-bit/66 MHz PXI/CompactPCI modules.

Controlling 6U CompactPCI®/PXI™ Modules

For applications requiring control of 6U PXI or CompactPCI modules through PCI Express, ADLINK provides the PXI-8565/6U, the 6U version of PXI-8565. The PXI-8565/6U provides the exact same features as PXI-8565 but in a 6U CompactPCI/PXI form factor. The product package includes one PCIe-8560 to plug into a host PC, one PXI-8565/6U for the remote 6U CompactPCI/PXI chassis, and one ACL-EXPRESS-1/3/7 expansion cable.

Features

- PCI Express-based control of PXI/CompactPCI
- High-speed PCI Express x1 interface
- Direct control of PXI/CompactPCI systems
- Supports 32-bit/66 MHz PCI™ interface
- Expansion distance of up to 7 meters (expansion cables at 1 M, 3 M, and 7 M)
- Comprehensive hardware and software transparency
- Compliant with
 - PCI Express® Base Specifications Rev. 1.0a
 - PXI™ Specifications Rev. 2.2
 - PCI-to-PCI Bridge Architecture Specifications Rev. 1.2
 - PCI™ Local Bus Specifications Rev. 3.0

General Specifications

- Operating temperature: 0°C to 50°C (32°F to 122°F)
- Storage temperature: -20°C to 80°C (-4°F to 176°F)
- Relative humidity: 10% to 90%, non-condensing

Certification

- EMC/EMI: CE, FCC Class A

Ordering Information

- **PCI Express-to-PXI Expansion Kit**
Includes One PCIe-8560, One PXI-8565, and One ACL-EXPRESS-3 Cable
- **PCIe-8560**
PCI Express-to-PXI Expansion Interface Card for host PC
- **PXI-8565**
PCI Express-to-PXI Expansion Interface Card for 3U CompactPCI/PXI Chassis
- **PXI-8565/6U**
PCI Express-to-PXI Expansion Interface Card for 6U CompactPCI/PXI Chassis
- **ACL-EXPRESS-1**
High-speed Expansion Cable, 1 M
- **ACL-EXPRESS-3**
High-speed Expansion Cable, 3 M
- **ACL-EXPRESS-7**
High-speed Expansion Cable, 7 M



PCIe-8560



PXI-8565



PXI-8565/6U

Specifications

■ PCIe-8560	<ul style="list-style-type: none"> • PCI Express Base Specifications Rev. 1.0a compliant • PCI Express x1 link with 250 MB/s data throughput • Extended distance of up to 7 meters • Dimension: Low-profile PCI Express card 69 mm (H) x 87 mm (W) (2.69" x 3.39") • Power requirement: <table border="1"> <thead> <tr> <th>Device</th> <th>+3.3 V</th> </tr> </thead> <tbody> <tr> <td>PCIe-8560</td> <td>210 mA (max)</td> </tr> </tbody> </table> 	Device	+3.3 V	PCIe-8560	210 mA (max)
Device	+3.3 V				
PCIe-8560	210 mA (max)				
■ PXI-8565, PXI-8565/6U	<ul style="list-style-type: none"> • PXI™ Specifications Rev. 2.2 compliant • PCI-to-PCI Bridge Architecture Specifications Rev. 1.2 compliant • PCI™ Local Bus Specifications Rev. 3.0 compliant • Supports 32-bit/66 MHz PCI™ interface • Internal arbiter supports up to 7 external masters • Up to seven PCI clock/bus requests • Extended distance of up to 7 meters • Dimensions: PXI-8565: 175 mm (W) x 107 mm (H) (6.82" x 4.17") PXI-8565/6U: 175 mm (W) x 233.35 mm (H) (6.82" x 9.1") • Power requirement: <table border="1"> <thead> <tr> <th>Device</th> <th>+3.3 V</th> </tr> </thead> <tbody> <tr> <td>PXI-8565, PXI-8565/6U</td> <td>720 mA</td> </tr> </tbody> </table> 	Device	+3.3 V	PXI-8565, PXI-8565/6U	720 mA
Device	+3.3 V				
PXI-8565, PXI-8565/6U	720 mA				
■ ACL-EXPRESS-1/-3/-7	<ul style="list-style-type: none"> • Length: 1 M, 3 M, 7 M 				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Data Logging & Acquisition](#) category:

Click to view products by [ADLINK Technology](#) manufacturer:

Other Similar products are found below :

[PCI-6208A](#) [DAQe-2502](#) [PXI-2208](#) [ACL-8112DG](#) [SpotBotBLE](#) [LPCI-7230](#) [USB-4761-BE](#) [SE028](#) [PCI-1761-BE](#) [AR207/8/S1/PPPP/IP65](#)
[PCI-1711UL-CE](#) [USB-4702-AE](#) [USB-4704-AE](#) [USB-4716-AE](#) [USB-4750-BE](#) [USB-4751-AE](#) [PCIE-1810-AE](#) [PCI-1710U-DE](#) [PCI-](#)
[1710HGU-DE](#) [AR207/8/S1/PPPP/IP30](#) [U2781A](#) [4610](#) [EL-USB-5](#) [AR407/S1/P/P/P/P](#) [AR207/8/S2/PPPP/IP30](#) [ACL-8112PG](#) [cPCI-7248](#)
[cPCI-7433](#) [DAQ-2213](#) [ND-6053](#) [ND-6060](#) [PCI-7230](#) [PCI-7432](#) [PCI-7442](#) [PCI-9112](#) [PCI-9112A](#) [PCI-9113A](#) [PCI-9221](#) [PCM-7248+](#) [USB-](#)
[1903](#) [USB-2401](#) [PCIE-1813-AE](#) [PCIE-1816-AE](#) [PCIE-1816H-AE](#) [PCIE-1884-AE](#) [USB-5856-AE](#) [USB-5860-AE](#) [USB-5862-AE](#)
[AR654/S1/P/P/P/P/IP30](#) [AR654/S2/P/P/P/P/IP30](#)