
# maxiFLOW™ Cross Cut High Performance Heat Sinks with Plastic Push Pin



#### ATS PART # ATS-1040-C1-R0

#### **Features & Benefits**

- » For larger heat sinks and higher pre-loads, push pins with compression springs are an effective mounting choice. The push pin has a flexible barb at the end that is designed to engage with a pre-drilled hole in a PWB. The compression spring adds the necessary force to hold the assembly together. Provides better thermal performance than comparable size straight fin and pin fin heat sinks
- » Features proven high performance maxiFLOW™ heat sink spread fin array to maximize cooling surfaces
- » Ideal for tight spaced components where wider heat sinks can't be used
- » Provided with pre-assembled thermal interface material centered on base
- » Nylon push pin with steel compression spring
- » Reccomended through hole size in PCB is 3.00 mm



\*Image above is for illustration purposes only.

#### **Thermal Performance**

| AIR VELOCITY |     | THERMAL RESISTANCE (°C/W UNDUCTED) |                   |  |
|--------------|-----|------------------------------------|-------------------|--|
| FT/MIN       | M/S | AIR FLOW STRAIGHT                  | AIR FLOW SIDEWAYS |  |
| 200          | 1.0 | 1.9                                | 3.6               |  |
| 300          | 1.5 | 1.6                                | 2.8               |  |
| 400          | 2.0 | 1.3                                | 2.1               |  |
| 500          | 2.5 | 1.1                                | 1.6               |  |
| 600          | 3.0 | 1                                  | 1.3               |  |

### **Product Details**

| DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D | INTERFACE MATERIAL | FINISH         |
|-------------|-------------|-------------|-------------|--------------------|----------------|
| 40 mm       | 38 mm       | 25 mm       | 65 mm       | CHOMERICS T-766    | GREEN ANODIZED |

#### **NOTES:**

- DIMENSION C = HEAT SINK HEIGHT FROM BOTTOM OF THE BASE TO THE TOP OF THE FIN FIELD.
- THERMAL PERFORMANCE DATA ARE PROVIDED FOR REFERENCE ONLY. ACTUAL PERFORMANCE MAY VARY BY APPLICATION.
- ATS RESERVES THE RIGHT TO UPDATE OR CHANGE ITS PRODUCTS WITHOUT NOTICE
- 4) CONTACT ATS TO LEARN ABOUT CUSTOM OPTIONS AVAILABLE



For more information, to find a distributor or to place an order, visit www.qats.com or call: 781.769.2800 (North America); +31 (0) 3569 84715 (Europe).

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Sinks category:

Click to view products by Advanced Thermal Solutions manufacturer:

Other Similar products are found below:

581102B00000G 656-15ABPE 657-20ABPNE 7020B-TC12-MTG 73452PPBA 7G0011A PF720G A22-4026 120-1873-007 HAH10L HAH15L 1542616-1 HS-2506-F1 HS-87M0-F2 218-40CTE3 231-69PAB-15V 25-7520 SW50-4G 231-75PAB-13V 231-75PAB-15V 253-122ABE-22 PSC22CB HAF10L HAQ10T D10100-28 BDN183CBA01 3-21053-4 32438 TX0506-1B TX1806B LAE66A3CB WA-DT2-101E 511-3U 73381PPBA 73403PPBA 7G0047C COMX-440-HSP 510-12M D10650-40T5 V8511 Y APF40-40-13CB/A01 780653U04500G ATS-54310K-C2-R0 FK 216 CB SA FK 231 SA 220 648-51AB 657-20ABPESC 2341BG 679-25AG FK 212 CB SA