BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD





ATS Part#: ATS-50210B-C1-R0

Description: 21.00 x 21.00 x 7.50 mm BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD

Heat Sink Type: maxiFLOW

Heat Sink Attachment: maxiGRIP

Equivalent Part Number: ATS-50210B-C2-R0 Discontinued

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock and Unpackaged Drop Testing standards
- · Comes preassembled with high performance, phase changing, thermal interface material
- Designed for standard height components from 3 to 4.5mm

Thermal Performance

| AIR VELOCITY | | @200 LFM 1.0 M/S | @300 LFM 1.5 M/S | @400 LFM 2.0 M/S | @500 LFM 2.5 M/S | @600 LFM 3.0 M/S | @700 LFM 3.5 M/S | @800 LFM 4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 11.9 °C/W | 9.5 °C/W | 8.2 °C/W | 7.3 °C/W | 6.7 °C/W | 6.2 °C/W | 5.8 °C/W |
| | Ducted Flow | 8.8 | N/A | N/A | N/A | N/A | N/A | N/A |

Product Detail

| Schematic Image | Dimension A | Dimension B | Dimension C | Dimension D | TIM | Finish |
|--|--|-----------------------|--|---|---|--|
| A.a. | 21.00 mm | 21.00 mm | 7.50 mm | 34.6 mm | T766 | BLUE-ANODIZED |
| *Image above is for illustration purpose only. | Dimensior ATS-5021 (Saint Got Thermal p application ATS reser performan ATS certifit Optional n | ves the right to upda | eight from the bottor ct heat sink assembl :: Saint Gobain C110 : provided for referen te or change its proc c assembly is RoHS- ion/Removal Tool Se | ly with an equivalent 10F is discontinued e 10ce only. Actual perfo 10cd only. Actual perfo | thermal in thermal in the thermal in the thermal in the thermance in the thermal in the the the thermal in the thermal in the thermal in the thermal in the | nterface material 2/31/10. nay vary by |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Sinks category:

Click to view products by Advanced Thermal Solutions manufacturer:

Other Similar products are found below:

581102B00000G 656-15ABPE 657-20ABPNE 7020B-TC12-MTG 73452PPBA 7G0011A PF720G A22-4026 120-1873-007 HAH10L 1542616-1 HS-2506-F1 HS-87M0-F2 218-40CTE3 25-7520 SW50-4G 231-75PAB-13V 231-75PAB-15V 253-122ABE-22 PSC22CB HAF10L HAQ10T D10100-28 BDN183CBA01 3-21053-4 32438 TX0506-1B TX1806B LAE66A3CB WA-DT2-101E 511-3U 73381PPBA 73403PPBA 7G0047C COMX-440-HSP 510-12M D10650-40T5 V8511 Y APF40-40-13CB/A01 780653U04500G ATS-54310K-C2-R0 FK 216 CB SA FK 231 SA 220 648-51AB 657-20ABPESC 2341BG 679-25AG FK 212 CB SA FK225 SA L1 680-5K