BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-Low Profile



ATS Part#: Description:

ATS-51330R-C1-R0

33.00 x 33.00 x 19.50 mm BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-Low Profile

 Heat Sink Type:
 maxiFLOW

 Heat Sink Attachment:
 maxiGRIP

 Equivalent Part Number:
 ATS-51330R-C2-R0 Discontinued

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock and Unpackaged Drop Testing standards
- · Comes preassembled with high performance, phase changing, thermal interface material
- Designed for low profile components from 1.5 to 2.99mm

Thermal Performance

| AIR VELOCITY | | @200 LFM 1.0 M/S | @300 LFM 1.5 M/S | @400 LFM 2.0 M/S | @500 LFM 2.5 M/S | @600 LFM 3.0 M/S | @700 LFM 3.5 M/S | @800 LFM 4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 2.6 °C/W | 2.1 °C/W | 1.8 °C/W | 1.7 °C/W | 1.5 °C/W | 1.4 °C/W | 1.3 °C/W |
| | Ducted Flow | 2 | N/A | N/A | N/A | N/A | N/A | N/A |

Product Detail

| Schematic Image | Dimension A | Dimension B | Dimension C | Dimension D | ТІМ | Finish | | | |
|---|--|-------------|----------------------|-------------|------|-----------------|--|--|--|
| | 33.00 mm | 33.00 mm | 19.50 mm | 58.2 mm | T766 | BLACK- ANODIZED | | | |
| | Notes: Dimension A and B refer to component size. Dimension C is the heat sink height from the bottom of the base to the top of the fin field. ATS-51330R-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint Gobain C1100F). NOTE: Saint Gobain C1100F is discontinued effective 12/31/10. Thermal performance data are provided for reference only. Actual performance may vary by application. ATS reserves the right to update or change its products without notice to improve the design or performance. | | | | | | | | |
| ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant. Optional maxiGRIP™ Installation/Removal Tool Set P/N: MGT330 Contact ATS to learn about custom options available. | | | | | | | | | |
| *Image above is for illustration purpose only. | | | usion options availe | | | | | | |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Sinks category:

Click to view products by Advanced Thermal Solutions manufacturer:

Other Similar products are found below :

 581102B00000G
 656-15ABPE
 657-20ABPNE
 7020B-TC12-MTG
 73452PPBA
 7G0011A
 PF720G
 A22-4026
 120-1873-007
 HAH10L

 HAH15L
 1542616-1
 HS-2506-F1
 HS-87M0-F2
 218-40CTE3
 231-69PAB-15V
 25-7520
 SW50-4G
 231-75PAB-13V
 231-75PAB-15V
 253

 122ABE-22
 PSC22CB
 HAF10L
 HAQ10T
 D10100-28
 BDN183CBA01
 3-21053-4
 32438
 TX0506-1B
 TX1806B
 LAE66A3CB
 WA-DT2

 101E
 511-3U
 73381PPBA
 73403PPBA
 7G0047C
 COMX-440-HSP
 510-12M
 D10650-40T5
 V8511 Y
 APF40-40-13CB/A01

 780653U04500G
 ATS-54310K-C2-R0
 FK 216 CB SA
 FK 231 SA 220
 648-51AB
 657-20ABPESC
 2341BG
 679-25AG
 FK 212 CB SA