LEAK DETECTORS



Leak Detector/Automatic Shut Off Valves

ATS' **Automatic Shut Off Valves** are electronic devices for detecting leaks (water only) from the piping system. When the system detects a leak, it automatically shuts off a valve in the piping preventing the flow of water and start beeping indicating there is a leak. This device is mainly used in water filtration system, but it can be used in any application that has water flow.

FEATURES

- » Automatic shut off when water leak is detected
- » Automatic shut off when battery power is low
- » Easy installation
- >> Power: 9V battery
- » Model ATS-LD-20: "end of filter life" alert
- » Environmental temperature: 0–60°C

APPLICATIONS

- » Water cooler
- >> Water cooling loop
- » Water loop in a cold plate
- » Water dispenser
- » Laboratory testing
- » Industrial applications
- » Water filtration systems

PRODUCT SPECIFICATIONS



ATS-LD-14 Auto Shut Off Valve For Water Leak Included Adapters

Part #: ATS046028-CF90-R0 ½ NPT male, 18g (.6oz) Part #: ATS030026-CF91-R0 ½ BSPP female, 9g (.3oz)



ATS-LD-14BR Auto Shut Off Valve For Water Leak Included Adapters

For inlet:

5

 Part #: ATS025024-CF92-R0
 ½ BSPP male, 4.5g (.2oz)

 Part #: ATS044027-CF93-R0
 ½ NPT male, 13.6g .5oz)

Part #: ATS046028-CF90-R0 ½ NPT male, 18g (.6oz) Part #: ATS030026-CF91-R0 ½ BSPP female, 9g (.3oz)



ATS-LD-20 Leak Control & Filter Life Monitor

Included Adapters

Part #: ATSO46028-CF90-R0 ½ NPT male, 18g (.6oz) Part #: ATSO30026-CF91-R0 ½ BSPP female, 9g (.3oz)

Part Number	Cable Length	Weight	Connection	Adapter	Temp Range	Max Pressure	Material	Special Feature
ATS-LD-14	1.5 m (5 ft.)	175g (.4 lbs)	1/2" BSP MALE	ATS046028-CF90-R0 ATS030026-CF91-R0	0 – 60°C	6 Bar (87 Psi)	Plastic	Auto shut off when water leak is detected.
ATS-LD-14BR	1.5 m (5 ft.)	258g (.6 lbs)	1/2" BSP MALE	ATS025024-CF92-R0 ATS044027-CF93-R0 ATS046028-CF90-R0 ATS030026-CF91-R0	0 – 60°C	8 BAR (116 Psi)	Brass	Auto shut off when water leak is detected.
ATS-LD-20	1.5 m (5 ft.)	176g (.4 lbs)	1/2"BSP MALE	ATS046028-CF90-R0 ATS030026-CF91-R0	0 – 60°C	6 BAR (87 Psi)	Plastic	Auto shut off when water leak is detected. End of filter life alert.

89-27 ACCESS ROAD, NORWOOD, MA 02062 USA | T: 781.769. 2800 F: 781.769.9979 | WWW.QATS.COM

R2_1016

Part #: ATS044027-Cl For outlet: Part #: ATS046028-Cl Part #: ATS020024 Cl

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by Advanced Thermal Solutions manufacturer:

Other Similar products are found below :

61FGPN8DAC120 CV500SLK21 70177-1011 F03-03 HAS C F03-31 81550401 FT1A-C12RA-W 88981106 H2CAC24A H2CRSAC110B R88A-CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 AFP0RT32CT DRT2ID08C DTB4896VRE DTB9696CVE DTB9696LVE E53-AZ01 E53E01 E53E8C E5C4Q40J999FAC120 E5CWLQ1TCAC100240 E5GNQ03PFLKACDC24 B300LKL21 NSCXDC1V3 NSH5-232CW-3M NT20SST122BV1 NV-CN001 OAS-160-N C40PEDRA K31S6 K33-L1B K3MA-F 100-240VAC K3TX-AD31A 89750101 L595020 SRM1-C02 SRS2-1 G32X-V2K 26546803 26546805 PWRA440A CPM1AETL03CH CV500SLK11 3G2A5BI081 3G2A5IA122 3G2A5LK010E 3G2A5OA223