
# High Performance BGA Cooling Solutions with superGRIP™ Attachment




**ATS PART # ATS-X53330P-C1-R0** 

#### **Features & Benefits**

- » Designed for 33 x 33 mm BGA components
- » superGRIP™ super strong, uniform attachment force helps achieve maximum performance from phase-changing TIM and does not require holes in the PCB
- » Allows the heat sink to be detached and reattached without damaging the component and/or the PCB, an important feature in the event a PCB may need to be reworked
- » Meets Telcordia GR-63-Core Office Vibration, ETSI 300 019 Transportation Vibration, and MIL-STD-810 Shock Testing and Unpackaged Drop Testing standards
- » Requires minimal space around the component's perimeter; ideal for densely populated PCBs
- "Keep-Out" Requirements: An "Un-Populated" boarder zone of 3 mm around the component is necessary to facilitate the Installation/Removal of the superGRIP™. Please refer to the superGRIP™ Keep-Out Guidelines and superGRIP™ Installation/Removal Instructions for further details





## **Thermal Performance**

\*Image above is for illustration purposes only.

| AIR VELOCITY |     | THERMAL RESISTANCE   |                    |  |
|--------------|-----|----------------------|--------------------|--|
| FT/MIN       | M/S | °C/W (UNDUCTED FLOW) | °C/W (DUCTED FLOW) |  |
| 200          | 1.0 | 4.1                  | 2.3                |  |
| 300          | 1.5 | 3.0                  |                    |  |
| 400          | 2.0 | 2.6                  |                    |  |
| 500          | 2.5 | 2.3                  |                    |  |
| 600          | 3.0 | 2.1                  |                    |  |
| 700          | 3.5 | 2.0                  |                    |  |
| 800          | 4.0 | 1.8                  |                    |  |

## **Product Details**

| DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D | INTERFACE MATERIAL | FINISH        |
|-------------|-------------|-------------|-------------|--------------------|---------------|
| 33 mm       | 33 mm       | 17.5 mm     | 33 mm       | CHOMERICS T-766    | BLUE ANODIZED |

#### NOTES

- DIMENSIONS ARE MEASURED IN MILLIMETERS
- 2) DIMENSIONS A & B REFER TO COMPONENT SIZE
- 3) DIMENSION C = THE HEIGHT OF THE HEAT SINK SHOWN ABOVE AND DOES NOT INCLUDE THE HEIGHT OF THE ATTACHMENT METHOD
- 4) ATS RESERVES THE RIGHT TO UPDATE OR CHANGE IT PRODUCTS WITHOUT NOTICE
- 5) CONTACT ATS TO LEARN ABOUT CUSTOM OPTIONS AVAILABLE



For more information, to find a distributor or to place an order, visit www.qats.com or call: 781.769.2800 (North America); +31 (0) 3569 84715 (Europe).

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Sinks category:

Click to view products by Advanced Thermal Solutions manufacturer:

Other Similar products are found below:

581102B00000G 630-35ABT3 656-15ABPE 657-20ABPNE 73452PPBA 7721-13NG 7G0011A FI306/SE PF720G A22-4026 120-1873-007 HAH10L 1542256-2 1542026-1 1542616-1 HS-2506-F1 HS-87M0-F2 218-40CTE3 25-7520 188854F00000G F-QB-F1

APA501-60-003 253-122ABE-22 PSC22CB CLP-201 CLP212SG CLP-7701G HAA072 HAA083 HAF10L HAQ10T D10100-28 TO5-002D 513101B02500G BDN183CBA01 531202B0000 HS-56M0-C1 3-21053-4 TX0506-1B TX1806B 336614B-00000 V2004X

LAE66A3CB WA-DT2-101E 511-3U 017177 530510B00000G 6110BG 73381PPBA 73403PPBA