



Compare Queue (0)

[Send Feedback](#)

English

Type Here to Search Products

[Home](#)
[Intel® Processors](#)
[3rd Generation Intel® Core™ i5 Processors](#)
[Intel® Core™ i5-3600 Mobile Processor Series](#)

i5-3610ME



## Intel® Core™ i5-3610ME Processor (3M Cache, up to 3.30 GHz)

### SPECIFICATIONS

[All](#)
[Essentials](#)
[Memory Specifications](#)
[Graphics Specifications](#)
[Expansion Options](#)
[Package Specifications](#)
[Advanced Technologies](#)
[ORDERING / SSPECS /  
STEPPINGS](#)

### Specifications

#### Essentials

Status	Launched
Launch Date	Q2'12
Processor Number	i5-3610ME
# of Cores	2
# of Threads	4
Clock Speed	2.7 GHz
Max Turbo Frequency	3.3 MHz
Intel® Smart Cache	3 MB
Bus/Core Ratio	27
DMI	5 GT/s
Instruction Set	64-bit
Instruction Set Extensions	AVX
Embedded Options Available	Yes
Lithography	22nm
Max TDP	35 W
Recommended Customer Price	TRAY: \$276
Description	ECC memory support only on BGA package

#### Memory Specifications

Max Memory Size (dependent on memory type)	32 GB
Memory Types	DDR3/DDR3L 1333/1600
# of Memory Channels	2
Max Memory Bandwidth	25.6 GB/s
<a href="#">ECC Memory Supported</a>	Yes

#### Graphics Specifications

Processor Graphics	Intel® HD Graphics 4000
Graphics Base Frequency	650 MHz
Graphics Max Dynamic Frequency	950 MHz
Graphics Output	eDP/DP/HDMI/SDVO/CRT
Intel® Quick Sync Video	Yes
Intel® InTru™ 3D Technology	Yes
Intel® Insider™	No
Intel® Wireless Display	No
Intel® Flexible Display Interface (Intel® FDI)	Yes
Intel® Clear Video HD Technology	Yes
Intel® Clear Video Technology for MID	No

### COMPARE PRODUCTS

- [Add to Compare](#)
- [Compare Now \(0\)](#)

- [Visit the Embedded Design Center >](#)

### QUICK LINKS

- [Products formerly Ivy Bridge](#)
- [No Datasheet Available](#)
- [Search Distributors](#)

### ADDITIONAL INFORMATION










#### PCN/MDDS INFORMATION

##### SR0QK

920313: [PCN](#) | [MDDS](#)

##### SR0QJ

920312: [PCN](#) | [MDDS](#)

Dual Display Capable	Yes
<b>*Trademarks</b>	
# of Displays Supported	 3
<b>Expansion Options</b>	
PCI Express Revision	3.0
PCI Express Configurations	 1x16 2x8 1x8 2x4
# of PCI Express Ports	1
<b>Package Specifications</b>	
Max CPU Configuration	1
T <sub>JUNCTION</sub>	105°C
Package Size	37.5mmx 37.5mm PGA
Graphics and IMC Lithography	22nm
Sockets Supported	FCBGA1023, FCPGA988
Low Halogen Options Available	See MDDS
<b>Advanced Technologies</b>	
Intel® Turbo Boost Technology	2.0
Intel® vPro Technology	Yes
Intel® Hyper-Threading Technology	 Yes
Intel® Virtualization Technology (VT-x)	 Yes
Intel® Virtualization Technology for Directed I/O (VT-d)	 Yes
Intel® Trusted Execution Technology	 Yes
AES New Instructions	 Yes
Intel® 64	 Yes
Intel® Anti-Theft Technology	No
Intel® My WiFi Technology	Yes
4G WiMAX Wireless Technology	No
Idle States	Yes
Enhanced Intel SpeedStep® Technology	 Yes
Intel® Demand Based Switching	No
Thermal Monitoring Technologies	Yes
Intel® Fast Memory Access	Yes
Intel® Flex Memory Access	Yes
Execute Disable Bit	Yes
Intel® Virtualization Technology for Itanium (VT-i)	No
Intel® VT-x with Extended Page Tables (EPT)	Yes

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See [http://www.intel.com/products/processor\\_number](http://www.intel.com/products/processor_number) for details.

Hyper-Threading Technology (HT Technology) requires a computer system with an Intel® processor supporting HT Technology and an HT Technology enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you use. See [www.intel.com/products/ht/hyperthreading\\_more.htm](http://www.intel.com/products/ht/hyperthreading_more.htm) for more information including details on which processors support HT Technology.

64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Consult with your system vendor for more information.

Max Turbo Frequency refers to the maximum single-core frequency that can be achieved with Intel® Turbo Boost Technology, which requires a PC with a processor with Intel Turbo Boost Technology capability. Intel Turbo Boost Technology performance varies depending on hardware, software, and overall system configuration. Check with your PC manufacturer on whether your system delivers Intel Turbo Boost Technology. See [www.intel.com/technology/turboboost/](http://www.intel.com/technology/turboboost/) for more information.

Enabling Execute Disable Bit functionality requires a PC with a processor with Execute Disable Bit capability and a supporting operating system. Check with your PC manufacturer on whether your system delivers Execute Disable Bit functionality.

Intel® Virtualization Technology requires a computer system with a processor, chipset, BIOS, virtual machine monitor (VMM) and for some uses, certain platform software, enabled for it. Functionality, performance or other benefit will vary depending on hardware and software configurations. Intel Virtualization Technology-enabled VMM applications are currently in development.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.



Compare Queue (0)

Send Feedback

English

Type Here to Search Products

Home

Intel® Processors

3rd Generation Intel® Core™ i5 Processors

Intel® Core™ i5-3600 Mobile Processor Series

i5-3610ME



## Intel® Core™ i5-3610ME Processor (3M Cache, up to 3.30 GHz)

### SPECIFICATIONS

#### ORDERING / SSPECS / STEPPINGS

#### All

#### Ordering / sSpecs / Steppings

#### Retired and Discontinued

### ORDERING AND SPEC INFORMATION

#### Ordering and Spec Information

#### Intel® Core™ i5-3610ME Processor (3M Cache, up to 3.30 GHz) FC-PGA12F, Tray

Socket	Step	Step TDP	Ordering Code	Spec Code	VT-x	ECCN	CCATS	US HTS	RCP
FCPGA988	L1	35 W	AW8063801115901	SR0QJ	Yes	5A992C	G077159	8542310000-HYBRD	\$276

#### Intel® Core™ i5-3610ME Processor (3M Cache, up to 3.30 GHz) FC-BGA12F, Tray

Socket	Step	Step TDP	Ordering Code	Spec Code	VT-x	ECCN	CCATS	US HTS	RCP
FCBGA1023	L1	35 W	AV8063801116102	SR0QK	Yes	5A992C	G077159	8542310000-HYBRD	\$276

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See [http://www.intel.com/products/processor\\_number](http://www.intel.com/products/processor_number) for details.

Hyper-Threading Technology (HT Technology) requires a computer system with an Intel® processor supporting HT Technology and an HT Technology enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you use. See [www.intel.com/products/ht/hyperthreading\\_more.htm](http://www.intel.com/products/ht/hyperthreading_more.htm) for more information including details on which processors support HT Technology.

64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Consult with your system vendor for more information.

Max Turbo Frequency refers to the maximum single-core frequency that can be achieved with Intel® Turbo Boost Technology, which requires a PC with a processor with Intel Turbo Boost Technology capability. Intel Turbo Boost Technology performance varies depending on hardware, software, and overall system configuration. Check with your PC manufacturer on whether your system delivers Intel Turbo Boost Technology. See [www.intel.com/technology/turboboost/](http://www.intel.com/technology/turboboost/) for more information.

Enabling Execute Disable Bit functionality requires a PC with a processor with Execute Disable Bit capability and a supporting operating system. Check with your PC manufacturer on whether your system delivers Execute Disable Bit functionality.

Intel® Virtualization Technology requires a computer system with a processor, chipset, BIOS, virtual machine monitor (VMM) and for some uses, certain platform software, enabled for it. Functionality, performance or other benefit will vary depending on hardware and software configurations. Intel Virtualization Technology-enabled VMM applications are currently in development.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

#### \*Trademarks

©Intel  
Corporation

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for CPU - Central Processing Units category:*

*Click to view products by [Advantech](#) manufacturer:*

Other Similar products are found below :

[D8751H](#) [AT80612003090AAS LBWJ](#) [N87C51](#) [IVPX7225-RTM-1](#) [CM8063401286600S R1AK](#) [CM8063501374802S R1A5](#)  
[CM8063501375101S R1A8](#) [MATXM-CORE-411-HTSNK](#) [BGSF 1717MN26 E6327](#) [BX80621E52620 S R0KW](#) [IVPX7225-02250813L](#)  
[D8086-2](#) [CM8063401293902S R1A4](#) [CM8063501374901S R1A6](#) [CM8066201928505 SR2HT](#) [CM8063501293200S R1A0](#)  
[CM8062301046008S R060](#) [ATLASEDGE.1](#) [AV8063801129600S R10F](#) [R0K5ML001SS00BR](#) [CM8066201921712S R2LF](#)  
[CM8064601467102S R152](#) [CM8063701094000S R0TA](#) [CM8063501375800S R1AX](#) [CM8063401376400S R1A9](#) [CM8063401293802S R1A3](#)  
[CM8063401286102S R19S](#) [CM8062107185405S R0KM](#) [CM8066002032201S R2R6](#) [CM8063501288301S R1AN](#) [COMX-300-HSP](#) [RTM-](#)  
[ATCA-7360](#) [96MPI7-3.4-8M11T](#) [96MPP-2.3-3M10T](#) [96MPI7-3.4-8M11T1](#) [96MPXE-2.0-15M20T](#) [96MPI5-3.0-6M10T](#) [96MPI5S-2.3-](#)  
[6M11T1](#) [FJ8066401715827S R2KG](#) [AFPC205 S R1Z1](#) [DNCE2510 S LHCM](#) [FJ8066401715843S R2KH](#) [DNCE2530G S LHCY](#)  
[DNCE2510GU S LHCW](#) [CM8066201935807S R2LM](#) [FH8065503554000S R3H4](#) [FH8065301615104S R1UU](#) [CM8066201934909S R2LK](#)  
[FJ8067702739633S R340](#) [CM8068403360212 SR3XB](#)