

ADAM-3011 ADAM-3013 ADAM-3014

Isolated Thermocouple Input Module

Isolated RTD Input Module

Isolated DC Input/Output Module



ADAM-3011

CE FCC



ADAM-3013

CE FCC



ADAM-3014

CE FCC

Specifications

Thermocouple Input

- Common Mode Rejection 115 dB min
- Input Type

T/C Type	Temperature Range (°C)	Accuracy at 25 °C
J	-40 ~ 760	±2
K	0 ~ 1,000	±2
T	-100 ~ 400	±2
E	0 ~ 1,000	±2
S	500 ~ 1,750	±4
R	500 ~ 1,750	±4
B	500 ~ 1,800	±4

- Isolation 1,000 V_{DC} (three way)
- Output Impedance 0.5 Ω
- Stability (Temperature Drift) ±2 °C
- Voltage Output 0 ~ 10 V

General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V_{DC}
- Power Consumption 1.4 W
- Power Input 24 V_{DC} ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature 0 ~ 50 °C (32 ~ 122 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

Ordering Information

- ADAM-3011-AE Isolated thermocouple input module

Specifications

RTD Input

- Accuracy ±0.1% of full range (voltage) or ±0.15 °C (voltage)
±0.2% of full range (current)
- Bandwidth 4 Hz
- Input CMR at DC 92 dB min.
- Input Connections 2/3/4 wires
- Input Type

RTD Type	α	Temperature Range (°C)
Pt	0.00385	-100 ~ 100
Pt	0.00385	0 ~ 100
Pt	0.00385	0 ~ 200
Pt	0.00385	0 ~ 600
Pt	0.00385	-100 ~ 0
Pt	0.00385	-100 ~ 200
Pt	0.00385	-50 ~ 50
Pt	0.00385	-50 ~ 150
Pt	0.00392	-100 ~ 100
Pt	0.00392	0 ~ 100
Pt	0.00392	0 ~ 200
Pt	0.00392	0 ~ 600
Ni	N/A	0 ~ 100
Ni	N/A	-80 ~ 100

- Output Range 0 ~ 5 V, 0 ~ 10 V, 0 ~ 20 mA
- Output Resistance < 5 Ω
- Temperature Drift ±30 ppm of full range

General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V_{DC}
- Power Consumption < 0.95 W
- Power Input 24 V_{DC} ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature 0 ~ 70 °C (32 ~ 158 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

Ordering Information

- ADAM-3013-AE Isolated RTD input module

Specifications

I/O

- Accuracy ±0.1% of full range (typical)
- Common Mode Rejection > 100 dB @ 50 Hz/60 Hz
- Current Input Bipolar: ±20 mA
Unipolar: 0 ~ 20 mA
Input impedance: 250 Ω
- Current Output 0 ~ 20 mA
- Stability (Temperature Drift) 150 ppm (typical)
- Voltage Input Bipolar input: ±10 mV, ±50 mV, ±100 mV, ±0.5 V, ±1.0 V, ±5 V, ±10 V
Unipolar input: 0 ~ 10 mV, 0 ~ 50 mV, 0 ~ 100 mV, 0 ~ 0.5 V, 0 ~ 1 V, 0 ~ 5 V, 0 ~ 10 V
Input impedance: 2 MΩ
Input bandwidth: 2.4 kHz (typical)
- Voltage Output Bipolar: ±5 V, ±10 V
Unipolar: 0 ~ 10 V
Impedance: < 50 Ω
Drive: 10 mA max.

General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V_{DC} (three way)
- Power Consumption 0.85 W (voltage output)
1.2 W (current output)
- Power Input 24 V_{DC} ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature -10 ~ 70 °C (14 ~ 158 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

Ordering Information

- ADAM-3014-AE Isolated DC input/output module

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Temperature Sensor Modules](#) category:

Click to view products by [Advantech](#) manufacturer:

Other Similar products are found below :

[084Z6042](#) [TX4L-14S](#) [084Z6041](#) [QP99](#) [CP82](#) [CP99](#) [R38-LAOO](#) [R38-LARR](#) [72-11304023-0150.0050](#) [72-11304027-0150.0050](#) [72-23304003-0150.0050.GGP](#) [72-23904001-0300.0040.TM](#) [TEM 73 A](#) [AT403-414-1000](#) [AT403-614-1000](#) [AT-503-1141-000](#) [AT-503-1161-000](#) [AT-503-6140-000](#) [AT-603-1141-000](#) [AT603-414-1000](#) [ATR121-AD](#) [ATR121-B](#) [TPMC-5](#) [TPMC-8W](#) [K39-HCRR](#) [K39T-HCRR](#) [K49-HCRR](#) [K49P-HCRR](#) [K85-HERR](#) [KR1-LCRR-D](#) [LHI968](#) [ZAD-1V2-24](#) [ZAD-ECO-V2](#) [RO](#) [E5CB-Q1P](#) [100-240AC](#) [E5CB-R1TC](#) [100-240AC](#) [E5CSV-R1T-500](#) [100-240AC](#) [E5CSV-R1TD-500](#) [24AC/DC](#) [RT-4](#) [SONDA](#) [DS18S20](#) [RTM-01](#) [RTM-02](#) [RTM-30](#) [RTM-30/S](#) [72-11301001-0300.0045.PP](#) [72-11301002-0300.0045.SS](#) [72-23304001-0150.0100.GGP](#) [CP82C](#) [STZ-02](#) [TPMC-7W](#) [TPMC-8](#)