

ADAM-3011 ADAM-3013 ADAM-3014

Isolated Thermocouple Input Module

Isolated RTD Input Module

Isolated DC Input/Output Module



ADAM-3011

CE FCC



ADAM-3013

CE FCC



ADAM-3014

CE FCC

Specifications

Thermocouple Input

- Common Mode Rejection 115 dB min
- Input Type

T/C Type	Temperature Range (°C)	Accuracy at 25 °C
J	-40 ~ 760	±2
K	0 ~ 1,000	±2
T	-100 ~ 400	±2
E	0 ~ 1,000	±2
S	500 ~ 1,750	±4
R	500 ~ 1,750	±4
B	500 ~ 1,800	±4

- Isolation 1,000 V_{DC} (three way)
- Output Impedance 0.5 Ω
- Stability (Temperature Drift) ±2 °C
- Voltage Output 0 ~ 10 V

General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V_{DC}
- Power Consumption 1.4 W
- Power Input 24 V_{DC} ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature 0 ~ 50 °C (32 ~ 122 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

Ordering Information

- ADAM-3011-AE Isolated thermocouple input module

Specifications

RTD Input

- Accuracy ±0.1% of full range (voltage) or ±0.15 °C (voltage)
±0.2% of full range (current)
- Bandwidth 4 Hz
- Input CMR at DC 92 dB min.
- Input Connections 2/3/4 wires
- Input Type

RTD Type	α	Temperature Range (°C)
Pt	0.00385	-100 ~ 100
Pt	0.00385	0 ~ 100
Pt	0.00385	0 ~ 200
Pt	0.00385	0 ~ 600
Pt	0.00385	-100 ~ 0
Pt	0.00385	-100 ~ 200
Pt	0.00385	-50 ~ 50
Pt	0.00385	-50 ~ 150
Pt	0.00392	-100 ~ 100
Pt	0.00392	0 ~ 100
Pt	0.00392	0 ~ 200
Pt	0.00392	0 ~ 600
Ni	N/A	0 ~ 100
Ni	N/A	-80 ~ 100

- Output Range 0 ~ 5 V, 0 ~ 10 V, 0 ~ 20 mA
- Output Resistance < 5 Ω
- Temperature Drift ±30 ppm of full range

General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V_{DC}
- Power Consumption < 0.95 W
- Power Input 24 V_{DC} ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature 0 ~ 70 °C (32 ~ 158 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

Ordering Information

- ADAM-3013-AE Isolated RTD input module

Specifications

I/O

- Accuracy ±0.1% of full range (typical)
- Common Mode Rejection > 100 dB @ 50 Hz/60 Hz
- Current Input Bipolar: ±20 mA
Unipolar: 0 ~ 20 mA
Input impedance: 250 Ω
- Current Output 0 ~ 20 mA
- Stability (Temperature Drift) 150 ppm (typical)
- Voltage Input Bipolar input: ±10 mV, ±50 mV, ±100 mV, ±0.5 V, ±1.0 V, ±5 V, ±10 V
Unipolar input: 0 ~ 10 mV, 0 ~ 50 mV, 0 ~ 100 mV, 0 ~ 0.5 V, 0 ~ 1 V, 0 ~ 5 V, 0 ~ 10 V
Input impedance: 2 MΩ
Input bandwidth: 2.4 kHz (typical)
- Voltage Output Bipolar: ±5 V, ±10 V
Unipolar: 0 ~ 10 V
Impedance: < 50 Ω
Drive: 10 mA max.

General

- Connectors Screw terminal
- Enclosure ABS
- Indicators Power LED indicator
- Isolation 1,000 V_{DC} (three way)
- Power Consumption 0.85 W (voltage output)
1.2 W (current output)
- Power Input 24 V_{DC} ±10%
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature -10 ~ 70 °C (14 ~ 158 °F)
- Storage Temperature -25 ~ 85 °C (-13 ~ 185 °F)

Ordering Information

- ADAM-3014-AE Isolated DC input/output module

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Modules](#) category:

Click to view products by [Advantech](#) manufacturer:

Other Similar products are found below :

[70L-IDC5S](#) [70L-OAC-L](#) [70Z3289-4](#) [G21960000700](#) [G21960002700](#) [G34960002700](#) [OACU](#) [C4SWOUT](#) [PB16H](#) [G34960001700](#) [G3TA-OA101SZ-1](#) [DC24](#) [G77-S](#) [5607189](#) [DA5](#) [ODC-24A](#) [IDC5P](#) [FC6A-N16B1](#) [6421](#) [70MRCQ32-HL](#) [G3TAOD201SDC24](#) [C200H-LK201-V1](#)
[G3TA-OA202SZ-US](#) [DC12](#) [GT1-OD16](#) [GT1-AD04CST](#) [B7AM-6BS](#) [70GRCQ24-HS](#) [6422](#) [84110410](#) [GT1-OD16MX](#) [G7VC-OC16-B7](#)
[70MRCK24-DIN](#) [6202](#) [6402](#) [PI/NI-2D/24](#) [FC6A-J2C1](#) [FC6A-KC1C](#) [FC6A-R081](#) [FC6A-J8CU1](#) [GP32900003700](#) [641-480-5022](#) [PB16H](#)
[84145010](#) [84110210](#) [FRUSB1601](#) [PCL-720+-BE](#) [FRRJ451601](#) [AP24MX3DB25F](#) [ADAM-5053S-AE](#) [WISE-S614-A](#) [C200H-OD211](#)