

ADAM-4053 ADAM-4055 ADAM-4080

16-ch Digital Input Module

16-ch Isolated Digital I/O Module with Modbus

2-ch Counter/Frequency Module



ADAM-4053



ADAM-4055



ADAM-4080



Specifications

General

- **Connectors** 2 x plug-in terminal blocks (#14 ~ 22 AWG)
- **Power Consumption** 0.4 W @ 24 V DC typ.
0.7 W @ 24 V DC max.
- **Watchdog Timer** System (1.6 second)
- **Supported Protocols** ASCII command and Modbus/RTU

Digital Input

- **Channels** 16
- **Input Level**
Dry contact: Logic level 0: close to GND
Logic level 1: open
Wet contact: Logic level 0: 2 V max.
Logic level 1: 4 ~ 30 V
- **Effective Distance** 500 m max.
(dry contact only)

Specifications

General

- **Connectors** 2 x plug-in terminal blocks (#14 ~ 28 AWG)
- **Power Consumption** 1 W @ 24 V DC typ.
1.7 W @ 24 V DC max.
- **Watchdog Timer** System (1.6 second) & Communication
- **Supported Protocols** ASCII command and Modbus/RTU

- **Isolation Voltage** 2,500 V_{DC}
- **LED Indicators** Yes

Digital Input

- **Channels** 8
- **Input Level**
Dry Contact: Logic level 0: open
Logic level 1: close to GND
Logic level 0: 3 V max.
Logic level 1: 10 ~ 50 V
Wet Contact: 70 V_{DC}
- **Overvoltage Protection**

Digital Output

- **Channels** 8, open collector to 40 V (200 mA max. load)
- **Power Dissipation** Channel: 1 W max.
Total: 2.2 W (8 Channels)

Specifications

General

- **Connectors** 2 x plug-in terminal blocks (#14 ~ 22 AWG)
- **Power Consumption** 2.0 W @ 24 V_{DC}
- **Watchdog Timer** System (1.6 second)
- **Supported Protocols** ASCII command
- **LED Indicators** 5-digit readout, Ch 0 or Ch 1 (programmable)

Counter Input

- **Channels** 2 independent counters (32-bit + 1-bit overflow)
- **Input Frequency** 50 kHz max.
- **Input Pulse Width** >10 μs.
- **Input Mode** Isolated or non-isolated
- **Isolated Input Level** Logic level 0: 1 V max.
Logic level 1: 3.5~30 V
- **Isolation Voltage** 2,500 V_{RMS}
- **Non-isolated Input Level** Programmable threshold:
Logic level 0: 0.8 V_{max}.
Logic level 1: 2.4 ~ 5.0 V
- **Maximum Count** 4,294,967,295 (32 bits)
- **Preset Type** Absolute or relative
- **Programmable Digital Noise Filter** 2 μs ~ 65 ms
- **Alarm** Alarm comparators on each counter
- **Frequency Measurement Range** 5 Hz ~ 50 kHz
- **Programmable Built-in Gate Time** 1 or 0.1 second

Digital Output

- **Channels** 2, open collector to 30 V, 30 mA max. load
- **Power Dissipation** 300 mW for each channel

Common Specifications

General

- **Power Input** Unregulated 10 ~ 30 V_{DC}

Environment

- **Humidity** 5 ~ 95% RH
- **Operating Temperature** -10 ~ 70°C (14 ~ 158°F)
- **Storage Temperature** -25 ~ 85°C (-13 ~ 185°F)

Ordering Information

- **ADAM-4053** 16-ch Digital Input Module
- **ADAM-4055** 16-ch Isolated Digital I/O Module with Modbus
- **ADAM-4080** 2-ch Counter/Frequency Modules

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Modules](#) category:

Click to view products by [Advantech](#) manufacturer:

Other Similar products are found below :

[70L-IDC5S](#) [70L-OAC-L](#) [70Z3289-4](#) [G21960000700](#) [G21960002700](#) [G34960002700](#) [OACU](#) [C4SWOUT](#) [PB16H](#) [G34960001700](#) [G3TA-OA101SZ-1](#) [DC24](#) [G77-S](#) [5607189](#) [DA5](#) [ODC-24A](#) [IDC5P](#) [FC6A-N16B1](#) [6421](#) [FC6A-N32B3](#) [70MRCQ32-HL](#) [G3TAOD201SDC24](#) [C200H-LK201-V1](#) [G3TA-OA202SZ-US](#) [DC12](#) [GT1-OD16](#) [GT1-AD04CST](#) [B7AM-6BS](#) [70GRCQ24-HS](#) [6422](#) [84110410](#) [GT1-OD16MX](#) [G7VC-OC16-B7](#) [70MRCK24-DIN](#) [6202](#) [6402](#) [FC6A-J2C1](#) [FC6A-KC1C](#) [FC6A-R081](#) [FC6A-J8CU1](#) [GP32900003700](#) [641-480-5022](#) [PB16H](#) [84145010](#) [84110210](#) [FRUSB1601](#) [PCL-720+-BE](#) [FRRJ451601](#) [AP24MX3DB25F](#) [ADAM-5053S-AE](#) [WISE-S614-A](#) [ADAM-5051S-AE](#)