

# ADAM-6150

## ADAM-6151/6156

15-ch Isolated Digital I/O Real-time Ethernet Module

16-ch Isolated Digital Input/ Digital Output Real-time Ethernet Module



ADAM-6150

FCC CE RoHS COMPLIANT 2002/95/EC

### Specifications

#### Digital Input

- Channels 8
- Dry Contact Logic level 0: open  
Logic level 1: close to DGND
- Wet Contact Logic level 0: 0 ~ 3 V<sub>DC</sub> or 0 ~ -3 V<sub>DC</sub>  
Logic level 1: 10 ~ 30 V<sub>DC</sub> or -10 ~ -30 V<sub>DC</sub>  
(Dry/Wet Contact decided by switch)
- Input Impedance 5.2 k $\Omega$  (Wet Contact)
- Transition Time From logic level 0 to 1: 0.2 ms  
From logic level 1 to 0: 0.2 ms

#### Digital Output

- Channels 7
- Output Voltage Range 8 ~ 35 V<sub>DC</sub>
- Normal Output Current 100 mA (per channel)

### Ordering Information

- ADAM-6150EI 15-ch Isolated DI/O EtherNet/IP Module
- ADAM-6150PN 15-ch Isolated DI/O PROFINET Module



ADAM-6151/6156

FCC CE RoHS COMPLIANT 2002/95/EC

### Specifications

#### Digital Input (ADAM-6151)

- Channels 16
- Dry Contact Logic level 0: open  
Logic level 1: close to DGND
- Wet Contact Logic level 0: 0 ~ 3 V<sub>DC</sub> or 0 ~ -3 V<sub>DC</sub>  
Logic level 1: 10 ~ 30 V<sub>DC</sub> or -10 ~ -30 V<sub>DC</sub>  
(Dry/Wet Contact decided by switch)
- Input Impedance 5.2 k $\Omega$  (Wet Contact)
- Transition Time From logic level 0 to 1: 0.2 ms  
From logic level 1 to 0: 0.2 ms

#### Digital Output (ADAM-6156)

- Channels 16
- Output Voltage Range 8 ~ 35 V<sub>DC</sub>
- Normal Output Current 100 mA (per channel)

### Ordering Information

- ADAM-6151EI 16-ch Isolated DI EtherNet/IP Module
- ADAM-6151PN 16-ch Isolated DI PROFINET Module
- ADAM-6156EI 16-ch Isolated DO EtherNet/IP Module
- ADAM-6156PN 16-ch Isolated DO PROFINET Module

## Common Specifications

#### General

- LAN 10/100Base-T(X)
- Power Consumption ADAM-6150: 3 W @ 24 V<sub>DC</sub>  
ADAM-6151: 2.7 W @ 24 V<sub>DC</sub>  
ADAM-6156: 3.2 W @ 24 V<sub>DC</sub>
- Connectors 2 x RJ-45 LAN, (Daisy Chain)  
Plug-in screw terminal block (I/O and power)
- Watchdog System (1.6 second)
- Power Input 10 ~ 30 V<sub>DC</sub>

#### Protection

- Over Voltage Protection  $\pm 35$  V<sub>DC</sub>
- Isolation Protection 2,500 V<sub>DC</sub>
- Power Reversal Protection

#### Environment

- Operating Temperature -10 ~ 70°C (14 ~ 158°F)
- Storage Temperature -20 ~ 80°C (-4 ~ 176°F)
- Operating Humidity 20 ~ 95% RH (non-condensing)
- Storage Humidity 0 ~ 95% RH (non-condensing)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [I/O Modules](#) category:*

*Click to view products by [Advantech](#) manufacturer:*

Other Similar products are found below :

[70L-IDC5S](#) [70L-OAC-L](#) [70Z3289-4](#) [G21960000700](#) [G21960002700](#) [G34960002700](#) [OACU](#) [C4SWOUT](#) [PB16H](#) [G34960001700](#) [G3TA-OA101SZ-1](#) [DC24](#) [G77-S](#) [5607189](#) [DA5](#) [ODC-24A](#) [IDC5P](#) [FC6A-N16B1](#) [6421](#) [FC6A-N32B3](#) [70MRCQ32-HL](#) [G3TAOD201SDC24](#) [C200H-LK201-V1](#) [G3TA-OA202SZ-US](#) [DC12](#) [GT1-OD16](#) [GT1-AD04CST](#) [B7AM-6BS](#) [70GRCQ24-HS](#) [6422](#) [84110410](#) [GT1-OD16MX](#) [G7VC-OC16-B7](#) [70MRCK24-DIN](#) [6202](#) [6402](#) [FC6A-J2C1](#) [FC6A-KC1C](#) [FC6A-R081](#) [FC6A-J8CU1](#) [GP32900003700](#) [641-480-5022](#) [PB16H](#) [84145010](#) [84110210](#) [FRUSB1601](#) [PCL-720+-BE](#) [FRRJ451601](#) [AP24MX3DB25F](#) [ADAM-5053S-AE](#) [WISE-S614-A](#) [ADAM-5051S-AE](#)