

# APAX-5070 APAX-5071 APAX-5072

## Modbus/TCP Communication Coupler

## PROFINET Communication Coupler

## EtherNet/IP Communication Coupler



APAX-5070



APAX-5071



APAX-5072



### Specifications

#### General

- **Certification** CE, FCC class A
- **Dimensions (W x H x D)** 30 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 190 g
- **Connector** 2 x RJ-45 (2-channel switch, share same IP address)
- **Power Consumption** 2 W @ 5 V<sub>DC</sub> (typical)

#### Communication

- **Protocol** Modbus/TCP
- **Connected I/O Modules** 32 (max.)\*
- **Digital Signals** 768 (max.)
- **Analog Signals** 192 (max.)
- **Data Transfer Rates** 10/100 Mbps
- **Topology** Line or star
- **Isolation Protection** 1,500 V<sub>AC</sub>

#### Environment

- **Operating Temperature** -10 ~ 60°C (mounted vertically)
- **Storage Temperature** -40 ~ 85°C
- **Relative Humidity** 5 ~ 95% (non-condensing)
- **Shock Protection** 10 G @ wall mount, half sine, 11 ms (confirms to IEC 60068-2-27)
- **Vibration Protection** 1 Grms @ 5 ~ 500 Hz (random, operating, 1 hr/axis)  
2 G @ 5 ~ 500 Hz (sine, non-operating, 1 hr/axis) (confirms to IEC 60068-2-64 and IEC 60068-2-6)

### Ordering Information

- **APAX-5070** Modbus/TCP Communication Coupler

### Specifications

#### General

- **Certification** CE, FCC class A
- **Dimensions (W x H x D)** 30 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 180 g
- **Connector** 2 x RJ-45 (2-channel switch, share same IP address)
- **Power Consumption** 2 W @ 5 V<sub>DC</sub> (typical)

#### Communication

- **Protocol** PROFINET RT V2.2
- **Connected I/O Modules** 32 (max.)\*
- **Digital Signals** 768 (max.)
- **Analog Signals** 192 (max.)
- **Data Transfer Rates** 10/100 Mbps
- **Topology** Line or Star

#### Environment

- **Operating Temperature** -10 ~ 60°C (mounted vertically)
- **Storage Temperature** -40 ~ 85°C
- **Relative Humidity** 5 ~ 95% (non-condensing)
- **Shock Protection** 10 G @ wall mount, half sine, 11 ms (Confirms to IEC 60068-2-27)
- **Vibration Protection** 1 Grms @ 5 ~ 500 Hz (random, operating, 1 hr/axis)  
2 G @ 5 ~ 500 Hz (sine, non-operating, 1 hr/axis) (confirms to IEC 60068-2-64 and IEC 60068-2-6)

### Ordering Information

- **APAX-5071** PROFINET Communication Coupler

### Specifications

#### General

- **Certification** CE, FCC class A
- **Dimensions (W x H x D)** 30 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 180 g
- **Connectors** 2 x RJ-45 (2-channel switch, share same IP address)
- **Power Consumption** 2 W @ 5 V<sub>DC</sub> (typical)

#### Communications

- **Protocol** EtherNet/IP
- **Connected I/O Modules** 32 (max.)\*
- **Digital Signals** 768 (max.)
- **Analog Signals** 192 (max.)
- **Data Transfer Rates** 10/100 Mbps
- **Topology** Line or star
- **Isolation Protection** 1,500 V<sub>AC</sub>

#### Environment

- **Operating Temperature** -10 ~ 60°C (mounted vertically)
- **Storage Temperature** -40 ~ 85°C
- **Relative Humidity** 5 ~ 95% (non-condensing)
- **Shock Protection** 10 G @ wall mount, half sine, 11 ms (confirms to IEC 60068-2-27)
- **Vibration Protection** 1 Grms @ 5 ~ 500 Hz (random, operating, 1 hr/axis)  
2 G @ 5 ~ 500 Hz (sine, non-operating, 1 hr/axis) (confirms to IEC 60068-2-64 and IEC 60068-2-6)

### Ordering Information

- **APAX-5072** EtherNet/IP Communication Coupler

#### Accessories

- **APAX-5002** 2-slot Backplane Module

\*APAX DI/O modules can use ID number 0 ~ 31, while AI/O modules and counter modules can only use ID numbers 0 ~ 15

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Networking Modules](#) category:*

*Click to view products by [Advantech](#) manufacturer:*

Other Similar products are found below :

[MS25041-4-327](#) [SE305-T](#) [509FX-SC](#) [SE308-T](#) [FCOPPER-SFP-100](#) [75070R-70](#) [75060R-40](#) [301-2010-27](#) [DC-ES-4SB-EU](#)  
[MGM111E256V2](#) [LTP5901IPC-IPRB1C1#PBF](#) [LTP5901IPC-IPRC1C2#PBF](#) [LTP5901IPC-IPRC1C1#PBF](#) [LTP5901IPC-IPRB1C2#PBF](#)  
[LTP5901IPC-IPRA1C2#PBF](#) [VSMD001V072](#) [65440R](#) [2000000844](#) [2000000849](#) [WISE-1020-0C01E](#) [WISE-1020-0S01E](#) [WISE-1021WR-1100E](#) [RAPID-NI-V2005](#) [RAPID-NI-V2011](#) [RAPID-NI-V2105](#) [855-19619](#) [X2E-Z1C-W1-W](#) [X2E-Z4C-D2-A](#) [PuIM-1G4T-I211-BP-R10](#)  
[PuIM-1G4T-I211-R10](#) [PUZZLE-IN003B-C0/8G-R10](#) [XXV710DA2OCP2](#) [MO11AA003-01R](#) [WP20010NMK-01](#) [WP500100S-01](#)  
[XP1001000-05R](#) [XP1001000M-05R](#) [XP100200S-05R](#) [XPDNC2000-01](#) [XPP100200S-02R](#) [112113-0001](#) [112113-0007](#) [1203630001](#) [SST-DN4-PCU](#) [2200515](#) [XpressV7-LP690HE-Gen3](#) [113990838](#) [SD-300-US](#) [MGM13P02F512GA-V2](#) [MGM13S02F512GA-V3](#)