ECU-1051TL

Cloud enabled Intelligent Communication Gateway for IIOT application



Features

- TI Cortex A8 600MHz CPU with DDR3L 256MB RAM
- Support web service for remotely on-line monitoring
- Firmware update by SD card and online update
- Data logger on SD card
- Support dual SIM slots for communication redundant
- Support MQTT Client for cloud communication
- Wide Operating temperature: -40 ~ 70°C

Introduction

For facility monitoring, distributed solar power, smart factory sector, especially cloud based applications which require a total wireless and Ethernet communication solutions, Advantech has released the ECU-1051TL RISC-based industrial communication gateway. ECU-1051TL has an open platform design with Cortex A8 processor, two 10/100 Ethernet ports and operating temperature range of -40-70°C.WithLinux operating system and open Edgelink SDK, which enable to system integrators to develop applications which precisely fit their need.

Specifications

General

- Certification .
- Mounting
- Power consumption (typical) Power Requirements

System

- CPU
- Memorv
- Indicators Storage
- SD Slot
- Watchdog
- . Real-time clock

Communication

- Serial Port
- Serial Port Speed
- .
- Drivers
- PLC Driver Support

Software

- **OS Support**

- Humidity

CE, FCC (No RED certification) Wall-Mount/ DIN-Rail 2.4W @ 24VDC

10 ~ 30 V_{DC}

TI Cortex A8, 600MHz DDR3L 256MB LEDs for Power, LAN (LINK, ACT), Programmable 512MB NAND Flash 1 x Micro-SD slot

Yes Yes

- Ethernet Port
- Wireless (Optional)

Communication Protocol

- Data Logger
- Database uplink
- Programming support

. **Configuration Tool**

Environment

- **Operating Temperature**
- Storage Temperature

Serial Port: 2 x RS232/RS485(isolation optional) RS-232/RS-485: 50 ~ 115200 bps 2 x 10/100 Base-T RJ-45 ports Interface: 1x Mini-PCIe (Full-size) Type: WIFI/Cellular/4G Signal: USB

IEC-60870-5-104 Modbus TCP/RTU MQTT FTP/HTTP/DHCP/TCP/IP 100+ PLC drivers Real-time datalogger

ODBC/ FTP Linux C, Restful API, Web service API. Event Manager

RT-Linux 3.12 Advantech Edgelink Studio

-40~70°C -40~85°C 5 ~ 95% (non-condensing)

Ordering Information

TI Cortex A8 industrial communication gateway with ECU-1051TL-R10AAE Edaelink

Cellular Solution (SIM card is not included)

- 96PD-EC25EFA
- 1750006264
- 1750005865

WIFI Solution (recommended)

- 96PD-RYUW131
- 1750000318

Storage Solution

Dimensions Unit: mm 30 21 0 ٦ 114.05 104.05 92 0 93.50 3 50 00000

AD\ANTECH **Power & Energy Solution**


All product specifications are subject to change without notice.

Last undated: 18-Dec-2020

- ATP 4G MICRO SD CARD I-GRD SLC(G) ATP 8G MICRO SD CARD I-GRD SLC(G)
- 2.4GHz Wi-Fi Full/Half Size Mini PCIe Card SMA(M) cable, 15 cm 2dBi antenna for testing, 11 cm

LTE Cat 4 Module with GNSS SMA(F) Cable, 15 cm

96FMMSDI-4G-ET-AT1 96FMMSDI-8G-ET-AT1



Dipole Antenna, 11 cm

1750006043

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Gateways category:

Click to view products by Advantech manufacturer:

Other Similar products are found below :

 BB-SG30000324-51
 MTCDT-LEU1-247A-915-EU-GB-AU
 MTCDTIP-LEU1-275L-868
 MTCDT-LEU1-246A-868-EU-GB
 WOP-2000G

 N2AE
 ESRP-PCS-ECU1251
 BB-SG30300525-42
 BB-SG30500520-42
 TRB140003000
 ECU-1051TL-R10AAE
 ECU-1251TL-R10AAE

 SGX5150202US
 SGX5150102US
 RG191
 UPS-EDGE-X70864-U01
 UPS-EDIOT-X70864-UW01
 ADAM-4572-CE
 ADAM-6717-A
 ECU

 1152-R11ABE
 EKI-1222-CE
 EKI-1224-CE
 EKI-1224CI-CE
 ICR-3211B
 ICR-3241W
 UNO-220-P4N1AE
 UNO-2271G-W1032GE
 WISE

 3310-D100L1E
 WISE-3610ILS-51A1N
 WISE-6610-N100-A
 AKX00016
 MESR901
 MESR902T
 X2-HMU-EM-B
 X4-Z1U-B101-A

 SGX5150020US
 SGX51501M2ES
 SGX51502N5ES
 XPC240200B-02
 XPC240200S-02
 XPC240400S-02
 XPC250100S-02

 WSDA-2000
 WSDA-200-USB
 1120780001
 1120780002
 MTCDT-246A-868-EU-GB
 MTCDT-247A-868-EU-GB
 MTCDT-L4N1-247A

 915-US
 ARGN-H
 MTCDT-L4N1-247A MTCDT-L4N1-247A MTCDT-L4N1-247A