

EKI-1528 / I / TI / N

EKI-1526 / I / TI / N

8-port RS-232/422/485 Serial Device Server

16-port RS-232/422/485 Serial Device Server



EKI-1528

EKI-1526



Features

- 8 or 16-port RS-232/422/485 serial communication
- Provides 2 x 10/100/1000 Mbps Ethernet ports for LAN redundancy
- Supports up to 976.5 kbps, and any baud rate setting
- Provides COM port redirection (Virtual COM), TCP and UDP operation modes
- Provides rich configuration methods: Windows utility, Telnet console, Web Browser, and serial console
- Built-in 15 KV ESD protection for all serial signals
- SNMP MIB-II for network management
- Built-in buzzer for easy location
- Standard 1U rackmount size
- Rear wiring
- Automatic RS-485 data flow control
- "I" models support a wide operating temperature

Introduction

The EKI-1528 and EKI-1526 are industrial-grade network-based serial device servers for connecting up to 8 or 16 serial RS-232/422/485 devices, such as CNCs, PLCs, scales and scanners, directly to a TCP/IP network. The EKI-1528 and EKI-1526 feature two independent Ethernet ports and MAC addresses to provide a redundant network mechanism to guarantee Ethernet network reliability. The EKI-1528 and EKI-1526 provide a simple and cost-effective way to bring the advantages of remote management and data accessibility to thousand of devices that can't connect to an Ethernet network. The EKI-1528 and EKI-1526 offer multiple ways to configure through Windows utility, Web Browser, serial console or Telnet console, these methods make it easy manage many EKI-1528 and EKI-1526 or serial devices on your network.

Specifications

Ethernet Communications

- **Compatibility** IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- **Speed** 10/100/1000 Mbps, auto MDI/MDIX
- **No. of Ports** 2
- **Port Connector** 8-pin RJ45
- **Protection** Built-in 1.5 KV magnetic isolation

Serial Communications

- **Port Type** RS-232/422/485, software selectable
- **No. of Ports** EKI-1528/EKI-1528I/EKI-1528TI/EKI-1528N: 8
EKI-1526/EKI-1526I/EKI-1526TI/EKI-1526N: 16
- **Port Connector** DB9 male or 8-pin RJ45
- **Data Bits** 5, 6, 7, 8
- **Stop Bits** 1, 1.5, 2
- **Parity** None, Odd, Even, Space, Mark
- **Flow Control** XON/XOFF, RTS/CTS, DTR/DSR
- **Baud Rate** 50 bps ~ 976.5 kbps, any baud rate setting
16 ports up to 230.4 kbps simultaneously
- **Serial Signals** RS-232: TxD, RxD, CTS, RTS, DTR, DSR, DCD, GND, RI
RS-422: TxD+, TxD-, RxD+, RxD-, GND
RS-485: Data+, Data-, GND
- **Protection** 15 KV ESD for all signals

Software

- **Driver Support** 32-bit/64-bit Windows 2000/XP/Vista/7/ 8/8.1/10, Windows Server 2003/2008/2012, and Linux
- **Utility Software** Advantech EKI Device Configuration Utility
- **Operation Modes** COM port redirection mode (Virtual COM)
TCP/UDP server (polling) mode
TCP/UDP client (event handling) mode
Pair connection (peer to peer) mode
RFC2217 mode

- **Configuration** Windows utility, Telnet console, Web Browser, serial console
- **Protocols** ARP, ICMP, IPv6, TCP, UDP, BOOTP/DHCP Client, Auto IP, Telnet, SNMP, HTTP, DNS, SMTP, NTP
- **Management** SNMP MIB-II

Mechanics

- **Dimensions (W x H x D)** 438 x 43.6 x 259.2 mm (17.24" x 1.71" x 10.2")
- **Enclosure** SECC chassis
- **Mounting** Rack

General

- **LED Indicators** System: Power, System Status
LAN: Speed, Link/Active
Serial: Tx, Rx
- **Alert Tools** Built-in buzzer and RTC (real time clock)
- **Reboot Trigger** Built-in WDT and push button for hardware reboot

Power Requirements

- **Power Input** EKI-1528(I)/EKI-1526(I): 100 ~ 240 V_{AC}, 50 ~ 60 Hz
EKI-1528T(I)/EKI-1526T(I): 12 ~ 48 V_{DC}, Terminal Block
- **Power Consumption** 5.6 W

Environment

- **Operating Temperature** -10 ~ 60°C (14 ~ 140°F)
"I" Model: -40 ~ 75°C (-40 ~ 167°F)
- **Storage Temperature** -40 ~ 85 °C (-40 ~ 185 °F)
- **Operating Humidity** 10 ~ 95% RH


Regulatory Approvals

- **EMC** CE, FCC Part 15 Subpart B (Class A)


Dimensions

Unit: mm [inch]


EKI-1526/1526I




EKI-1526T/1526TI



EKI-1528/1528I




EKI-1528T/1528TI




Dimensions

Unit: mm [inch]

EKI-1526N



EKI-1528N



Ordering Information

- **EKI-1528** 8-port RS-232/422/485 Serial Device Server
- **EKI-1526** 16-port RS-232/422/485 Serial Device Server
- **EKI-1528T-VDC** 8-port RS-232/422/485 Serial Device Server w/ DC Input
- **EKI-1526T-VDC** 16-port RS-232/422/485 Serial Device Server w/ DC Input
- **EKI-1528I** 8-port RS-232/422/485 Serial Device Server W/T
- **EKI-1526I** 16-port RS-232/422/485 Serial Device Server W/T
- **EKI-1528TI-VDC** 8-port RS-232/422/485 Serial Device Server w/ DC W/T Input
- **EKI-1526TI-VDC** 16-port RS-232/422/485 Serial Device Server w/ DC W/T Input
- **EKI-1528N** 8-port RS-232/422/485 Serial Device Server with RJ45 Connector
- **EKI-1526N** 16-port RS-232/422/485 Serial Device Server with RJ45 Connector

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Servers](#) category:

Click to view products by [Advantech](#) manufacturer:

Other Similar products are found below :

[70001611](#) [AGS-913I-R11A1E](#) [EDSOR04P-01](#) [SB800EX-TDT-IR](#) [SB800EX-TDD-IR](#) [SLB882KIT-20P](#) [SLC82321201S](#) [SLC80322201G](#)
[70002323](#) [70002268](#) [70001951](#) [70001931](#) [70001949](#) [70002329](#) [DS-520AN-US](#) [EKI-1526N-CE](#) [20-101-1318](#) [70001862](#) [ASB-5402-RM16-](#)
[GLB](#) [ASB-5402-RM00-GLB](#) [ASB-5402-RM04-OUS](#) [ASB-5402-RM06-GLB](#) [ASB-5402-RME4-GLB](#) [IT01-M100-GLB](#) [IT16-1002](#) [IT48-](#)
[1002](#) [EDS00812N-01](#) [EDS01612N-02](#) [EDS03212N-02](#) [PEN100100A-01-IT](#) [SLC80082201S](#) [SLC80161201S](#) [SLC80162211S](#)
[SLC80322401S](#) [SLC80081201S](#) [SLC80162201S](#) [SLC80481201S](#) [UD110000B-01](#) [XPS1002CP-01-S](#) [Pioneer-FreedomBox-HSK-US](#)
[WIZ1000](#)